

Takeshi Morita

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/10541379/publications.pdf>

Version: 2024-02-01

60
papers

1,959
citations

279798

23
h-index

254184

43
g-index

60
all docs

60
docs citations

60
times ranked

1014
citing authors

#	ARTICLE	IF	CITATIONS
1	Miniature piezoelectric motors. <i>Sensors and Actuators A: Physical</i> , 2003, 103, 291-300.	4.1	280
2	Stepping piezoelectric actuators with large working stroke for nano-positioning systems: A review. <i>Sensors and Actuators A: Physical</i> , 2019, 292, 39-51.	4.1	173
3	A micro ultrasonic motor using a micro-machined cylindrical bulk PZT transducer. <i>Sensors and Actuators A: Physical</i> , 2006, 127, 131-138.	4.1	126
4	A cylindrical shaped micro ultrasonic motor utilizing PZT thin film (1.4 mm in diameter and 5.0 mm) Tj ETQq0 0 0 rgBT /Overlock 10 Tf 5	4.1	125
5	An ultrasonic micromotor using a bending cylindrical transducer based on PZT thin film. <i>Sensors and Actuators A: Physical</i> , 1995, 50, 75-80.	4.1	96
6	Single Process to Deposit Lead Zirconate Titanate (PZT) Thin Film by a Hydrothermal Method. <i>Japanese Journal of Applied Physics</i> , 1997, 36, 2998-2999.	1.5	95
7	Resonant-type Smooth Impact Drive Mechanism (SIDM) actuator using a bolt-clamped Langevin transducer. <i>Ultrasonics</i> , 2012, 52, 75-80.	3.9	95
8	Cylindrical Micro Ultrasonic Motor Utilizing Bulk Lead Zirconate Titanate (PZT). <i>Japanese Journal of Applied Physics</i> , 1999, 38, 3347-3350.	1.5	76
9	(K,Na)NbO ₃ lead-free piezoelectric ceramics synthesized from hydrothermal powders. <i>Materials Letters</i> , 2010, 64, 125-128.	2.6	58
10	Three DOF parallel link mechanism utilizing smooth impact drive mechanism. <i>Precision Engineering</i> , 2002, 26, 289-295.	3.4	56
11	Ferroelectric properties of an epitaxial lead zirconate titanate thin film deposited by a hydrothermal method below the Curie temperature. <i>Applied Physics Letters</i> , 2004, 84, 5094-5096.	3.3	52
12	A cylindrical micro-ultrasonic motor (stator transducer size: 1.4 mm in diameter and 5.0 mm long). <i>Ultrasonics</i> , 2000, 38, 33-36.	3.9	47
13	A hydrothermally deposited epitaxial lead titanate thin film on strontium ruthenium oxide bottom electrode. <i>Applied Physics Letters</i> , 2004, 85, 2331-2333.	3.3	45
14	A miniaturized resonant-type smooth impact drive mechanism actuator. <i>Sensors and Actuators A: Physical</i> , 2012, 178, 188-192.	4.1	41
15	Resonant-type smooth impact drive mechanism actuator using lead-free piezoelectric material. <i>Sensors and Actuators A: Physical</i> , 2018, 274, 179-183.	4.1	38
16	Piezoelectric Materials Synthesized by the Hydrothermal Method and Their Applications. <i>Materials</i> , 2010, 3, 5236-5245.	2.9	35
17	Ferroelectric property of an epitaxial lead zirconate titanate thin film deposited by a hydrothermal method. <i>Journal of Materials Research</i> , 2004, 19, 1862-1868.	2.6	32
18	Resonant-Type Smooth Impact Drive Mechanism Actuator Operating at Lower Input Voltages. <i>Japanese Journal of Applied Physics</i> , 2013, 52, 07HE05.	1.5	32

#	ARTICLE	IF	CITATIONS
19	Shape memory piezoelectric actuator. Applied Physics Letters, 2007, 90, 082909.	3.3	31
20	Synthesis of Nondoped Potassium Niobate Ceramics by Ultrasonic Assisted Hydrothermal Method. Japanese Journal of Applied Physics, 2008, 47, 7673-7677.	1.5	30
21	Piezoelectric property of an epitaxial lead titanate thin film deposited by the hydrothermal method. Applied Physics Letters, 2006, 88, 112908.	3.3	29
22	Wireguide driving actuator using resonant-type smooth impact drive mechanism. Sensors and Actuators A: Physical, 2015, 230, 40-44.	4.1	27
23	Nondoped Potassium Niobate Ceramics Synthesized by Hydrothermal Method with Optimum Temperature Condition. Japanese Journal of Applied Physics, 2008, 47, 3824-3828.	1.5	26
24	Rotational feedthrough using an ultrasonic motor and its performance in ultra high vacuum conditions. Vacuum, 2003, 70, 53-57.	3.5	24
25	Resonant-Type Smooth Impact Drive Mechanism Actuator with Two Langevin Transducers. Advanced Robotics, 2012, 26, 277-290.	1.8	23
26	Resonance frequency ratio control with an additional inductor for a miniaturized resonant-type SIDM actuator. Sensors and Actuators A: Physical, 2014, 214, 142-148.	4.1	21
27	Rotational feedthrough using ultrasonic motor for high vacuum condition. Vacuum, 2002, 65, 85-90.	3.5	19
28	Dynamic preload control of traveling wave rotary ultrasonic motors for energy efficient operation. Japanese Journal of Applied Physics, 2019, 58, SGGD04.	1.5	18
29	Opposing preloads type ultrasonic linear motor with quadruped stator. Sensors and Actuators A: Physical, 2020, 301, 111764.	4.1	18
30	Improved Process for Hydrothermal Lead-Free Piezoelectric Powders and Performances of Sintered ($K_{0.48}Na_{0.52}$) NbO_3 Ceramics. Japanese Journal of Applied Physics, 2011, 50, 07HC01.	1.5	18
31	Improved Process for Hydrothermal Lead-Free Piezoelectric Powders and Performances of Sintered ($K_{0.48}Na_{0.52}$) NbO_3 Ceramics. Japanese Journal of Applied Physics, 2011, 50, 07HC01.	1.5	15
32	Utilization of Permittivity Memory Effect for Position Detection of Shape Memory Piezoelectric Actuator. Japanese Journal of Applied Physics, 2008, 47, 217-219.	1.5	13
33	Ultrasonically assisted hydrothermal synthesis of polycrystalline PZT thin film on titanium substrate. IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, 2009, 56, 9-13.	3.0	12
34	Noncontact Operation of a Miniature Cycloid Motor by Magnetic Force. IEEE/ASME Transactions on Mechatronics, 2013, 18, 1563-1571.	5.8	12
35	Rod drive type ultrasonic linear motor with quadruped stator. Japanese Journal of Applied Physics, 2020, 59, SKKD13.	1.5	11
36	Study on optimizing ultrasonic irradiation period for thick polycrystalline PZT film by hydrothermal method. Ultrasonics, 2013, 53, 837-841.	3.9	10

#	ARTICLE	IF	CITATIONS
37	Optimum reaction conditions for lead zirconate titanate thick film deposition by ultrasound-assisted hydrothermal method. Japanese Journal of Applied Physics, 2016, 55, 07KC05.	1.5	10
38	Dynamic resonant frequency control of ultrasonic transducer for stabilizing resonant state in wide frequency band. Japanese Journal of Applied Physics, 2017, 56, 07JE08.	1.5	10
39	Piezoelectric nonlinear vibration focusing on the second-harmonic vibration mode. Ultrasonics, 2018, 82, 233-238.	3.9	10
40	Double-parabolic-reflectors acoustic waveguides for high-power medical ultrasound. Scientific Reports, 2019, 9, 18493.	3.3	10
41	Estimation of Resolution and Contact Force of a Longitudinally Vibrating Touch Probe Sensor Using Lead Zirconate Titanate (PZT) Thin-Film Vibrator. Japanese Journal of Applied Physics, 2001, 40, 3646-3651.	1.5	9
42	Effect of Deposition Time on Film Thickness and Their Properties for Hydrothermally-Grown Epitaxial KNbO_3 Thick Films. Japanese Journal of Applied Physics, 2010, 49, 07HF01.	1.5	9
43	Nonlinear coefficients in lead-free $\text{CuO}^{2+}(\text{K,Na})\text{NbO}_3$ transducers. Japanese Journal of Applied Physics, 2015, 54, 07HC01.	1.5	8
44	A Hydrothermally Deposited Epitaxial PbTiO_3 Thin Film on SrRuO_3 Bottom Electrode for the Ferroelectric Ultra-High Density Storage Medium. Integrated Ferroelectrics, 2004, 64, 247-257.	0.7	7
45	Simplified determination of nonlinear coefficients in piezoelectric transducers. Japanese Journal of Applied Physics, 2015, 54, 10ND01.	1.5	6
46	Dynamic control of the resonant frequency of ultrasonic transducer. Sensors and Actuators A: Physical, 2017, 262, 64-67.	4.1	6
47	Ultrasonic-assisted hydrothermal deposition of ferroelectric PbZrO_3 thin film on NiTi-based superelastic shape memory alloys. Journal of Electroceramics, 2012, 28, 45-52.	2.0	3
48	Dynamic resonant frequency control system of ultrasonic transducer for non-sinusoidal waveform excitation. Sensors and Actuators A: Physical, 2021, 332, 113124.	4.1	3
49	Robust Speed Control of Ultrasonic Motors Based on Deep Reinforcement Learning of a Lyapunov Function. IEEE Access, 2022, 10, 46895-46910.	4.2	3
50	Domain-orientation-controlled potassium niobate family piezoelectric materials with hydrothermal powders. IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, 2014, 61, 1593-1598.	3.0	2
51	Improvement of miniaturized resonant type SIDM actuator. , 2012, , .		1
52	Thick KNbO_3 films deposited by ultrasonic-assisted hydrothermal method. Acoustical Science and Technology, 2015, 36, 262-264.	0.5	1
53	Characterization of Shape Memory Piezoelectric Actuator and Investigation of the Origin of the Imprint Electrical Field. , 2010, , 195-200.		1
54	Piezoelectric Properties of Li-Doped $(\text{K}_{0.48}\text{Na}_{0.52})\text{NbO}_3$ Ceramics Synthesized Using Hydrothermally-Derived KNbO_3 and NaNbO_3 Fine Powders. Japanese Journal of Applied Physics, 2012, 51, 09MD08.	1.5	1

#	ARTICLE	IF	CITATIONS
55	Ferroelectric property of an epitaxial lead zirconate titanate thin film deposited by a hydrothermal method. Materials Research Society Symposia Proceedings, 2003, 784, 11311.	0.1	0
56	Perfectly c-axis oriented epitaxial lead titanate thin film deposited by a hydrothermal method for a data storage medium. Materials Research Society Symposia Proceedings, 2004, 830, 171.	0.1	0
57	Polycrystalline PZT film on porous Ti substrate synthesized by Ultrasonic Assisted Hydrothermal Method. , 2012, , .		0
58	Piezoelectric applications of hydrothermal lead-free $(K_{0.48}Na_{0.52})NbO_3$ ceramics. , 2012, , .		0
59	Multi Degrees of Freedom Forceps for Ultrasonically Activated Device using Ultrasonic Motor. Procedia CIRP, 2013, 5, 70-73.	1.9	0
60	Shape Memory Piezoelectric Actuator and Various Memories in Ferroelectric Materials. , 2010, , 141-152.		0