Minghao Qi

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/11104666/publications.pdf Version: 2024-02-01



| # | Article | IF | CITATIONS |
|----|---|------|-----------|
| 1 | Physics-informed recurrent neural network for time dynamics in optical resonances. Nature Computational Science, 2022, 2, 169-178. | 8.0 | 7 |
| 2 | Switching dynamics of dark-pulse Kerr frequency comb states in optical microresonators. Physical Review A, 2021, 103, . | 2.5 | 30 |
| 3 | InP high power monolithically integrated widely tunable laser and SOA array for hybrid integration. Optics Express, 2021, 29, 3490. | 3.4 | 6 |
| 4 | Optical Dual-Comb Vernier Division of an Octave-Spanning Kerr Microcomb. , 2021, , . | | 1 |
| 5 | Nano-Optic Broadband Power Splitter Design via Cycle-Consistent Adversarial Deep Learning. , 2021, , . | | 2 |
| 6 | Optical Division of an Octave-Spanning Comb on an All-Silicon Nitride Platform. , 2021, , . | | 0 |
| 7 | Generative Deep Learning Model for Inverse Design of Integrated Nanophotonic Devices. Laser and Photonics Reviews, 2020, 14, 2000287. | 8.7 | 47 |
| 8 | Exceptional coupling in photonic anisotropic metamaterials for extremely low waveguide crosstalk. Optica, 2020, 7, 881. | 9.3 | 50 |
| 9 | High-dimensional optical quantum logic in large operational spaces. Npj Quantum Information, 2019, 5, | 6.7 | 92 |
| 10 | Hot-Cavity Spectroscopy of Dark Pulse Kerr Combs in Microresonators. , 2019, , . | | 0 |
| 11 | Kerr Combs for Stimulated Brillouin Scattering Mitigation in Long-Haul Analog Optical Links. Journal of Lightwave Technology, 2019, 37, 5773-5779. | 4.6 | 5 |
| 12 | Switching Dynamics of Dark Solitons in Kerr Microresonators. , 2019, , . | | 0 |
| 13 | Dissipative cnoidal waves (Turing rolls) and the soliton limit in microring resonators. Optica, 2019, 6, 1220. | 9.3 | 42 |
| 14 | Characterizing pump line phase offset of a single-soliton Kerr comb by dual comb interferometry. Optics Letters, 2019, 44, 1460. | 3.3 | 3 |
| 15 | Microcomb-Based True-Time-Delay Network for Microwave Beamforming With Arbitrary Beam Pattern Control. Journal of Lightwave Technology, 2018, 36, 2312-2321. | 4.6 | 68 |
| 16 | Kerr Combs for Single-Span Long-Haul Analog Optical Links. , 2018, , . | | 2 |
| 17 | Observation of Breathing Dark Pulses in Normal Dispersion Optical Microresonators. Physical Review Letters, 2018, 121, 257401. | 7.8 | 23 |
| 18 | Controlling evanescent waves using silicon photonic all-dielectric metamaterials for dense integration. Nature Communications, 2018, 9, 1893. | 12.8 | 140 |

4

| # | Article | IF | CITATIONS |
|----|--|------|-----------|
| 19 | 50-GHz-spaced comb of high-dimensional frequency-bin entangled photons from an on-chip silicon nitride microresonator. Optics Express, 2018, 26, 1825. | 3.4 | 134 |
| 20 | High-order coherent communications using mode-locked dark-pulse Kerr combs from microresonators. Nature Communications, 2018, 9, 1598. | 12.8 | 167 |
| 21 | Two-qudit deterministic optical quantum logic in a single photon. , 2018, , . | | 1 |
| 22 | Stability of cnoidal wave frequency combs in microresonators. , 2018, , . | | 1 |
| 23 | Kerr combs from normal and anomalous dispersion silicon nitride microresonators. , 2017, , . | | 0 |
| 24 | Second-harmonic-assisted four-wave mixing in chip-based microresonator frequency comb generation. Light: Science and Applications, 2017, 6, e16253-e16253. | 16.6 | 83 |
| 25 | Microresonator Kerr frequency combs with high conversion efficiency. Laser and Photonics Reviews, 2017, 11, 1600276. | 8.7 | 153 |
| 26 | Dispersion engineering and frequency comb generation in thin silicon nitride concentric microresonators. Nature Communications, 2017, 8, 372. | 12.8 | 108 |
| 27 | Long-haul coherent communications using microresonator-based frequency combs. Optics Express, 2017, 25, 26678. | 3.4 | 40 |
| 28 | Persistent energy–time entanglement covering multiple resonances of an on-chip biphoton frequency comb. Optica, 2017, 4, 655. | 9.3 | 61 |
| 29 | Spatial mode-interaction induced single soliton generation in microresonators. Optica, 2017, 4, 1011. | 9.3 | 74 |
| 30 | Soliton repetition rate in a silicon-nitride microresonator. Optics Letters, 2017, 42, 759. | 3.3 | 37 |
| 31 | Normal Dispersion High Conversion Efficiency Kerr Comb with 50 GHz Repetition Rate. , 2017, , . | | 2 |
| 32 | High-Efficiency WDM Sources Based on Microresonator Kerr Frequency Combs. , 2017, , . | | 2 |
| 33 | Direct soliton generation in microresonators. Optics Letters, 2017, 42, 2519. | 3.3 | 60 |
| 34 | Frequency Noise of a Normal Dispersion Microresonator-based Frequency Comb. , 2017, , . | | 0 |
| 35 | Directly stabilized solitons in silicon-nitride microresonators. , 2017, , . | | 0 |
| | | | |

36 Double slot fiber-to-chip coupler using direct strip-slot mode coupling. , 2017, , .

| # | Article | IF | CITATIONS |
|----|---|-----|-----------|
| 37 | Dispersion immune change of soliton repetition rate in a silicon-nitride microresonator. , 2017, , . | | 0 |
| 38 | High-Q silicon nitride microresonators exhibiting low-power frequency comb initiation. Optica, 2016, 3, 1171. | 9.3 | 148 |
| 39 | Comparison and analysis on single-layer Si fiber-to-chip edge couplers with different taper tips. , 2016, , | | 4 |
| 40 | Broadband second-harmonic phase-matching in dispersion engineered slot waveguides. Optics Express, 2016, 24, 773. | 3.4 | 16 |
| 41 | Observation of Fermi-Pasta-Ulam Recurrence Induced by Breather Solitons in an Optical Microresonator. Physical Review Letters, 2016, 117, 163901. | 7.8 | 116 |
| 42 | Intracavity characterization of micro-comb generation in the single-soliton regime. Optics Express, 2016, 24, 10890. | 3.4 | 101 |
| 43 | Controlled and Stabilized Light–Matter Interaction in Graphene: Plasmonic Film with Largeâ€Scale 10â€nm Lithography. Advanced Optical Materials, 2016, 4, 1811-1823. | 7.3 | 28 |
| 44 | Coherent Kerr frequency comb generation in microresonators with χ(2)and χ(3)nonlinearities. , 2016, , . | | 0 |
| 45 | Normal-dispersion microresonator Kerr frequency combs. Nanophotonics, 2016, 5, 244-262. | 6.0 | 44 |
| 46 | Thermal tuning of Kerr frequency combs in silicon nitride microring resonators. Optics Express, 2016, 24, 687. | 3.4 | 118 |
| 47 | Strip-slot direct mode coupler. Optics Express, 2016, 24, 6532. | 3.4 | 22 |
| 48 | Long-Haul Coherent Transmission Using a Silicon Nitride Microresonator-Based Frequency Comb as WDM Source. , 2016, , . | | 3 |
| 49 | Frequency Comb Generation in 300 nm-Thick Si3N4 Concentric-Ring-Resonators. , 2016, , . | | 1 |
| 50 | Reciprocal Waveforms at Through and Drop Ports in Microcomb Generation. , 2016, , . | | 0 |
| 51 | Offset Frequency Tuning of a Microcomb with an Integrated Microheater. , 2016, , . | | 0 |
| 52 | Anomalous Dispersion in 300 nm-Thick Si3N4 Concentric-Ring-Resonators. , 2016, , . | | 0 |
| 53 | Measurement of Hot-cavity Detuning in Microcomb Generation Using Fiber Comb Spectroscopy. , 2016, , | | 0 |
| 54 | Experimental Characterization of Pump Power and Detuning in Microresonator Frequency Combs. , 2016, , . | | 1 |

Minghao Qi

| # | Article | IF | CITATIONS |
|----|--|------|-----------|
| 55 | Intracavity Characterization of Micro-comb Generation in the Single Soliton Regime. , 2016, , . | | 0 |
| 56 | Mode-evolution-based polarization rotation and coupling between silicon and hybrid plasmonic waveguides. Scientific Reports, 2015, 5, 18378. | 3.3 | 26 |
| 57 | Normalâ€dispersion microcombs enabled by controllable mode interactions. Laser and Photonics Reviews, 2015, 9, L23. | 8.7 | 159 |
| 58 | Dispersion engineered hetero-slot waveguides for broadband on-chip second-harmonic phase-matching. , 2015, , . | | 0 |
| 59 | Nonreciprocal transmission through a silicon optical diode. , 2015, , . | | 0 |
| 60 | Reconfigurable radio-frequency arbitrary waveforms synthesized in a silicon photonic chip. Nature Communications, 2015, 6, 5957. | 12.8 | 107 |
| 61 | Mode-locked Microresonator Combs in the Normal Dispersion Region. , 2015, , . | | 1 |
| 62 | Polarization rotation and coupling between silicon waveguide and hybrid plasmonic waveguide. Optics Express, 2015, 23, 9968. | 3.4 | 31 |
| 63 | A silicon-on-insulator polarization diversity scheme in the mid-infrared. Optics Express, 2015, 23, 15029. | 3.4 | 22 |
| 64 | Mode-locked dark pulse Kerr combs in normal-dispersion microresonators. Nature Photonics, 2015, 9, 594-600. | 31.4 | 459 |
| 65 | Mode-Locked and Repetition-Rate-Tunable Comb Generation Using Dual Coupled Microrings. , 2015, , . | | 0 |
| 66 | High-Q Silicon Nitride Microresonator for Low Power Frequency Comb Initiation at Normal Dispersion Regime. , 2015, , . | | 3 |
| 67 | Spectral broadening of Kerr Frequency Combs Generated from a Normal Dispersion Silicon Nitride Microresonator. , 2015, , . | | 1 |
| 68 | Frequency Comb-enhanced Coupling in Silicon Nitride Microresonators. , 2015, , . | | 0 |
| 69 | Improved performance in Si nanowire AWG routers based on a comparative study of optimization techniques. , 2014, , . | | 0 |
| 70 | Ultrabroadband Silicon-on-Insulator Polarization Beam Splitter Based on Cascaded Mode-Sorting Asymmetric Y-Junctions. IEEE Photonics Journal, 2014, 6, 1-8. | 2.0 | 7 |
| 71 | A fabrication-tolerant SOI polarization splitter-rotator with cascaded MMI couplers and an assisted bi-level taper. , 2014, , . | | 0 |
| 72 | First Demonstration of a Tunable Single-Bandpass Photonic Radiofrequency Filter Based on Optical Frequency Comb from a Microring. , 2014, , . | | 5 |

Minghao Qi

| # | Article | IF | CITATIONS |
|----|---|------|-----------|
| 73 | Bandwidth scaling of a phase-modulated continuous-wave comb through four-wave mixing in a silicon nano-waveguide. Optics Letters, 2014, 39, 6478. | 3.3 | 5 |
| 74 | Investigation of mode coupling in normal-dispersion silicon nitride microresonators for Kerr frequency comb generation. Optica, 2014, 1, 137. | 9.3 | 186 |
| 75 | Design of a SiO_2 top-cladding and compact polarization splitter-rotator based on a rib directional coupler. Optics Express, 2014, 22, 4137. | 3.4 | 52 |
| 76 | Low-loss and low-crosstalk 8 × 8 silicon nanowire AWG routers fabricated with CMOS technology. Optics Express, 2014, 22, 9395. | 3.4 | 75 |
| 77 | Copper nanorod array assisted silicon waveguide polarization beam splitter. Optics Express, 2014, 22, 9508. | 3.4 | 31 |
| 78 | Drop-port study of microresonator frequency combs: power transfer, spectra and time-domain characterization: erratum. Optics Express, 2014, 22, 12148. | 3.4 | 0 |
| 79 | One-way transmission of 10 Gbps data through a silicon optical diode based on nonreciprocal resonance reshaping. Optics Express, 2014, 22, 25739. | 3.4 | 4 |
| 80 | Proposal for fabrication-tolerant SOI polarization splitter-rotator based on cascaded MMI couplers and an assisted bi-level taper. Optics Express, 2014, 22, 27869. | 3.4 | 46 |
| 81 | Large-scale nanoshaping of ultrasmooth 3D crystalline metallic structures. Science, 2014, 346, 1352-1356. | 12.6 | 153 |
| 82 | Novel ultra-broadband polarization splitter-rotator based on mode-evolution tapers and a mode-sorting asymmetric Y-junction. Optics Express, 2014, 22, 13565. | 3.4 | 73 |
| 83 | An all-silicon optical diode. , 2014, , . | | 0 |
| 84 | Programmable Single-Bandpass Photonic RF Filter Based on Kerr Comb from a Microring. Journal of Lightwave Technology, 2014, 32, 3557-3565. | 4.6 | 136 |
| 85 | Frequency Combs from Normal Dispersion Silicon Nitride Microresonators. , 2014, , . | | 0 |
| 86 | Summary of the 2011 Dielectric Laser Accelerator Workshop. Nuclear Instruments and Methods in Physics Research, Section A: Accelerators, Spectrometers, Detectors and Associated Equipment, 2014, 734, 51-59. | 1.6 | 12 |
| 87 | Rapidly Reconfigurable RF Arbitrary Waveform Synthesis using a CMOS Silicon Photonic Chip. , 2014, , . | | 0 |
| 88 | Retrieving the Complex Intracavity Pump Field of a Kerr Comb from the Through Port Data. , 2014, , . | | 0 |
| 89 | Investigation of Mode Interaction in Optical Microresonators for Kerr Frequency Comb Generation. , 2014, , . | | 1 |
| 90 | Metal Nanorods Array Embedded Silicon Waveguide Polarization Beam Splitter. , 2014, , . | | 0 |

Μινςμαό Qi

| # | Article | IF | CITATIONS |
|-----|---|------|-----------|
| 91 | Tunable Frequency Comb Generation from a Microring with a Thermal Heater. , 2014, , . | | 2 |
| 92 | A Hollowâ€Core Optical Cavity Built in a Three‣ayer Silicon Photonic Crystal. Advanced Optical Materials, 2013, 1, 740-746. | 7.3 | 1 |
| 93 | Enhanced Photon Management of Thinâ€Film Silicon Solar Cells Using Inverse Opal Photonic Crystals with 3D Photonic Bandgaps. Advanced Optical Materials, 2013, 1, 692-698. | 7.3 | 32 |
| 94 | Ultra high optical nonreciprocity using silicon microring resonators. , 2013, , . | | 0 |
| 95 | Photonic Crystals: Enhanced Photon Management of Thin-Film Silicon Solar Cells Using Inverse Opal Photonic Crystals with 3D Photonic Bandgaps (Advanced Optical Materials 10/2013). Advanced Optical Materials, 2013, 1, 680-680. | 7.3 | 0 |
| 96 | An all-silicon optical diode transmitting 10 Gbps data. , 2013, , . | | 0 |
| 97 | A Theoretical Model for an Optical Diode Built With Nonlinear Silicon Microrings. Journal of Lightwave Technology, 2013, 31, 313-321. | 4.6 | 38 |
| 98 | Resistless Nanoimprinting in Metal for Plasmonic Nanostructures. Small, 2013, 9, 3778-3783. | 10.0 | 27 |
| 99 | Optical Diodes and Transistors on a Silicon Chip. , 2013, , . | | 0 |
| 100 | Silicon optical diode with 40ÂdB nonreciprocal transmission. Optics Letters, 2013, 38, 1259. | 3.3 | 87 |
| 101 | Nanoimprinted plasmonic nanocavity arrays. Optics Express, 2013, 21, 15081. | 3.4 | 26 |
| 102 | Drop-port study of microresonator frequency combs: power transfer, spectra and time-domain characterization. Optics Express, 2013, 21, 22441. | 3.4 | 40 |
| 103 | Far-field polarization characterization of the fundamental modes of a strip silicon waveguide. Optics Letters, 2013, 38, 4785. | 3.3 | 1 |
| 104 | Frequency comb-induced nonlinear coupling effect in microresonators. , 2013, , . | | 0 |
| 105 | Rapid and Lowâ€Cost Prototyping of 3D Nanostructures with Multi‣ayer Hydrogen Silsesquioxane Scaffolds. Small, 2013, 9, 4237-4242. | 10.0 | 9 |
| 106 | Neuron-Like Functionality of a Silicon Optical Transistor. , 2013, , . | | 0 |
| 107 | Generation of a 96 GHz Pulse Train through On-Chip Pulse Shaping of an Optical Frequency Comb. , 2013, , . | | 0 |
| 108 | One-Way 10 Gbps Data Transmission through a Silicon Optical Diode. , 2013, , . | | 0 |

Μινςμαό Qi

| # | Article | IF | CITATIONS |
|-----|--|------|-----------|
| 109 | Radio-Frequency Arbitrary Waveform Generation with a Programmable SiN Spectral Shaper. , 2013, , . | | 0 |
| 110 | A CMOS Photonic Chip for Rapidly Reconfigurable RF Arbitrary Waveform Generation. , 2013, , . | | 0 |
| 111 | Design of a compact mode and polarization converter in three-dimensional photonic crystals. Optics Express, 2012, 20, 20356. | 3.4 | 8 |
| 112 | Direct fabrication of silicon photonic devices on a flexible platform and its application for strain sensing. Optics Express, 2012, 20, 20564. | 3.4 | 59 |
| 113 | On-chip wavelength-routed photonic networks with comb switches. , 2012, , . | | 5 |
| 114 | Nonreciprocal transmission of 10 Gbps OOK data through an all-silicon passive optical diode. , 2012, , 703-704. | | 0 |
| 115 | Efficient Silicon-on-Insulator Polarization Rotator based on Mode Evolution. , 2012, , . | | 1 |
| 116 | An All-Silicon Passive Optical Diode. Science, 2012, 335, 447-450. | 12.6 | 621 |
| 117 | A Silicon Optical Transistor. , 2012, 2012, . | | 5 |
| 118 | An All-Silicon Passive Optical Diode. , 2012, , . | | 1 |
| 119 | 40 dB Optical Nonreciprocal Transmission on a Silicon Chip. , 2012, , . | | 0 |
| 120 | A Hollow-core Cavity in Three-layer Photonic Crystals. , 2012, , . | | 0 |
| 121 | Selective Contact Anneal Effects on Indium Oxide Nanowire Transistors using Femtosecond Laser. Journal of Physical Chemistry C, 2011, 115, 17147-17153. | 3.1 | 13 |
| 122 | Control of Current Saturation and Threshold Voltage Shift in Indium Oxide Nanowire Transistors with Femtosecond Laser Annealing. ACS Nano, 2011, 5, 1095-1101. | 14.6 | 32 |
| 123 | A Contra-Directional Coupling based Waveguide Mode Converter in 3D Photonic Crystals. , 2011, , . | | 0 |
| 124 | Ultrabroad-bandwidth arbitrary radiofrequency waveform generation with a silicon photonic chip-based spectral shaper. Nature Photonics, 2010, 4, 117-122. | 31.4 | 335 |
| 125 | Radio-frequency waveform generation with a CMOS compatible on-chip spectral shaper. , 2010, , . | | 0 |
| 126 | A Taper to Reduce the Straight-to-Bend Transition Loss in Compact Silicon Waveguides. IEEE Photonics Technology Letters, 2010, 22, 1174-1176. | 2.5 | 12 |

| # | Article | IF | CITATIONS |
|-----|---|-----|-----------|
| 127 | Eight-channel reconfigurable microring filters with tunable frequency, extinction ratio and bandwidth. Optics Express, 2010, 18, 18067. | 3.4 | 53 |
| 128 | On-chip programmable radio-frequency waveform generation. , 2010, , . | | 1 |
| 129 | Hollow-core high-Q micro-cavities in three-dimensional photonic crystals. , 2010, , . | | 0 |
| 130 | Arbitrary Radio-Frequency Waveform Generation with a Silicon Chip-Based Spectral Shaper. , 2009, , . | | 0 |
| 131 | Nano-switch for study of gold contact behavior. , 2009, , . | | 3 |
| 132 | Radio-Frequency Arbitrary Waveform Generation on a Silicon Chip. , 2009, , . | | 0 |
| 133 | Silicon-on-Insulator Microring Add-Drop Filters With Free Spectral Ranges Over 30 nm. Journal of Lightwave Technology, 2008, 26, 228-236. | 4.6 | 91 |
| 134 | Programmable RF waveform generation with thermo-optically tunable multi-channel micro-ring resonators on a silicon chip. , 2008, , . | | 0 |
| 135 | Low-power light control with light in high Q/V silicon microring resonators. , 2008, , . | | 0 |
| 136 | Eight-channel microring resonator array with accurately controlled channel spacing. , 2008, , . | | 0 |
| 137 | Epitaxially grown graphene field-effect transistors with electron mobility exceeding 1500 cm ² /Vs and hole mobility exceeding 3400 cm ² /Vs. , 2007, , . | | 1 |
| 138 | Ultralow-Loss Compact Silicon Microring Resonators. , 2007, , . | | 0 |
| 139 | Two-Photon Absorption Induced Thermal-Optic Effect in High-Q Silicon Microring Resonators. Conference Proceedings - Lasers and Electro-Optics Society Annual Meeting-LEOS, 2007, , . | 0.0 | 2 |
| 140 | Multiple-channel silicon micro-resonator based filters for WDM applications. Optics Express, 2007, 15, 7489. | 3.4 | 145 |
| 141 | Modeling and measurement of losses in silicon-on-insulator resonators and bends. Optics Express, 2007, 15, 10553. | 3.4 | 129 |
| 142 | Compact silicon microring resonators with ultra-low propagation loss in the C band. Optics Express, 2007, 15, 14467. | 3.4 | 119 |
| 143 | A highly compact third-order silicon microring add-drop filter with a very large free spectral range, a flat passband and a low delay dispersion. Optics Express, 2007, 15, 14765. | 3.4 | 127 |
| | | | |

Low-loss Ultra-compact SOI Microring Add-Drop Filters. , 2007, , .

| # | Article | IF | CITATIONS |
|-----|--|------|-----------|
| 145 | Tunable Microcavities in 3D Photonic Crystals for Single-Photon Emission. , 2006, , . | | 0 |
| 146 | Broadband optical studies of 1D and 3D photonic crystals. , 2005, , . | | 0 |
| 147 | Microcavities in Three-Dimensional Photonic Crystals. , 2005, , . | | 0 |
| 148 | Strain-tunable silicon photonic band gap microcavities in optical waveguides. Applied Physics Letters, 2004, 84, 1242-1244. | 3.3 | 79 |
| 149 | A three-dimensional optical photonic crystal with designed point defects. Nature, 2004, 429, 538-542. | 27.8 | 457 |
| 150 | Fabrication of three-dimensional photonic crystals with midgap wavelength at 1.55 /spl mu/m. , 2003, , . | | 0 |
| 151 | Achieving nanometer-scale, controllable pattern shifts in x-ray lithography using an assembly-tilting technique. Journal of Vacuum Science & Technology an Official Journal of the American Vacuum Society B, Microelectronics Processing and Phenomena, 2002, 20, 2991. | 1.6 | 6 |