

PThomas

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/2902029/publications.pdf>

Version: 2024-02-01

31
papers

1,067
citations

471509
17
h-index

677142
22
g-index

31
all docs

31
docs citations

31
times ranked

1202
citing authors

#	ARTICLE	IF	CITATIONS
1	Structural, thermal and dielectric properties and thermalÂdegradation kinetics of nylon 11/CaCu3Ti4O12 (CCTO) nanocomposites. <i>Journal of Thermal Analysis and Calorimetry</i> , 2020, 141, 1123-1135.	3.6	20
2	Synthetic ester oil based high permittivity CaCu₃Ti₄O₁₂ (CCTO) nanofluids an alternative insulating medium for power transformer. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2019, 26, 314-321.	2.9	33
3	Dielectric properties of nylon 11/CaCu₃Ti₄O₁₂ (CCTO) nanocomposite films with high permittivity. <i>IEEE Transactions on Dielectrics and Electrical Insulation</i> , 2019, 26, 568-575.	2.9	11
4	Structural, thermal and dielectric behavior of Polyaryletherketone (PAEK)/CaCu3Ti4O12 (CCTO) nanocomposite films. <i>Ceramics International</i> , 2019, 45, 25052-25059.	4.8	13
5	Effect on dielectric, structural and thermal behaviour of \$CaCu₃Ti₄O₁₂ CaCu 3 Ti 4 O. <i>Bulletin of Materials Science</i> , 2019, 42, 1.	1.7	4
6	Dielectric and Thermal Behavior of PTFE/Sr ₂ TiMnO ₆ (STMO) Composites. , 2019, , .		1
7	Symmetric supercapacitor performances of CaCu3Ti4O12 decorated polyaniline nanocomposite. <i>Electrochimica Acta</i> , 2018, 292, 558-567.	5.2	28
8	Efficient Solar Energy Conversion Using CaCu3Ti4O12 Photoanode for Photocatalysis and Photoelectrocatalysis. <i>Scientific Reports</i> , 2016, 6, 18557.	3.3	83
9	Enhanced energy storage performance of glass added 0.715Bi_{0.5}Na_{0.5}TiO₃-0.065BaTiO₃-0.22SrTiO₃ ferroelectric ceramics. <i>Journal of Asian Ceramic Societies</i> , 2015, 3, 383-389.	2.3	21
10	Effect of Sr ₂ TiMnO ₆ fillers on mechanical, dielectric and thermal behaviour of PMMA polymer. <i>Journal of Advanced Dielectrics</i> , 2015, 05, 1550018.	2.4	17
11	Piezoelectric properties of individual nanocrystallites of Ba_{0.85}Ca_{0.15}Zr_{0.1}Ti_{0.9}O₃ obtained by oxalate precursor route. <i>Journal of Materials Chemistry C</i> , 2015, 3, 4762-4770.	5.5	44
12	Polyaniline/CaCu₃Ti₄O₁₂ nanofiber composite with a synergistic effect on visible light photocatalysis. <i>RSC Advances</i> , 2015, 5, 87241-87250.	3.6	28
13	Fabrication and characterization of poly(methyl methacrylate)/CaCu₃Ti₄O₁₂ composites. <i>Polymer Engineering and Science</i> , 2014, 54, 551-558.	3.1	8
14	Structural, thermal and electrical properties of poly(methyl methacrylate)/CaCu3Ti4O12 composite sheets fabricated via melt mixing. <i>Journal of Thermal Analysis and Calorimetry</i> , 2014, 115, 1311-1319.	3.6	37
15	Effect of TeO₂ addition on the dielectric properties of CaCu₃Ti₄O₁₂ ceramics derived from the oxalate precursor route. <i>Journal of Advanced Dielectrics</i> , 2013, 03, 1350028.	2.4	2
16	Dielectric properties of Poly(methyl methacrylate) (PMMA)/CaCu₃Ti₄O₁₂ composites. , 2012, , .		12
17	Effect of calcium stoichiometry on the dielectric response of CaCu3Ti4O12 ceramics. <i>Journal of the European Ceramic Society</i> , 2012, 32, 1681-1690.	5.7	35
18	Dielectric properties of Poly(vinylidene fluoride)/CaCu3Ti4O12 composites. <i>Composites Science and Technology</i> , 2010, 70, 539-545.	7.8	258

#	ARTICLE	IF	CITATIONS
19	Dielectric properties of poly(vinylidene fluoride)/CaCu ₃ Ti ₄ O ₁₂ nanocrystal composite thick films. EXPRESS Polymer Letters, 2010, 4, 632-643.	2.1	124
20	Synthesis of nanoparticles of the giant dielectric material, CaCu ₃ Ti ₄ O ₁₂ from a precursor route. Journal of Thermal Analysis and Calorimetry, 2009, 95, 267-272.	3.6	55
21	In situ synthesis and characterization of polyaniline-“CaCu ₃ Ti ₄ O ₁₂ nanocrystal composites. Synthetic Metals, 2009, 159, 2128-2134.	3.9	39
22	Nanoparticles of the giant dielectric material, CaCu ₃ Ti ₄ O ₁₂ from a precursor route. Journal of Physics and Chemistry of Solids, 2008, 69, 2594-2604.	4.0	65
23	Microwave synthesis and sintering characteristics of CaCu ₃ Ti ₄ O ₁₂ . Bulletin of Materials Science, 2007, 30, 567-570.	1.7	30
24	A study on the effect of the type and content of filler in epoxy-glass composite system on the friction and slide wear characteristics. Wear, 2005, 259, 634-641.	3.1	63
25	Influence of moisture absorption on electrical characteristics of glass-epoxy polymer composite system., 2005, , .	5	
26	Biodegradable dielectric liquids for transformer applications., 2005, , .	6	
27	Effect of benzotriazole and 2,6 ditertiary butyl para cresol on the accelerated oxidation of new and reclaimed transformer oils-a comparative study., 0, , .	5	
28	Dielectric liquid from vegetable origin-Indian beech oil., 0, , .	3	
29	Synthesis and evaluation of oleic acid esters as dielectric liquids., 0, , .	1	
30	Ageing characteristics of synthetic liquids., 0, , .	7	
31	Ageing studies on paper and oil to assess the condition of solid insulation used in power transformers., 0, , .	9	