

Leonardo M Angelone

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/2924202/publications.pdf>

Version: 2024-02-01

57
papers

1,614
citations

304743

22
h-index

315739

38
g-index

60
all docs

60
docs citations

60
times ranked

1369
citing authors

#	ARTICLE	IF	CITATIONS
1	Parallel transmission to reduce absorbed power around deep brain stimulation devices in MRI: Impact of number and arrangement of transmit channels. <i>Magnetic Resonance in Medicine</i> , 2020, 83, 299-311.	3.0	25
2	Effect of Multiple Scattering on Heating Induced by Radio Frequency Energy. <i>IEEE Transactions on Electromagnetic Compatibility</i> , 2020, 62, 2311-2316.	2.2	3
3	Changes in the specific absorption rate (SAR) of radiofrequency energy in patients with retained cardiac leads during MRI at 1.5T and 3T. <i>Magnetic Resonance in Medicine</i> , 2019, 81, 653-669.	3.0	42
4	Investigation of RF-Induced Heating Near Interventional Catheters at 1.5 T MRI: A Combined Modeling and Experimental Study. <i>IEEE Transactions on Electromagnetic Compatibility</i> , 2019, 61, 1423-1431.	2.2	11
5	A Study on the Feasibility of the Deep Brain Stimulation (DBS) Electrode Localization Based on Scalp Electric Potential Recordings. <i>Frontiers in Physiology</i> , 2019, 9, 1788.	2.8	10
6	Numerical and Experimental Analysis of Radiofrequency-Induced Heating Versus Lead Conductivity During EEG-MRI at 3 T. <i>IEEE Transactions on Electromagnetic Compatibility</i> , 2019, 61, 852-859.	2.2	12
7	Reducing RF-Induced Heating Near Implanted Leads Through High-Dielectric Capacitive Bleeding of Current (CBLOC). <i>IEEE Transactions on Microwave Theory and Techniques</i> , 2019, 67, 1265-1273.	4.6	46
8	The "virtual DBS population": five realistic computational models of deep brain stimulation patients for electromagnetic MR safety studies. <i>Physics in Medicine and Biology</i> , 2019, 64, 035021.	3.0	11
9	RF-induced heating in tissue near bilateral DBS implants during MRI at 1.5T and 3T: The role of surgical lead management. <i>NeuroImage</i> , 2019, 184, 566-576.	4.2	92
10	Realistic modeling of deep brain stimulation implants for electromagnetic MRI safety studies. <i>Physics in Medicine and Biology</i> , 2018, 63, 095015.	3.0	27
11	A numerical investigation on the effect of RF coil feed variability on global and local electromagnetic field exposure in human body models at 64 MHz. <i>Magnetic Resonance in Medicine</i> , 2018, 79, 1135-1144.	3.0	15
12	Effect Of Incident Field Magnitude And Phase Distribution On Rf-induced Heating Due To Hip Implants. , 2018, 2018, 1360-1363.		0
13	Radio-Frequency Safety Assessment of Stents in Blood Vessels During Magnetic Resonance Imaging. <i>Frontiers in Physiology</i> , 2018, 9, 1439.	2.8	26
14	Computational assessment of radiofrequency energy absorption of fetus during an MRI scan. <i>Biomedical Physics and Engineering Express</i> , 2018, 4, 045032.	1.2	1
15	Retrospective analysis of RF heating measurements of passive medical implants. <i>Magnetic Resonance in Medicine</i> , 2018, 80, 2726-2730.	3.0	37
16	Coupled modeling and experimental investigation of RF-induced heating near ablation catheters under 1.5T MRI. , 2018, , .		0
17	Feasibility of using linearly polarized rotating birdcage transmitters and close-fitting receive arrays in MRI to reduce SAR in the vicinity of deep brain simulation implants. <i>Magnetic Resonance in Medicine</i> , 2017, 77, 1701-1712.	3.0	70
18	RF Safety Evaluation of a Breast Tissue Expander Device for MRI: Numerical Simulation and Experiment. <i>IEEE Transactions on Electromagnetic Compatibility</i> , 2017, 59, 1390-1399.	2.2	5

#	ARTICLE	IF	CITATIONS
19	The Role of Computational Modeling and Simulation in the Total Product Life Cycle of Peripheral Vascular Devices. <i>Journal of Medical Devices, Transactions of the ASME</i> , 2017, 11, .	0.7	35
20	Improvement of Electromagnetic Field Distributions Using High Dielectric Constant (HDC) Materials for CTL-Spine MRI: Numerical Simulations and Experiments. <i>IEEE Transactions on Electromagnetic Compatibility</i> , 2017, 59, 1382-1389.	2.2	5
21	Construction and modeling of a reconfigurable MRI coil for lowering SAR in patients with deep brain stimulation implants. <i>NeuroImage</i> , 2017, 147, 577-588.	4.2	58
22	Local <sc>SAR</sc> near deep brain stimulation (<sc>DBS</sc>) electrodes at 64 and 127 <sc>MHz</sc>: A simulation study of the effect of extracranial loops. <i>Magnetic Resonance in Medicine</i> , 2017, 78, 1558-1565.	3.0	81
23	Investigating the effect of coil model losses on computational electromagnetic exposure of an ASTM phantom at 64 MHz MRI. , 2017, 2017, 1481-1484.		2
24	The electromagnetic fields of a 64 MHz quadrature driven birdcage coil in ASTM phantom. , 2017, , .		0
25	Effects of tuning conditions on near field of MRI transmit birdcage coil at 64 MHz. , 2016, 2016, 6242-6245.		6
26	Investigation of assumptions underlying current safety guidelines on EM-induced nerve stimulation. <i>Physics in Medicine and Biology</i> , 2016, 61, 4466-4478.	3.0	14
27	RF induced energy for partially implanted catheters: A computational study. , 2016, 2016, 1256-1259.		2
28	High dielectric material in MRI: Numerical assessment of the reduction of the induced local power on implanted cardiac leads. , 2016, 2016, 2361-2364.		7
29	Assessing the Electromagnetic Fields Generated By a Radiofrequency MRI Body Coil at 64 MHz: Defeating Versus Accuracy. <i>IEEE Transactions on Biomedical Engineering</i> , 2016, 63, 1591-1601.	4.2	35
30	Simulation platform for coupled modeling of EM-induced neuronal dynamics and functionalized anatomical models. , 2015, , .		1
31	MIDA: A Multimodal Imaging-Based Detailed Anatomical Model of the Human Head and Neck. <i>PLoS ONE</i> , 2015, 10, e0124126.	2.5	220
32	A Novel Brain Stimulation Technology Provides Compatibility with MRI. <i>Scientific Reports</i> , 2015, 5, 9805.	3.3	61
33	A Novel Method to Decrease Electric Field and SAR Using an External High Dielectric Sleeve at 3 T Head MRI: Numerical and Experimental Results. <i>IEEE Transactions on Biomedical Engineering</i> , 2015, 62, 1063-1069.	4.2	13
34	Real Time MR Thermometry Using Tm-DOTMA. <i>Journal of Electromagnetic Analysis and Applications</i> , 2015, 07, 115-125.	0.2	3
35	Assessment of MRI Issues at 7 T. <i>American Journal of Roentgenology</i> , 2014, 203, W560-W560.	2.2	2
36	A computational model for bipolar deep brain stimulation of the subthalamic nucleus. , 2014, 2014, 6258-61.		6

#	ARTICLE	IF	CITATIONS
37	Computational platform combining detailed and precise functionalized anatomical phantoms with EM-Neuron interaction modeling. , 2014, , .		4
38	A Virtual Patient Simulator Based on Human Connectome and 7 T MRI for Deep Brain Stimulation. International Journal on Advances in Life Sciences, 2014, 6, 364-372.	1.0	6
39	Specific absorption rate in a standard phantom containing a Deep Brain Stimulation lead at 3 Tesla MRI. , 2013, , .		8
40	A Novel Method to Decrease Electric Field and SAR Using an External High Dielectric Sleeve at 3T Head MRI: Numerical and Experimental Results. , 2013, , .		0
41	A New Method to Concentrate Electromagnetic Field Within ROI Using a High Dielectric Material in 3T Body MRI. , 2013, , .		1
42	MRI-Based Multiscale Model for Electromagnetic Analysis in the Human Head with Implanted DBS. Computational and Mathematical Methods in Medicine, 2013, 2013, 1-12.	1.3	22
43	Analysis of Conservative and Magnetically Induced Electric Fields in a Low-Frequency Birdcage Coil. Journal of Electromagnetic Analysis and Applications, 2013, 05, 271-280.	0.2	4
44	Evaluation of unintended electrical stimulation from MR gradient fields. Frontiers in Bioscience - Elite, 2012, E4, 1731.	1.8	1
45	Analysis of the Role of Lead Resistivity in Specific Absorption Rate for Deep Brain Stimulator Leads at 3T MRI. IEEE Transactions on Medical Imaging, 2010, 29, 1029-1038.	8.9	46
46	Computational Electromagnetic Analysis in a Human Head Model with EEG Electrodes and Leads Exposed to RF-Field Sources at 915 MHz and 1748 MHz. Radiation Research, 2010, 174, 91-100.	1.5	15
47	On the Measurement of Electrical Impedance Spectroscopy (EIS) of the Human Head. International Journal of Bioelectromagnetism, 2010, 12, 32-46.	0.0	17
48	MRI-based anatomical model of the human head for specific absorption rate mapping. Medical and Biological Engineering and Computing, 2008, 46, 1239-1251.	2.8	69
49	Specific absorption rate studies of the parallel transmission of inner volume excitations at 7T. Journal of Magnetic Resonance Imaging, 2008, 28, 1005-1018.	3.4	67
50	EEG/(f)MRI measurements at 7 Tesla using a new EEG cap (Cap). NeuroImage, 2006, 33, 1082-1092.	4.2	59
51	On the effect of resistive EEG electrodes and leads during 7 T MRI: simulation and temperature measurement studies. Magnetic Resonance Imaging, 2006, 24, 801-812.	1.8	51
52	Metallic electrodes and leads in simultaneous EEG-MRI: Specific absorption rate (SAR) simulation studies. Bioelectromagnetics, 2004, 25, 285-295.	1.6	74
53	Multimodal integration of EEG and MEG data: A simulation study with variable signal-to-noise ratio and number of sensors. Human Brain Mapping, 2004, 22, 52-62.	3.6	51
54	Multimodal integration of high-resolution EEG and functional magnetic resonance imaging data: a simulation study. NeuroImage, 2003, 19, 1-15.	4.2	126

#	ARTICLE	IF	CITATIONS
55	Multimodal integration of high resolution EEG and functional magnetic resonance: a simulation study. NeuroImage, 2001, 13, 66.	4.2	1
56	fMRI Priors for the Linear Inverse Estimation of EEG Cortical Sources. Electromagnetics, 2001, 21, 579-592.	0.7	7
57	Multimodal integration of high resolution EEG and functional magnetic resonance: a simulation study. , 0, , .		0