

# Bin Lin

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4358565/publications.pdf>

Version: 2024-02-01

111  
papers

4,064  
citations

101543

36  
h-index

133252

59  
g-index

114  
all docs

114  
docs citations

114  
times ranked

3610  
citing authors

#	ARTICLE	IF	CITATIONS
1	Shaping triple-conducting semiconductor BaCo <sub>0.4</sub> Fe <sub>0.4</sub> Zr <sub>0.1</sub> Y <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> into an electrolyte for low-temperature solid oxide fuel cells. <i>Nature Communications</i> , 2019, 10, 1707.	12.8	218
2	Ultrathin Cu <sub>2</sub> O as an efficient inorganic hole transporting material for perovskite solar cells. <i>Nanoscale</i> , 2016, 8, 6173-6179.	5.6	191
3	High Yield Synthesis of Bracelet-like Hydrophilic Ni <sup>2+</sup> /Co Magnetic Alloy Flux-Closure Nanorings. <i>Journal of the American Chemical Society</i> , 2008, 130, 11606-11607.	13.7	164
4	An ammonia fuelled SOFC with a BaCe <sub>0.9</sub> Nd <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> thin electrolyte prepared with a suspension spray. <i>Journal of Power Sources</i> , 2007, 170, 38-41.	7.8	112
5	High performance of proton-conducting solid oxide fuel cell with a layered PrBaCo <sub>2</sub> O <sub>5+<math>\delta</math></sub> cathode. <i>Journal of Power Sources</i> , 2009, 194, 835-837.	7.8	109
6	Magnetic field-induced solvothermal synthesis of one-dimensional assemblies of Ni-Co alloy microstructures. <i>Nano Research</i> , 2008, 1, 303-313.	10.4	108
7	A novel facile strategy to suppress Sr segregation for high-entropy stabilized La <sub>0.8</sub> Sr <sub>0.2</sub> MnO <sub>3-<math>\delta</math></sub> cathode. <i>Journal of Power Sources</i> , 2021, 482, 228959.	7.8	102
8	Recycling of fly ash for preparing porous mullite membrane supports with titania addition. <i>Journal of Hazardous Materials</i> , 2010, 180, 173-180.	12.4	99
9	High performance proton-conducting solid oxide fuel cells with a stable Sm <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>3-<math>\delta</math></sub> ∥Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>2-<math>\delta</math></sub> composite cathode. <i>Journal of Power Sources</i> , 2010, 195, 3155-3158.	7.8	95
10	Investigation of cobalt-free cathode material Sm <sub>0.5</sub> Sr <sub>0.5</sub> Fe <sub>0.8</sub> Cu <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> for intermediate temperature solid oxide fuel cell. <i>International Journal of Hydrogen Energy</i> , 2010, 35, 6905-6910.	7.1	93
11	Reaction-sintered porous mineral-based mullite ceramic membrane supports made from recycled materials. <i>Journal of Hazardous Materials</i> , 2009, 172, 180-186.	12.4	92
12	Prontonic ceramic membrane fuel cells with layered GdBaCo <sub>2</sub> O <sub>5+x</sub> cathode prepared by gel-casting and suspension spray. <i>Journal of Power Sources</i> , 2008, 177, 330-333.	7.8	87
13	Morphology and electrochemical performance of Li[Ni <sub>1/3</sub> Co <sub>1/3</sub> Mn <sub>1/3</sub> ]O <sub>2</sub> cathode material by a slurry spray drying method. <i>Journal of Power Sources</i> , 2008, 175, 564-569.	7.8	81
14	Intermediate-to-low temperature protonic ceramic membrane fuel cells with Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> ∥BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> composite cathode. <i>Journal of Power Sources</i> , 2009, 186, 58-61.	7.8	77
15	Rational Design of Antifouling Polymeric Nanocomposite for Sustainable Fluoride Removal from NOM-Rich Water. <i>Environmental Science &amp; Technology</i> , 2017, 51, 13363-13371.	10.0	77
16	Mo-doped Pr <sub>0.6</sub> Sr <sub>0.4</sub> Fe <sub>0.8</sub> Ni <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> as potential electrodes for intermediate-temperature symmetrical solid oxide fuel cells. <i>Electrochimica Acta</i> , 2017, 227, 33-40.	5.2	73
17	High performance protonic ceramic membrane fuel cells (PCMFCs) with Ba <sub>0.5</sub> Sr <sub>0.5</sub> Zn <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> perovskite cathode. <i>Electrochemistry Communications</i> , 2008, 10, 1388-1391.	4.7	71
18	In situ screen-printed BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> electrolyte-based protonic ceramic membrane fuel cells with layered SmBaCo <sub>2</sub> O <sub>5+x</sub> cathode. <i>Journal of Power Sources</i> , 2009, 186, 446-449.	7.8	67

#	ARTICLE	IF	CITATIONS
19	Surface modification of g-C <sub>3</sub> N <sub>4</sub> by hydrazine: Simple way for noble-metal free hydrogen evolution catalysts. <i>Chemical Engineering Journal</i> , 2016, 286, 339-346.	12.7	67
20	A cobalt-free Sm <sub>0.5</sub> Sr <sub>0.5</sub> Fe <sub>0.8</sub> Cu <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> /Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>2-<math>\delta</math></sub> composite cathode for proton-conducting solid oxide fuel cells. <i>Journal of Power Sources</i> , 2011, 196, 2631-2634.	7.8	66
21	Simple solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2010, 490, 214-222.	5.5	55
22	Enhanced performance of symmetrical solid oxide fuel cells using a doped ceria buffer layer. <i>Electrochimica Acta</i> , 2016, 208, 318-324.	5.2	53
23	Novel quasi-symmetric solid oxide fuel cells with enhanced electrochemical performance. <i>Journal of Power Sources</i> , 2016, 310, 109-117.	7.8	53
24	An Upgraded Lithium Ion Battery Based on a Polymeric Separator Incorporated with Anode Active Materials. <i>Advanced Energy Materials</i> , 2019, 9, 1803627.	19.5	53
25	A high-entropy perovskite cathode for solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2021, 872, 159633.	5.5	53
26	A cobalt-free SrFe <sub>0.9</sub> Sb <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> cathode material for proton-conducting solid oxide fuel cells with stable BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.1</sub> Yb <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> electrolyte. <i>Journal of Power Sources</i> , 2010, 195, 7042-7045.	7.8	48
27	Stable, easily sintered BaCe <sub>0.5</sub> Zr <sub>0.3</sub> Y <sub>0.16</sub> Zn <sub>0.04</sub> O <sub>3-<math>\delta</math></sub> electrolyte-based protonic ceramic membrane fuel cells with Ba <sub>0.5</sub> Sr <sub>0.5</sub> Zn <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> perovskite cathode. <i>Journal of Power Sources</i> , 2008, 183, 479-484.	7.8	46
28	Effects of organic acids of different molecular size on phosphate removal by HZO-201 nanocomposite. <i>Chemosphere</i> , 2017, 166, 422-430.	8.2	43
29	Surface Functionalization of g-C <sub>3</sub> N <sub>4</sub> : Molecular-Level Design of Noble-Metal-Free Hydrogen Evolution Photocatalysts. <i>Chemistry - A European Journal</i> , 2015, 21, 10290-10295.	3.3	42
30	Progress in Ni-based anode materials for direct hydrocarbon solid oxide fuel cells. <i>Journal of Materials Science</i> , 2018, 53, 8747-8765.	3.7	42
31	Exploiting rare-earth-abundant layered perovskite cathodes of LnBa <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>1.5</sub> Fe <sub>0.5</sub> O <sub>5+<math>\delta</math></sub> (Ln=La and Tj) ETQq1 <sub>7.1</sub> 0.784314 rgBT <sub>42</sub>		
32	Reduced-temperature redox-stable LSM as a novel symmetrical electrode material for SOFCs. <i>Electrochimica Acta</i> , 2018, 260, 121-128.	5.2	42
33	Ag <sub>2</sub> S Quantum Dots as an Infrared Excited Photocatalyst for Hydrogen Production. <i>ACS Applied Energy Materials</i> , 2019, 2, 2751-2759.	5.1	40
34	Highly promoted performance of triple-conducting cathode for YSZ-based SOFC via fluorine anion doping. <i>Ceramics International</i> , 2020, 46, 23964-23971.	4.8	40
35	Layered perovskite LaBaCuMO <sub>5+x</sub> (M=Fe, Co) cathodes for intermediate-temperature protonic ceramic membrane fuel cells. <i>Journal of Alloys and Compounds</i> , 2010, 493, 252-255.	5.5	39
36	Numerical investigation on impacts on fuel velocity distribution nonuniformity among solid oxide fuel cell unit channels. <i>International Journal of Hydrogen Energy</i> , 2015, 40, 3035-3047.	7.1	39

#	ARTICLE	IF	CITATIONS
37	High sintering activity Cu-Gd co-doped CeO <sub>2</sub> electrolyte for solid oxide fuel cells. <i>Journal of Power Sources</i> , 2010, 195, 6510-6515.	7.8	38
38	Highly permeable porous YSZ hollow fiber membrane prepared using ethanol as external coagulant. <i>Journal of Alloys and Compounds</i> , 2010, 494, 366-371.	5.5	37
39	Numerical simulation of cell-to-cell performance variation within a syngas-fuelled planar solid oxide fuel cell stack. <i>Applied Thermal Engineering</i> , 2017, 114, 653-662.	6.0	37
40	A Zn-Doped Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> Perovskite Cathode with Enhanced ORR Catalytic Activity for SOFCs. <i>Catalysts</i> , 2020, 10, 235.	3.5	37
41	Enhanced ORR activity of A-site deficiency engineered BaCo <sub>0.4</sub> Fe <sub>0.4</sub> Zr <sub>0.1</sub> Y <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> cathode in practical YSZ fuel cells. <i>International Journal of Hydrogen Energy</i> , 2021, 46, 5593-5603.	7.1	37
42	Asymmetric porous cordierite hollow fiber membrane for microfiltration. <i>Journal of Alloys and Compounds</i> , 2009, 487, 631-638.	5.5	36
43	A cobalt-free Sm <sub>0.5</sub> Sr <sub>0.5</sub> FeO <sub>3-<math>\delta</math></sub> /BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 8630-8634.	7.1	35
44	Fabrication of Li <sub>2</sub> TiO <sub>3</sub> pebbles by water-based sol-gel method. <i>Fusion Engineering and Design</i> , 2008, 83, 112-116.	1.9	34
45	A modified suspension spray combined with particle gradation method for preparation of protonic ceramic membrane fuel cells. <i>Journal of Power Sources</i> , 2008, 179, 576-583.	7.8	33
46	A cathode-supported SOFC with thin Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> electrolyte prepared by a suspension spray. <i>Journal of Alloys and Compounds</i> , 2008, 465, 285-290.	5.5	33
47	Screen-printed BaCe <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> thin membrane solid oxide fuel cells with surface modification by spray coating. <i>Journal of Alloys and Compounds</i> , 2009, 473, 48-52.	5.5	33
48	Thin yttria-stabilized zirconia electrolyte and transition layers fabricated by particle suspension spray. <i>Journal of Power Sources</i> , 2007, 164, 567-571.	7.8	31
49	SrCo <sub>0.9</sub> Sb <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> cubic perovskite as a novel cathode for intermediate-to-low temperature solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 472, 556-558.	5.5	30
50	Low-temperature solid oxide fuel cells with novel La <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.8</sub> Cu <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> perovskite cathode and functional graded anode. <i>Journal of Power Sources</i> , 2010, 195, 1624-1629.	7.8	29
51	Layered SmBaCuCoO <sub>5+</sub> and SmBaCuFeO <sub>5+</sub> perovskite oxides as cathode materials for proton-conducting SOFCs. <i>Journal of Alloys and Compounds</i> , 2010, 492, 291-294.	5.5	29
52	Preparation and electrochemical properties of Li[Ni <sub>1/3</sub> Co <sub>1/3</sub> Mn <sub>1-x/3</sub> Zr <sub>x/3</sub> ]O <sub>2</sub> cathode materials for Li-ion batteries. <i>Journal of Power Sources</i> , 2007, 174, 544-547.	7.8	28
53	Superior trichloroethylene removal from water by sulfide-modified nanoscale zero-valent iron/graphene aerogel composite. <i>Journal of Environmental Sciences</i> , 2020, 88, 90-102.	6.1	28
54	Improving stability and electrochemical performance of Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> electrode for symmetrical solid oxide fuel cells by Mo doping. <i>Journal of Alloys and Compounds</i> , 2020, 831, 154711.	5.5	27

#	ARTICLE	IF	CITATIONS
55	Fabrication and improvement of the density of Li <sub>2</sub> TiO <sub>3</sub> pebbles by the optimization of a sol-gel method. <i>Journal of Nuclear Materials</i> , 2009, 393, 186-191.	2.7	25
56	(La, Pr) <sub>0.8</sub> Sr <sub>0.2</sub> FeO <sub>3-δ</sub> /Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>2-δ</sub> composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2014, 39, 13665-13670.	7.1	25
57	Comparative study of electrochemical properties of different composite cathode materials associated to stable proton conducting BaZr <sub>0.7</sub> Pr <sub>0.1</sub> Y <sub>0.2</sub> O <sub>3-δ</sub> electrolyte. <i>Electrochimica Acta</i> , 2014, 146, 1-7.	5.2	25
58	Cost-effective tubular cordierite micro-filtration membranes processed by co-sintering. <i>Journal of Alloys and Compounds</i> , 2009, 477, L35-L40.	5.5	24
59	Evaluation of simple, easily sintered La <sub>0.7</sub> Ca <sub>0.3</sub> Cr <sub>0.97</sub> O <sub>3-δ</sub> perovskite oxide as novel interconnect material for solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 479, 764-768.	5.5	24
60	Preparation and characterization of carbon-coated Li[Ni <sub>1/3</sub> Co <sub>1/3</sub> Mn <sub>1/3</sub> ]O <sub>2</sub> cathode material for lithium-ion batteries. <i>Journal of Solid State Electrochemistry</i> , 2010, 14, 1807-1811.	2.5	24
61	Low-temperature protonic ceramic membrane fuel cells (PCMFCs) with SrCo <sub>0.9</sub> Sb <sub>0.1</sub> O <sub>3-δ</sub> cubic perovskite cathode. <i>Journal of Power Sources</i> , 2008, 185, 937-940.	7.8	23
62	Improvement of the performances of tubular solid oxide fuel cells by optimizing co-sintering temperature of the NiO/YSZ anode-YSZ electrolyte double layers. <i>Journal of Power Sources</i> , 2007, 171, 495-498.	7.8	22
63	Characterization and polarization DRT analysis of a stable and highly active proton-conducting cathode. <i>Ceramics International</i> , 2018, 44, 14297-14302.	4.8	22
64	Highly active self-assembled hybrid catalyst with multiphase heterointerfaces to accelerate cathodic oxygen reduction of intermediate-temperature solid oxide fuel cells. <i>Ceramics International</i> , 2020, 46, 9661-9668.	4.8	22
65	Potentiality of cobalt-free perovskite Ba <sub>0.5</sub> Sr <sub>0.5</sub> Fe <sub>0.9</sub> Mo <sub>0.1</sub> O <sub>3-δ</sub> as a single-phase cathode for intermediate-to-low-temperature solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2013, 38, 14323-14328.	7.1	21
66	Enhance coking tolerance of high-performance direct carbon dioxide-methane solid oxide fuel cells with an additional internal reforming catalyst. <i>Journal of Power Sources</i> , 2021, 512, 230533.	7.8	21
67	A promising cathode for proton-conducting intermediate temperature solid oxide fuel cells: Y <sub>0.8</sub> Ca <sub>0.2</sub> BaCo <sub>4</sub> O <sub>7+δ</sub> . <i>Ceramics International</i> , 2015, 41, 6687-6692.	4.8	19
68	A robust carbon tolerant anode for solid oxide fuel cells. <i>Science China Materials</i> , 2015, 58, 204-212.	6.3	19
69	An efficient and prospective self-assembled hybrid electrocatalyst for symmetrical and reversible solid oxide cells. <i>Electrochimica Acta</i> , 2020, 362, 137171.	5.2	19
70	A new A-site excessive strategy to improve performance of layered perovskite cathode for intermediate-temperature solid oxide fuel cells. <i>Electrochimica Acta</i> , 2017, 231, 686-693.	5.2	18
71	Evaluation of electrical conductivity and oxygen diffusivity of the typical Ruddlesden-Popper oxide Sr <sub>3</sub> Fe <sub>2</sub> O <sub>7-δ</sub> . <i>Ceramics International</i> , 2017, 43, 16264-16269.	4.8	18
72	g-C <sub>3</sub> N <sub>4</sub> /TiO <sub>2</sub> hybrid film on the metal surface, a cheap and efficient sunlight active photoelectrochemical anticorrosion coating. <i>Journal of Materials Science: Materials in Electronics</i> , 2019, 30, 12710-12717.	2.2	18

#	ARTICLE	IF	CITATIONS
73	Combustion synthesis and characterization of Cu <sup>2+</sup> /Sm co-doped CeO <sub>2</sub> electrolytes. <i>Journal of the European Ceramic Society</i> , 2011, 31, 2365-2376.	5.7	17
74	New insights into the fractionation of effluent organic matter on diagnosis of key composition affecting advanced phosphate removal by Zr-based nanocomposite. <i>Water Research</i> , 2020, 186, 116299.	11.3	17
75	Fabrication of dense LaCrO <sub>3</sub> -based interconnect thin membrane on anode substrates by co-firing. <i>Materials Research Bulletin</i> , 2009, 44, 2127-2133.	5.2	16
76	BaZr <sub>0.1</sub> Ce <sub>0.7</sub> Y <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> proton-conducting electrolyte prepared by gel-casting for low-temperature solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 474, 364-369.	5.5	16
77	Tuning Ba <sub>0.5</sub> Sr <sub>0.5</sub> Co <sub>0.8</sub> Fe <sub>0.2</sub> O <sub>3-<math>\delta</math></sub> cathode to high stability and activity via Ce-doping for ceramic fuel cells. <i>Ceramics International</i> , 2022, 48, 31418-31427.	4.8	14
78	Development of a novel type of composite cathode material for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 5940-5945.	7.1	13
79	A robust Ni <sup>2+</sup> /Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> anode for direct-methane solid oxide fuel cell. <i>Materials Research Bulletin</i> , 2015, 71, 1-6.	5.2	13
80	Improved performance of symmetrical solid oxide fuel cells with redox-reversible cermet electrodes. <i>Materials Letters</i> , 2017, 188, 413-416.	2.6	12
81	Highly sulfur poisoning-tolerant BaCe <sub>0.6</sub> Sr <sub>0.4</sub> Co <sub>0.2</sub> Fe <sub>0.8</sub> O <sub>3-<math>\delta</math></sub> cathodes for solid oxide fuel cells. <i>Journal Physics D: Applied Physics</i> , 2018, 51, 435502.	2.8	12
82	Control of endwall secondary flow in a compressor cascade with dielectric barrier discharge plasma actuation. <i>Science in China Series D: Earth Sciences</i> , 2009, 52, 3715-3721.	0.9	11
83	Preparation and characterization of Ba <sub>0.5</sub> Sr <sub>0.5</sub> Fe <sub>0.9</sub> Ni <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> /Sm <sub>0.2</sub> Ce <sub>0.8</sub> O <sub>1.9</sub> composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 9830-9835.	7.1	11
84	Layered perovskite oxide Y <sub>0.8</sub> Ca <sub>0.2</sub> BaCoFeO <sub>5+<math>\delta</math></sub> as a novel cathode material for intermediate-temperature solid oxide fuel cells. <i>Journal of Rare Earths</i> , 2015, 33, 519-523.	4.8	11
85	New Gd-Zn co-doping enhanced mechanical properties of BaZrO <sub>3</sub> proton conductors with high conductivity for IT-SOFCs. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2018, 238-239, 76-82.	3.5	11
86	Phase stability and hydrogen permeation performance of BaCo <sub>0.4</sub> Fe <sub>0.4</sub> Zr <sub>0.1</sub> Y <sub>0.1</sub> O <sub>3-<math>\delta</math></sub> ceramic membranes. <i>Ceramics International</i> , 2022, 48, 9946-9954.	4.8	10
87	Enhancing performance and stability of symmetrical solid oxide fuel cells via quasi-symmetrical ceria-based buffer layers. <i>Ceramics International</i> , 2022, 48, 27509-27515.	4.8	10
88	Stable, easily sintered BaCe <sub>0.5</sub> Zr <sub>0.3</sub> Y <sub>0.16</sub> Zn <sub>0.04</sub> O <sub>3-<math>\delta</math></sub> electrolyte-based proton-conducting solid oxide fuel cells by gel-casting and suspension spray. <i>Journal of Alloys and Compounds</i> , 2009, 478, 590-593.	5.5	9
89	A simple Ce-doping strategy to enhance stability of hybrid symmetrical electrode for solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2020, 45, 29259-29270.	7.1	9
90	Predicting Perovskite Performance with Multiple Machine-Learning Algorithms. <i>Crystals</i> , 2021, 11, 818.	2.2	9

#	ARTICLE	IF	CITATIONS
91	One stable electrocatalyst for two evolution reactions by one-pot combustion synthesis. International Journal of Hydrogen Energy, 2020, 45, 22691-22699.	7.1	8
92	$\text{CrI}_3/\text{Y}_2\text{CH}_2$ Heterointerface-Induced Stable Half-Metallicity of Two-Dimensional $\text{CrI}_3$ Monolayer Ferromagnets. ACS Applied Materials & Interfaces, 2021, 13, 16694-16703.	8.0	8
93	Nanoengineering electrode for yttria-stabilized zirconia-based symmetrical solid oxide fuel cells to achieve superior output performance. Separation and Purification Technology, 2022, 295, 121174.	7.9	8
94	Understanding the Surface of g-C <sub>3</sub> N <sub>4</sub> , an Experimental Investigation of the Catalytic Active Site on the Interface. Catalysis Letters, 2019, 149, 3296-3303.	2.6	7
95	A simple, feasible, and non-hazardous laboratory evaluation of direct ammonia solid oxide fuel cells fueled by aqueous ammonia. Separation and Purification Technology, 2022, 297, 121511.	7.9	7
96	Promoted Performance of Layered Perovskite $\text{PrBaFe}_2\text{O}_5+\delta$ Cathode for Protonic Ceramic Fuel Cells by Zn Doping. Catalysts, 2022, 12, 488.	3.5	6
97	A stable Zr-Y co-doped perovskite $\text{BaCo}_0.4\text{Fe}_0.4\text{Zr}_0.1\text{Y}_0.1\text{O}_3+\delta$ ceramic membrane for highly efficient oxygen separation. Separation and Purification Technology, 2022, 295, 121206.	7.9	6
98	Mechanical strengthening of Sm-doped $\text{CeO}_2$ ceramics by 1mol% cobalt oxide for solid oxide fuel cell application. Journal of Power Sources, 2011, 196, 8402-8405.	7.8	5
99	Alkaline-earth-free quasi-ternary $\text{La}(\text{Co}, \text{Ni}, \text{Fe})\text{O}_3+\delta$ perovskite as potential cathode for solid oxide fuel cells. Materials Research Express, 2019, 6, 096310.	1.6	5
100	Influences of equal A-site rare-deficiency or B-site high-valent metal doping on $\text{NdBaFe}_2\text{O}$ employed as the symmetrical electrode for solid oxide fuel cells. Journal of Alloys and Compounds, 2022, 918, 165368.	5.5	5
101	Synthesis and characterization of a $\text{Sr}_0.95\text{Y}_0.05\text{TiO}_3+\delta$ -based hydrogen electrode for reversible solid oxide cells. RSC Advances, 2015, 5, 17000-17006.	3.6	4
102	$\text{SrCo}_0.9\text{Sb}_0.1\text{O}_3+\delta$ cubic perovskite as a novel cathode for intermediate-to-low temperature SOFCs. Fuel Cells Bulletin, 2009, 2009, 12-15.	0.1	3
103	Stable and easily sintered $(\text{Pr}_0.5\text{Nd}_0.5)_0.7\text{Ca}_0.3\text{CrO}_3+\delta/\text{Sm}_0.2\text{Ce}_0.8\text{O}_1.9$ composite interconnect materials for IT-solid oxide fuel cells. Journal of Power Sources, 2011, 196, 2075-2079.	7.8	2
104	PVA-assisted synthesis and characterization of nano-crystalline $\text{La}^{3+}$ and $\text{Mg}^{2+}$ co-doped $\text{CeO}_2$ electrolyte for intermediate-temperature solid oxide fuel cells. Ionics, 2013, 19, 343-349.	2.4	2
105	Frontispiece: Surface Functionalization of g-C <sub>3</sub> N <sub>4</sub> : Molecular-Level Design of Noble-Metal-Free Hydrogen Evolution Photocatalysts. Chemistry - A European Journal, 2015, 21, n/a-n/a.	3.3	1
106	A new in-situ-grown $\text{Ni-Sr}_2\text{WO}_5+\delta$ cermet to enhance coking tolerance of direct-hydrocarbon solid oxide fuel cells. Materials Letters, 2021, 301, 130301.	2.6	1
107	Fly ash to improve density and ionic conductivity of solid oxide cell electrolytes. Materials Today Communications, 2022, , 103546.	1.9	1
108	Micro-Tubular Solid Oxide Fuel Cell with Asymmetric Structure Anode and $\text{La}_0.6\text{Sr}_0.4\text{Co}_0.8\text{Cu}_0.2\text{O}_3+\delta$ Perovskite Cathode. Advanced Materials Research, 2011, 197-198, 672-676.	0.3	0

#	ARTICLE	IF	CITATIONS
109	Preparation and Investigation of Cu Doped( $\text{Pr}_{0.5}\text{Nd}_{0.5}$ ) $\text{Ni}_{0.7}\text{Ca}_{0.3}\text{CrO}$ Ceramic Interconnect Materials. Applied Mechanics and Materials, 0, 448-453, 2950-2958.		
110	CO <sub>2</sub> -Stable Alkaline-Earth-Free Solid Oxide Fuel Cells with Ni <sub>0.7</sub> Co <sub>0.3</sub> O-Ce <sub>0.8</sub> Sm <sub>0.2</sub> O <sub>1.9</sub> Composite Cathodes. ECS Transactions, 2017, 78, 489-497.	0.5	0
111	Lowering the sintering temperature of low-temperature solid oxide fuel cells with Sm <sup>3+</sup> and Nd <sup>3+</sup> co-doped ceria electrolyte. , 2017, , .		0