

Bin Lin

List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/4358565/publications.pdf>

Version: 2024-02-01

111
papers

4,064
citations

101543

36
h-index

133252

59
g-index

114
all docs

114
docs citations

114
times ranked

3610
citing authors

#	ARTICLE	IF	CITATIONS
1	Phase stability and hydrogen permeation performance of $\text{BaCo}_{0.4}\text{Fe}_{0.4}\text{Zr}_{0.1}\text{Y}_{0.1}\text{O}_{3-\delta}$ ceramic membranes. <i>Ceramics International</i> , 2022, 48, 9946-9954.	4.8	10
2	Fly ash to improve density and ionic conductivity of solid oxide cell electrolytes. <i>Materials Today Communications</i> , 2022, , 103546.	1.9	1
3	Promoted Performance of Layered Perovskite $\text{PrBaFe}_2\text{O}_5$ Cathode for Protonic Ceramic Fuel Cells by Zn Doping. <i>Catalysts</i> , 2022, 12, 488.	3.5	6
4	Nanoengineering electrode for yttria-stabilized zirconia-based symmetrical solid oxide fuel cells to achieve superior output performance. <i>Separation and Purification Technology</i> , 2022, 295, 121174.	7.9	8
5	Influences of equal A-site rare-deficiency or B-site high-valent metal doping on NdBaFe_2O employed as the symmetrical electrode for solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2022, 918, 165368.	5.5	5
6	A stable Zr-Y co-doped perovskite $\text{BaCo}_{0.4}\text{Fe}_{0.4}\text{Zr}_{0.1}\text{Y}_{0.1}\text{O}_{3-\delta}$ ceramic membrane for highly efficient oxygen separation. <i>Separation and Purification Technology</i> , 2022, 295, 121206.	7.9	6
7	Enhancing performance and stability of symmetrical solid oxide fuel cells via quasi-symmetrical ceria-based buffer layers. <i>Ceramics International</i> , 2022, 48, 27509-27515.	4.8	10
8	A simple, feasible, and non-hazardous laboratory evaluation of direct ammonia solid oxide fuel cells fueled by aqueous ammonia. <i>Separation and Purification Technology</i> , 2022, 297, 121511.	7.9	7
9	Tuning $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ cathode to high stability and activity via Ce-doping for ceramic fuel cells. <i>Ceramics International</i> , 2022, 48, 31418-31427.	4.8	14
10	Exploiting rare-earth-abundant layered perovskite cathodes of $\text{LnBa}_{0.5}\text{Sr}_{0.5}\text{Co}_{1.5}\text{Fe}_{0.5}\text{O}_{5+\delta}$ (Ln=La and Tj) <i>ETQq0.0.0 rgBT /Overlock 1</i>	7.1	42
11	A novel facile strategy to suppress Sr segregation for high-entropy stabilized $\text{La}_{0.8}\text{Sr}_{0.2}\text{MnO}_{3-\delta}$ cathode. <i>Journal of Power Sources</i> , 2021, 482, 228959.	7.8	102
12	Enhanced ORR activity of A-site deficiency engineered $\text{BaCo}_{0.4}\text{Fe}_{0.4}\text{Zr}_{0.1}\text{Y}_{0.1}\text{O}_{3-\delta}$ cathode in practical YSZ fuel cells. <i>International Journal of Hydrogen Energy</i> , 2021, 46, 5593-5603.	7.1	37
13	$\text{CrI}_{3-\delta}/\text{YCH}_{2-\delta}$ Heterointerface-Induced Stable Half-Metallicity of Two-Dimensional $\text{CrI}_{3-\delta}$ Monolayer Ferromagnets. <i>ACS Applied Materials & Interfaces</i> , 2021, 13, 16694-16703.	8.0	8
14	Predicting Perovskite Performance with Multiple Machine-Learning Algorithms. <i>Crystals</i> , 2021, 11, 818.	2.2	9
15	A high-entropy perovskite cathode for solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2021, 872, 159633.	5.5	53
16	A new in-situ-grown $\text{Ni-Sr}_2\text{WO}_5$ cermet to enhance coking tolerance of direct-hydrocarbon solid oxide fuel cells. <i>Materials Letters</i> , 2021, 301, 130301.	2.6	1
17	Enhance coking tolerance of high-performance direct carbon dioxide-methane solid oxide fuel cells with an additional internal reforming catalyst. <i>Journal of Power Sources</i> , 2021, 512, 230533.	7.8	21
18	Superior trichloroethylene removal from water by sulfide-modified nanoscale zero-valent iron/graphene aerogel composite. <i>Journal of Environmental Sciences</i> , 2020, 88, 90-102.	6.1	28

#	ARTICLE	IF	CITATIONS
19	Highly active self-assembled hybrid catalyst with multiphase heterointerfaces to accelerate cathodic oxygen reduction of intermediate-temperature solid oxide fuel cells. <i>Ceramics International</i> , 2020, 46, 9661-9668.	4.8	22
20	An efficient and prospective self-assembled hybrid electrocatalyst for symmetrical and reversible solid oxide cells. <i>Electrochimica Acta</i> , 2020, 362, 137171.	5.2	19
21	One stable electrocatalyst for two evolution reactions by one-pot combustion synthesis. <i>International Journal of Hydrogen Energy</i> , 2020, 45, 22691-22699.	7.1	8
22	A simple Ce-doping strategy to enhance stability of hybrid symmetrical electrode for solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2020, 45, 29259-29270.	7.1	9
23	New insights into the fractionation of effluent organic matter on diagnosis of key composition affecting advanced phosphate removal by Zr-based nanocomposite. <i>Water Research</i> , 2020, 186, 116299.	11.3	17
24	Highly promoted performance of triple-conducting cathode for YSZ-based SOFC via fluorine anion doping. <i>Ceramics International</i> , 2020, 46, 23964-23971.	4.8	40
25	Improving stability and electrochemical performance of Ba _{0.5} Sr _{0.5} Co _{0.2} Fe _{0.8} O _{3-δ} electrode for symmetrical solid oxide fuel cells by Mo doping. <i>Journal of Alloys and Compounds</i> , 2020, 831, 154711.	5.5	27
26	A Zn-Doped Ba _{0.5} Sr _{0.5} Co _{0.8} Fe _{0.2} O _{3-δ} Perovskite Cathode with Enhanced ORR Catalytic Activity for SOFCs. <i>Catalysts</i> , 2020, 10, 235.	3.5	37
27	g-C ₃ N ₄ /TiO ₂ hybrid film on the metal surface, a cheap and efficient sunlight active photoelectrochemical anticorrosion coating. <i>Journal of Materials Science: Materials in Electronics</i> , 2019, 30, 12710-12717.	2.2	18
28	Alkaline-earth-free quasi-ternary La(Co, Ni, Fe)O _{3-δ} perovskite as potential cathode for solid oxide fuel cells. <i>Materials Research Express</i> , 2019, 6, 096310.	1.6	5
29	Understanding the Surface of g-C ₃ N ₄ , an Experimental Investigation of the Catalytic Active Site on the Interface. <i>Catalysis Letters</i> , 2019, 149, 3296-3303.	2.6	7
30	Ag ₂ S Quantum Dots as an Infrared Excited Photocatalyst for Hydrogen Production. <i>ACS Applied Energy Materials</i> , 2019, 2, 2751-2759.	5.1	40
31	Shaping triple-conducting semiconductor BaCo _{0.4} Fe _{0.4} Zr _{0.1} Y _{0.1} O _{3-δ} into an electrolyte for low-temperature solid oxide fuel cells. <i>Nature Communications</i> , 2019, 10, 1707.	12.8	218
32	An Upgraded Lithium Ion Battery Based on a Polymeric Separator Incorporated with Anode Active Materials. <i>Advanced Energy Materials</i> , 2019, 9, 1803627.	19.5	53
33	Progress in Ni-based anode materials for direct hydrocarbon solid oxide fuel cells. <i>Journal of Materials Science</i> , 2018, 53, 8747-8765.	3.7	42
34	New Gd-Zn co-doping enhanced mechanical properties of BaZrO ₃ proton conductors with high conductivity for IT-SOFCs. <i>Materials Science and Engineering B: Solid-State Materials for Advanced Technology</i> , 2018, 238-239, 76-82.	3.5	11
35	Highly sulfur poisoning-tolerant BaCeO ₃ -impregnated La _{0.6} Sr _{0.4} Co _{0.2} Fe _{0.8} O _{3-δ} cathodes for solid oxide fuel cells. <i>Journal Physics D: Applied Physics</i> , 2018, 51, 435502.	2.8	12
36	Characterization and polarization DRT analysis of a stable and highly active proton-conducting cathode. <i>Ceramics International</i> , 2018, 44, 14297-14302.	4.8	22

#	ARTICLE	IF	CITATIONS
37	Reduced-temperature redox-stable LSM as a novel symmetrical electrode material for SOFCs. <i>Electrochimica Acta</i> , 2018, 260, 121-128.	5.2	42
38	Numerical simulation of cell-to-cell performance variation within a syngas-fuelled planar solid oxide fuel cell stack. <i>Applied Thermal Engineering</i> , 2017, 114, 653-662.	6.0	37
39	A new A-site excessive strategy to improve performance of layered perovskite cathode for intermediate-temperature solid oxide fuel cells. <i>Electrochimica Acta</i> , 2017, 231, 686-693.	5.2	18
40	Mo-doped Pr _{0.6} Sr _{0.4} Fe _{0.8} Ni _{0.2} O _{3-δ} as potential electrodes for intermediate-temperature symmetrical solid oxide fuel cells. <i>Electrochimica Acta</i> , 2017, 227, 33-40.	5.2	73
41	Rational Design of Antifouling Polymeric Nanocomposite for Sustainable Fluoride Removal from NOM-Rich Water. <i>Environmental Science & Technology</i> , 2017, 51, 13363-13371.	10.0	77
42	Evaluation of electrical conductivity and oxygen diffusivity of the typical Ruddlesden-Popper oxide Sr ₃ Fe ₂ O _{7-δ} . <i>Ceramics International</i> , 2017, 43, 16264-16269.	4.8	18
43	CO ₂ -Stable Alkaline-Earth-Free Solid Oxide Fuel Cells with Ni _{0.7} Co _{0.3} O-Ce _{0.8} Sm _{0.2} O _{1.9} Composite Cathodes. <i>ECS Transactions</i> , 2017, 78, 489-497.	0.5	0
44	Effects of organic acids of different molecular size on phosphate removal by HZO-201 nanocomposite. <i>Chemosphere</i> , 2017, 166, 422-430.	8.2	43
45	Improved performance of symmetrical solid oxide fuel cells with redox-reversible cermet electrodes. <i>Materials Letters</i> , 2017, 188, 413-416.	2.6	12
46	Lowering the sintering temperature of low-temperature solid oxide fuel cells with Sm ³⁺ and Nd ³⁺ co-doped ceria electrolyte. , 2017, , .		0
47	Enhanced performance of symmetrical solid oxide fuel cells using a doped ceria buffer layer. <i>Electrochimica Acta</i> , 2016, 208, 318-324.	5.2	53
48	Ultrathin Cu ₂ O as an efficient inorganic hole transporting material for perovskite solar cells. <i>Nanoscale</i> , 2016, 8, 6173-6179.	5.6	191
49	Novel quasi-symmetric solid oxide fuel cells with enhanced electrochemical performance. <i>Journal of Power Sources</i> , 2016, 310, 109-117.	7.8	53
50	Surface modification of g-C ₃ N ₄ by hydrazine: Simple way for noble-metal free hydrogen evolution catalysts. <i>Chemical Engineering Journal</i> , 2016, 286, 339-346.	12.7	67
51	Surface Functionalization of g-C ₃ N ₄ : Molecular-Level Design of Noble-Metal-Free Hydrogen Evolution Photocatalysts. <i>Chemistry - A European Journal</i> , 2015, 21, 10290-10295.	3.3	42
52	Frontispiece: Surface Functionalization of g-C ₃ N ₄ : Molecular-Level Design of Noble-Metal-Free Hydrogen Evolution Photocatalysts. <i>Chemistry - A European Journal</i> , 2015, 21, n/a-n/a.	3.3	1
53	Synthesis and characterization of a Sr _{0.95} Y _{0.05} TiO _{3-δ} -based hydrogen electrode for reversible solid oxide cells. <i>RSC Advances</i> , 2015, 5, 17000-17006.	3.6	4
54	Numerical investigation on impacts on fuel velocity distribution nonuniformity among solid oxide fuel cell unit channels. <i>International Journal of Hydrogen Energy</i> , 2015, 40, 3035-3047.	7.1	39

#	ARTICLE	IF	CITATIONS
55	A promising cathode for proton-conducting intermediate temperature solid oxide fuel cells: $\text{Y}_{0.8}\text{Ca}_{0.2}\text{BaCo}_4\text{O}_{7+\delta}$. <i>Ceramics International</i> , 2015, 41, 6687-6692.	4.8	19
56	A robust $\text{NiO} \cdot \text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{1.9}$ anode for direct-methane solid oxide fuel cell. <i>Materials Research Bulletin</i> , 2015, 71, 1-6.	5.2	13
57	A robust carbon tolerant anode for solid oxide fuel cells. <i>Science China Materials</i> , 2015, 58, 204-212.	6.3	19
58	Layered perovskite oxide $\text{Y}_{0.8}\text{Ca}_{0.2}\text{BaCoFeO}_{5+\delta}$ as a novel cathode material for intermediate-temperature solid oxide fuel cells. <i>Journal of Rare Earths</i> , 2015, 33, 519-523.	4.8	11
59	$(\text{La}, \text{Pr})_{0.8}\text{Sr}_{0.2}\text{FeO}_{3+\delta} \cdot \text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{2+\delta}$ composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2014, 39, 13665-13670.	7.1	25
60	Comparative study of electrochemical properties of different composite cathode materials associated to stable proton conducting $\text{BaZr}_{0.7}\text{Pr}_{0.1}\text{Y}_{0.2}\text{O}_{3-\delta}$ electrolyte. <i>Electrochimica Acta</i> , 2014, 146, 1-7.	5.2	25
61	Potentiality of cobalt-free perovskite $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Fe}_{0.9}\text{Mo}_{0.1}\text{O}_{3+\delta}$ as a single-phase cathode for intermediate-to-low-temperature solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2013, 38, 14323-14328.	7.1	21
62	PVA-assisted synthesis and characterization of nano-crystalline La^{3+} and Mg^{2+} co-doped CeO_2 electrolyte for intermediate-temperature solid oxide fuel cells. <i>Ionics</i> , 2013, 19, 343-349.	2.4	2
63	Development of a novel type of composite cathode material for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 5940-5945.	7.1	13
64	A cobalt-free $\text{Sm}_{0.5}\text{Sr}_{0.5}\text{FeO}_{3+\delta} \cdot \text{BaZr}_{0.1}\text{Ce}_{0.7}\text{Y}_{0.2}\text{O}_{3+\delta}$ composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 8630-8634.	7.1	35
65	Preparation and characterization of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Fe}_{0.9}\text{Ni}_{0.1}\text{O}_{3+\delta} \cdot \text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{1.9}$ composite cathode for proton-conducting solid oxide fuel cells. <i>International Journal of Hydrogen Energy</i> , 2012, 37, 9830-9835.	7.1	11
66	Combustion synthesis and characterization of $\text{Cu} \cdot \text{Sm}$ co-doped CeO_2 electrolytes. <i>Journal of the European Ceramic Society</i> , 2011, 31, 2365-2376.	5.7	17
67	Mechanical strengthening of Sm-doped CeO_2 ceramics by 1mol% cobalt oxide for solid oxide fuel cell application. <i>Journal of Power Sources</i> , 2011, 196, 8402-8405.	7.8	5
68	A cobalt-free $\text{Sm}_{0.5}\text{Sr}_{0.5}\text{Fe}_{0.8}\text{Cu}_{0.2}\text{O}_{3+\delta} \cdot \text{Ce}_{0.8}\text{Sm}_{0.2}\text{O}_{2+\delta}$ composite cathode for proton-conducting solid oxide fuel cells. <i>Journal of Power Sources</i> , 2011, 196, 2631-2634.	7.8	66
69	Stable and easily sintered $(\text{Pr}_{0.5}\text{Nd}_{0.5})_{0.7}\text{Ca}_{0.3}\text{CrO}_{3+\delta} / \text{Sm}_{0.2}\text{Ce}_{0.8}\text{O}_{1.9}$ composite interconnect materials for IT-solid oxide fuel cells. <i>Journal of Power Sources</i> , 2011, 196, 2075-2079.	7.8	2
70	Micro-Tubular Solid Oxide Fuel Cell with Asymmetric Structure Anode and $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.8}\text{Cu}_{0.2}\text{O}_{3+\delta}$ Perovskite Cathode. <i>Advanced Materials Research</i> , 2011, 197-198, 672-676.	0.3	0
71	Recycling of fly ash for preparing porous mullite membrane supports with titania addition. <i>Journal of Hazardous Materials</i> , 2010, 180, 173-180.	12.4	99
72	Preparation and characterization of carbon-coated $\text{Li}[\text{Ni}_{1/3}\text{Co}_{1/3}\text{Mn}_{1/3}]\text{O}_2$ cathode material for lithium-ion batteries. <i>Journal of Solid State Electrochemistry</i> , 2010, 14, 1807-1811.	2.5	24

#	ARTICLE	IF	CITATIONS
73	Low-temperature solid oxide fuel cells with novel $\text{La}_{0.6}\text{Sr}_{0.4}\text{Co}_{0.8}\text{Cu}_{0.2}\text{O}_{3-\delta}$ perovskite cathode and functional graded anode. <i>Journal of Power Sources</i> , 2010, 195, 1624-1629.	7.8	29
74	High performance proton-conducting solid oxide fuel cells with a stable $\text{Sm}_{0.5}\text{Sr}_{0.5}\text{Co}_{3-\delta}$ - $\text{Ce}_{0.8}\text{Sm}_{0.2}\text{O}_{2-\delta}$ composite cathode. <i>Journal of Power Sources</i> , 2010, 195, 3155-3158.	7.8	95
75	High sintering activity Cu - Gd co-doped CeO_2 electrolyte for solid oxide fuel cells. <i>Journal of Power Sources</i> , 2010, 195, 6510-6515.	7.8	38
76	A cobalt-free $\text{SrFe}_{0.9}\text{Sb}_{0.1}\text{O}_{3-\delta}$ cathode material for proton-conducting solid oxide fuel cells with stable $\text{BaZr}_{0.1}\text{Ce}_{0.7}\text{Y}_{0.1}\text{b}_{0.1}\text{O}_{3-\delta}$ electrolyte. <i>Journal of Power Sources</i> , 2010, 195, 7042-7045.	7.8	48
77	Investigation of cobalt-free cathode material $\text{Sm}_{0.5}\text{Sr}_{0.5}\text{Fe}_{0.8}\text{Cu}_{0.2}\text{O}_{3-\delta}$ for intermediate temperature solid oxide fuel cell. <i>International Journal of Hydrogen Energy</i> , 2010, 35, 6905-6910.	7.1	93
78	Simple solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2010, 490, 214-222.	5.5	55
79	Layered SmBaCuCoO_{5+x} and SmBaCuFeO_{5+x} perovskite oxides as cathode materials for proton-conducting SOFCs. <i>Journal of Alloys and Compounds</i> , 2010, 492, 291-294.	5.5	29
80	Layered perovskite LaBaCuMO_{5+x} (M=Fe, Co) cathodes for intermediate-temperature protonic ceramic membrane fuel cells. <i>Journal of Alloys and Compounds</i> , 2010, 493, 252-255.	5.5	39
81	Highly permeable porous YSZ hollow fiber membrane prepared using ethanol as external coagulant. <i>Journal of Alloys and Compounds</i> , 2010, 494, 366-371.	5.5	37
82	Fabrication of dense LaCrO_3 -based interconnect thin membrane on anode substrates by co-firing. <i>Materials Research Bulletin</i> , 2009, 44, 2127-2133.	5.2	16
83	Fabrication and improvement of the density of Li_2TiO_3 pebbles by the optimization of a sol-gel method. <i>Journal of Nuclear Materials</i> , 2009, 393, 186-191.	2.7	25
84	$\text{SrCo}_{0.9}\text{Sb}_{0.1}\text{O}_{3-\delta}$ cubic perovskite as a novel cathode for intermediate-to-low temperature SOFCs. <i>Fuel Cells Bulletin</i> , 2009, 2009, 12-15.	0.1	3
85	Reaction-sintered porous mineral-based mullite ceramic membrane supports made from recycled materials. <i>Journal of Hazardous Materials</i> , 2009, 172, 180-186.	12.4	92
86	Intermediate-to-low temperature protonic ceramic membrane fuel cells with $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ - $\text{BaZr}_{0.1}\text{Ce}_{0.7}\text{Y}_{0.2}\text{O}_{3-\delta}$ composite cathode. <i>Journal of Power Sources</i> , 2009, 186, 58-61.	7.8	77
87	In situ screen-printed $\text{BaZr}_{0.1}\text{Ce}_{0.7}\text{Y}_{0.2}\text{O}_{3-\delta}$ electrolyte-based protonic ceramic membrane fuel cells with layered $\text{SmBaCo}_2\text{O}_{5+x}$ cathode. <i>Journal of Power Sources</i> , 2009, 186, 446-449.	7.8	67
88	High performance of proton-conducting solid oxide fuel cell with a layered $\text{PrBaCo}_2\text{O}_{5+\delta}$ cathode. <i>Journal of Power Sources</i> , 2009, 194, 835-837.	7.8	109
89	Control of endwall secondary flow in a compressor cascade with dielectric barrier discharge plasma actuation. <i>Science in China Series D: Earth Sciences</i> , 2009, 52, 3715-3721.	0.9	11
90	$\text{SrCo}_{0.9}\text{Sb}_{0.1}\text{O}_{3-\delta}$ cubic perovskite as a novel cathode for intermediate-to-low temperature solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 472, 556-558.	5.5	30

#	ARTICLE	IF	CITATIONS
91	Screen-printed BaCe _{0.8} Sm _{0.2} O ₃ thin membrane solid oxide fuel cells with surface modification by spray coating. <i>Journal of Alloys and Compounds</i> , 2009, 473, 48-52.	5.5	33
92	BaZr _{0.1} Ce _{0.7} Y _{0.2} O ₃ proton-conducting electrolyte prepared by gel-casting for low-temperature solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 474, 364-369.	5.5	16
93	Cost-effective tubular cordierite micro-filtration membranes processed by co-sintering. <i>Journal of Alloys and Compounds</i> , 2009, 477, L35-L40.	5.5	24
94	Stable, easily sintered BaCe _{0.5} Zr _{0.3} Y _{0.16} Zn _{0.04} O ₃ electrolyte-based proton-conducting solid oxide fuel cells by gel-casting and suspension spray. <i>Journal of Alloys and Compounds</i> , 2009, 478, 590-593.	5.5	9
95	Evaluation of simple, easily sintered La _{0.7} Ca _{0.3} Cr _{0.97} O ₃ perovskite oxide as novel interconnect material for solid oxide fuel cells. <i>Journal of Alloys and Compounds</i> , 2009, 479, 764-768.	5.5	24
96	Asymmetric porous cordierite hollow fiber membrane for microfiltration. <i>Journal of Alloys and Compounds</i> , 2009, 487, 631-638.	5.5	36
97	Morphology and electrochemical performance of Li[Ni _{1/3} Co _{1/3} Mn _{1/3}]O ₂ cathode material by a slurry spray drying method. <i>Journal of Power Sources</i> , 2008, 175, 564-569.	7.8	81
98	A modified suspension spray combined with particle gradation method for preparation of protonic ceramic membrane fuel cells. <i>Journal of Power Sources</i> , 2008, 179, 576-583.	7.8	33
99	Low-temperature protonic ceramic membrane fuel cells (PCMFCs) with SrCo _{0.9} Sb _{0.1} O ₃ cubic perovskite cathode. <i>Journal of Power Sources</i> , 2008, 185, 937-940.	7.8	23
100	Magnetic field-induced solvothermal synthesis of one-dimensional assemblies of Ni-Co alloy microstructures. <i>Nano Research</i> , 2008, 1, 303-313.	10.4	108
101	Protonic ceramic membrane fuel cells with layered GdBaCo ₂ O _{5+x} cathode prepared by gel-casting and suspension spray. <i>Journal of Power Sources</i> , 2008, 177, 330-333.	7.8	87
102	Stable, easily sintered BaCe _{0.5} Zr _{0.3} Y _{0.16} Zn _{0.04} O ₃ electrolyte-based protonic ceramic membrane fuel cells with Ba _{0.5} Sr _{0.5} Zn _{0.2} Fe _{0.8} O ₃ perovskite cathode. <i>Journal of Power Sources</i> , 2008, 183, 479-484.	7.8	46
103	High performance protonic ceramic membrane fuel cells (PCMFCs) with Ba _{0.5} Sr _{0.5} Zn _{0.2} Fe _{0.8} O ₃ perovskite cathode. <i>Electrochemistry Communications</i> , 2008, 10, 1388-1391.	4.7	71
104	Fabrication of Li ₂ TiO ₃ pebbles by water-based sol-gel method. <i>Fusion Engineering and Design</i> , 2008, 83, 112-116.	1.9	34
105	A cathode-supported SOFC with thin Ce _{0.8} Sm _{0.2} O _{1.9} electrolyte prepared by a suspension spray. <i>Journal of Alloys and Compounds</i> , 2008, 465, 285-290.	5.5	33
106	High Yield Synthesis of Bracelet-like Hydrophilic Ni-Co Magnetic Alloy Flux-Closure Nanorings. <i>Journal of the American Chemical Society</i> , 2008, 130, 11606-11607.	13.7	164
107	An ammonia fuelled SOFC with a BaCe _{0.9} Nd _{0.1} O ₃ thin electrolyte prepared with a suspension spray. <i>Journal of Power Sources</i> , 2007, 170, 38-41.	7.8	112
108	Improvement of the performances of tubular solid oxide fuel cells by optimizing co-sintering temperature of the NiO/YSZ anode-YSZ electrolyte double layers. <i>Journal of Power Sources</i> , 2007, 171, 495-498.	7.8	22

#	ARTICLE	IF	CITATIONS
109	Preparation and electrochemical properties of $\text{Li}[\text{Ni}_{1/3}\text{Co}_{1/3}\text{Mn}_{1-x}/3\text{Zr}_x/3]\text{O}_2$ cathode materials for Li-ion batteries. <i>Journal of Power Sources</i> , 2007, 174, 544-547.	7.8	28
110	Thin yttria-stabilized zirconia electrolyte and transition layers fabricated by particle suspension spray. <i>Journal of Power Sources</i> , 2007, 164, 567-571.	7.8	31
111	Preparation and Investigation of Cu Doped $(\text{Pr}_{0.5}\text{Nd}_{0.5})_{0.7}\text{Ca}_{0.3}\text{CrO}$ Ceramic Interconnect Materials. <i>Applied Mechanics and Materials</i> , 0, 448-453, 2950-2958.		