Dae-Soon Lim

List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/7260063/publications.pdf

Version: 2024-02-01

414414 516710 1,030 39 16 32 citations h-index g-index papers 39 39 39 1443 docs citations times ranked citing authors all docs

#	Article	IF	CITATIONS
1	Effect of Carbon Nanotube Addition on Tribological Behavior of UHMWPE. Tribology Letters, 2004, 16, 305-309.	2.6	208
2	Effect of carbon nanotube addition on the tribological behavior of carbon/carbon composites. Wear, 2002, 252, 512-517.	3.1	142
3	Effect of hydrogen plasma-mediated surface modification of carbon fibers on the mechanical properties of carbon-fiber-reinforced polyetherimide composites. Composites Part B: Engineering, 2017, 116, 451-458.	12.0	101
4	Tribological behavior of PTFE film with nanodiamond. Surface and Coatings Technology, 2004, 188-189, 534-538.	4.8	66
5	Multi-layer electrode with nano-Li4Ti5O12 aggregates sandwiched between carbon nanotube and graphene networks for high power Li-ion batteries. Scientific Reports, 2014, 4, 7334.	3.3	49
6	The electrical and corrosion properties of carbon nanotube coated 304 stainless steel/polymer composite as PEM fuel cell bipolar plates. International Journal of Hydrogen Energy, 2009, 34, 9781-9787.	7.1	47
7	Enhanced electrochemical oxidation of phenol by boron-doped diamond nanowire electrode. RSC Advances, 2017, 7, 6229-6235.	3.6	44
8	Roll-to-roll slot die production of 300 mm large area silver nanowire mesh films for flexible transparent electrodes. RSC Advances, 2017, 7, 7540-7546.	3.6	37
9	Non-Enzymatic Glucose Sensor Based on Cu Electrode Modified with CuO Nanoflowers. Journal of the Electrochemical Society, 2013, 160, B43-B46.	2.9	35
10	3D-networked carbon nanotube/diamond core-shell nanowires for enhanced electrochemical performance. NPG Asia Materials, 2014, 6, e115-e115.	7.9	31
11	Synthesis of sea urchin-like particles of carbon nanotubes directly grown on stainless steel cores and their effect on the mechanical properties of polymer composites. Carbon, 2010, 48, 2910-2916.	10.3	24
12	Improved electrode durability using a boron-doped diamond catalyst support for proton exchange membrane fuel cells. RSC Advances, 2015, 5, 1103-1108.	3.6	23
13	Preparation and properties on the graphite/polypropylene composite bipolar plates with a 304 stainless steel by compression molding for PEM fuel cell. International Journal of Hydrogen Energy, 2011, 36, 7621-7627.	7.1	22
14	Direct deposition of patterned nanocrystalline CVD diamond using an electrostatic self-assembly method with nanodiamond particles. Nanotechnology, 2010, 21, 505302.	2.6	20
15	Electrical and corrosion properties of stainless steel bipolar plates coated with a conduction polymer composite. Current Applied Physics, 2010, 10, S18-S21.	2.4	17
16	The effect of iron catalysts on the microstructure and tribological properties of carbide-derived carbon. Carbon, 2010, 48, 3628-3634.	10.3	16
17	Morphology control of 3D-networked boron-doped diamond nanowires and its electrochemical properties. Journal of Electroanalytical Chemistry, 2018, 820, 140-145.	3.8	14
18	Sulfur-impregnated MWCNT microball cathode for Li–S batteries. RSC Advances, 2014, 4, 16062.	3.6	13

#	Article	IF	Citations
19	Carbide derived carbon: from growth to tribological application. Journal of the Ceramic Society of Japan, 2014, 122, 577-585.	1.1	12
20	Influence of Immobilization of Bacterial Cells and TiO2 on Phenol Degradation. Water, Air, and Soil Pollution, 2013, 224, 1.	2.4	11
21	Phase and microstructural evolution of Sn particles embedded in amorphous carbon nanofibers and their anode properties in Li-ion batteries. Journal of Electroceramics, 2014, 32, 261-268.	2.0	11
22	Selective growth of carbon nanotubes on boron-doped diamond for electrochemical biosensor application. RSC Advances, 2015, 5, 23395-23400.	3.6	9
23	Friction and wear of pressureless sintered Ti(C,N)–WC ceramics. Wear, 2003, 255, 682-685.	3.1	8
24	Multi-stacked electrodes employing aluminum coated tissue papers and non-oxidized graphene nanoflakes for high performance lithium–sulfur batteries. RSC Advances, 2016, 6, 60537-60545.	3.6	8
25	Characteristics of hydrogen plasma treated carbon nanotubes and their influence on the mechanical properties of polyetherimide-based nanocomposites. Carbon, 2017, 118, 650-658.	10.3	8
26	Analysis of Parameters Affecting the Surface Roughness in Sapphire Wafer Polishing Using Nanocrystalline–Microcrystalline Multilayer Diamond CVD Pellets. International Journal of Precision Engineering and Manufacturing, 2019, 20, 883-891.	2.2	7
27	Effect of a silane coupling agent on the optical and the mechanical characteristics of nanodiamond/acrylic resin composites. Journal of the Korean Physical Society, 2014, 65, 1049-1053.	0.7	6
28	Fabrication of hollow boron-doped diamond nanostructure via electrochemical corrosion of a tungsten oxide template. Nanotechnology, 2018, 29, 325602.	2.6	6
29	Non-Enzymatic Glucose Detection Using Free Standing Hollow Boron-Doped Diamond Nanorod Electrodes. Journal of the Electrochemical Society, 2019, 166, B576-B580.	2.9	6
30	Effect of hydrogen on the physical and mechanical properties of silicon carbide-derived carbon films. Surface and Coatings Technology, 2009, 204, 1018-1021.	4.8	5
31	Boron-doped diamond nanowire array electrode with high mass transfer rates in flow-by operation. RSC Advances, 2018, 8, 11102-11108.	3.6	5
32	Fabrication of boron-doped nanocrystalline diamond nanoflowers based on 3D Cu(OH)2 dendritic architectures. Journal of the Korean Physical Society, 2012, 60, 836-841.	0.7	4
33	Modification of the surface morphology of the silicon substrate for boron-doped diamond electrodes in electrochemical wastewater treatment applications. Journal of the Korean Physical Society, 2016, 68, 109-114.	0.7	4
34	Metal-oxide thin-film transistor-based pH sensor with a silver nanowire top gate electrode. Journal of the Korean Physical Society, 2016, 68, 901-907.	0.7	3
35	Effect of the Properties of Uniformly Patterned Micro-Diamond Pellets on Sapphire Grinding. Journal of the Korean Physical Society, 2018, 73, 871-876.	0.7	3
36	Cr effect on the durability of Pt–TM catalysts for PEMFCs. RSC Advances, 2015, 5, 55401-55405.	3.6	2

#	Article	IF	CITATIONS
37	Effect of the Molecular Weight of Dispersant to the Slurry for Lead-Free Transparent Dielectric Films. Molecular Crystals and Liquid Crystals, 2009, 514, 190/[520]-200/[530].	0.9	1
38	Plasma resistance of Y ₂ O ₃ nanofilms on quartz with different interlayer deposited by EB-PVD. Journal of the Ceramic Society of Japan, 2012, 120, 539-543.	1.1	1
39	Structure and tribological properties of plasma-treated carbide derived carbon layer. Carbon, 2016, 96, 1070-1076.	10.3	1