## Ichiro Fujii

## List of Publications by Year in descending order

Source: https://exaly.com/author-pdf/7279971/publications.pdf

Version: 2024-02-01

331670 330143 1,800 140 21 37 h-index citations g-index papers 140 140 140 1508 docs citations times ranked citing authors all docs

#	Article	IF	CITATIONS
1	Domain wall contributions to the properties of piezoelectric thin films. Journal of Electroceramics, 2007, 19, 49-67.	2.0	252
2	Structural and electrical characteristics of potential candidate lead-free BiFeO3-BaTiO3 piezoelectric ceramics. Journal of Applied Physics, 2017, 122, .	2.5	95
3	Grain size effect on the dielectric nonlinearity of BaTiO3 ceramics. Journal of Applied Physics, 2010, 107, .	2.5	65
4	Effect of Grain Size on Dielectric Nonlinearity in Model BaTiO3-Based Multilayer Ceramic Capacitors. Journal of the American Ceramic Society, 2011, 94, 194-199.	3.8	52
5	Influence of Mn doping on domain wall motion in Pb(Zr0.52Ti0.48)O3 films. Journal of Applied Physics, 2011, 109, .	2.5	49
6	Domain Wall Motion in <scp>A</scp> and <scp>B</scp> Site Donorâ€Doped <scp><scp>Pb</scp> </scp> <td><!--<b-->susb&gt;)<s∈< td=""><td>:р<b>•</b>9х scp&gt;О&lt;</td></s∈<></td>	<b susb>) <s∈< td=""><td>:р<b>•</b>9х scp&gt;О&lt;</td></s∈<>	:р <b>•</b> 9х scp>О<
7	Enhanced piezoelectric response of BaTiO3–KNbO3 composites. Applied Physics Letters, 2011, 99, .	3.3	44
8	Structural, Dielectric, and Piezoelectric Properties of Mn-Doped BaTiO <sub>3</sub> â€"Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> â€"BiFeO <sub>3</sub> Ceramics. Japanese Journal of Applied Physics, 2011, 50, 09ND07.	1.5	42
9	Structural, Dielectric, and Piezoelectric Properties of Mn-Doped BaTiO <sub>3</sub> â€"Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> â€"BiFeO <sub>3</sub> Ceramic Japanese Journal of Applied Physics, 2011, 50, 09ND07.	CS1.5	42
10	A new approach for the preparation of SrTiO3 nanocubes. Ceramics International, 2013, 39, 3231-3234.	4.8	41
11	Electric field induced lattice strain in pseudocubic Bi(Mg1/2Ti1/2)O3-modified BaTiO3-BiFeO3 piezoelectric ceramics. Applied Physics Letters, 2016, $108$ , .	3.3	40
12	Thickness dependence of dielectric nonlinearity of lead zirconate titanate films. IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, 2010, 57, 1717-1723.	3.0	38
13	Structural, dielectric, and piezoelectric properties of BaTiO3-Bi(Ni1/2Ti1/2)O3 ceramics. Journal of the Ceramic Society of Japan, 2012, 120, 30-34.	1.1	37
14	Microstructure of BaTiO <sub>3</sub> –Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> –BiFeO <sub>3</sub> Piezoele Ceramics. Japanese Journal of Applied Physics, 2012, 51, 09LD04.	ectr <b>s</b> c	34
15	Piezoelectricity in perovskite-type pseudo-cubic ferroelectrics by partial ordering of off-centered cations. Communications Materials, 2020, $1$ , .	6.9	33
16	Effect of Heating Rates during Sintering on the Electrical Properties of Ultra‶hin Ni–BaTiO <sub>3</sub> Multilayer Ceramic Capacitors. Journal of the American Ceramic Society, 2008, 91, 2540-2544.	3.8	31
17	Influence of quenching temperature on piezoelectric and ferroelectrics properties in BaTiO3-Bi(Mg1/2Ti1/2)O3-BiFeO3 ceramics. Ceramics International, 2018, 44, S199-S202.	4.8	31
18	Spatially Resolved Spectroscopic Mapping of Polarization Reversal in Polycrystalline Ferroelectric Films: Crossing the Resolution Barrier. Physical Review Letters, 2009, 103, 057601.	7.8	30

#	Article	IF	Citations
19	Enhancement in the piezoelectric properties of BaTiO3–Bi(Mg1/2Ti1/2)O3–BiFeO3 system ceramics by nanodomain. Ceramics International, 2013, 39, S695-S699.	4.8	27
20	Local measurements of Preisach density in polycrystalline ferroelectric capacitors using piezoresponse force spectroscopy. Applied Physics Letters, 2010, 96, .	3.3	25
21	Effect of thermal annealing on crystal structures and electrical properties in BaTiO3 ceramics. Journal of Applied Physics, 2018, 124, .	2.5	24
22	Effect of Oxygen Partial Pressure During Firing on the High AC Field Response of BaTiO <sub>3</sub> Dielectrics. Journal of the American Ceramic Society, 2010, 93, 1081-1088.	3.8	22
23	Fabrication of Transparent <scp><scp>Pb</scp></scp> <scb>Nb</scb> 2/3- Based Ceramics by Conventional Sintering. Journal of the American Ceramic Society, 2013, 96, 3782-3787.	<b sub>) <s< td=""><td>cp<b>22</b> scp &gt; 0 e</td></s<>	cp <b>22</b> scp > 0 e
24	Influence of grain size effect and Ba/Ti ratios on dielectric, ferroelectric, and piezoelectric properties of BaTiO <sub>3</sub> ceramics. Japanese Journal of Applied Physics, 2019, 58, SLLC05.	1.5	21
25	Preparation of Barium Titanate–Potassium Niobate Nanostructured Ceramics with Artificial Morphotropic Phase Boundary Structure By Solvothermal Method. Japanese Journal of Applied Physics, 2011, 50, 09NC08.	1.5	20
26	Microstructure of BaTiO <sub>3</sub> â€"Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> â€"BiFeO <sub>3</sub> Piezoele Ceramics. Japanese Journal of Applied Physics, 2012, 51, 09LD04.	ectrisc	20
27	Preparation of BaZrO3 cubes by composite-hydroxide-mediated approach at low temperature. Journal of the Ceramic Society of Japan, 2011, 119, 532-534.	1.1	19
28	Low-temperature synthesis of SrZrO3 nanocubes by the composite-hydroxide-mediated approach. Journal of Crystal Growth, 2013, 376, 35-40.	1.5	19
29	In-situ electric field induced lattice strain response observation in BiFeO <sub>3</sub> –BaTiO <sub>3</sub> lead-free piezoelectric ceramics. Journal of the Ceramic Society of Japan, 2018, 126, 316-320.	1.1	19
30	Relaxor Characteristics of BaTiO <sub>3</sub> 1/21/21/2)O <sub>3</sub> 1/231/20 <sub>3</sub> 1/20 <sub>3</sub> 1/21/20 <sub>3</sub> 1/21	su <b>b&amp;i</b> gt;	18
31	Crystal Structure of BaTiO <sub>3</sub> –KNbO <sub>3</sub> Nanocomposite Ceramics: Relationship between Dielectric Property and Structure of Heteroepitaxial Interface. Japanese Journal of Applied Physics, 2012, 51, 09LE05.	1.5	17
32	Fabrication of (K,Na)NbO3films on SrRuO3/(001)SrTiO3substrates by pulsed laser deposition. Japanese Journal of Applied Physics, 2015, 54, 10NA13.	1.5	17
33	Nanostructure Control of Barium Titanate–Potassium Niobate Nanocomplex Ceramics and Their Enhanced Ferroelectric Properties. Japanese Journal of Applied Physics, 2012, 51, 09LC05.	1.5	15
34	Ferroelectric and piezoelectric properties of (Bi <sub>1/2</sub> Na <sub>1/2</sub> )TiO <sub>3</sub> â€"BiFeO <sub>3</sub> ceramics. Journal of Materials Research, 2016, 31, 28-35.	2.6	15
35	Grain-size dependence of piezoelectric properties in thermally annealed BaTiO <sub>3</sub> ceramics. Journal of the Ceramic Society of Japan, 2018, 126, 536-541.	1.1	15
36	Effects of sintering aid and atmosphere powder on the growth of (K0.5Na0.5)NbO3 single crystals fabricated by solid-state crystal growth method. Journal of the European Ceramic Society, 2020, 40, 2970-2976.	5.7	15

#	Article	IF	CITATIONS
37	Fabrication of lead-free piezoelectric (Bi0.5Na0.5)TiO3–BaTiO3 ceramics using electrophoretic deposition. Journal of Materials Science, 2018, 53, 2396-2404.	3.7	14
38	Preparation of Barium Titanate/Strontium Titanate Multilayered Nanoparticles. Key Engineering Materials, 0, 485, 305-308.	0.4	13
39	Preparation of KNbO <sub>3</sub> nanocubes using a solvothermal method at low temperature. Journal of the Ceramic Society of Japan, 2013, 121, 693-697.	1.1	13
40	Preparation of Barium Titanate–Potassium Niobate Nanostructured Ceramics with Artificial Morphotropic Phase Boundary Structure By Solvothermal Method. Japanese Journal of Applied Physics, 2011, 50, 09NC08.	1.5	13
41	Piezoelectric Properties of Porous Potassium Niobate System Ceramics. Key Engineering Materials, 0, 485, 61-64.	0.4	12
42	Effect of sintering condition and V-doping on the piezoelectric properties of BaTiO <sub>3</sub> â€"Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3&amp;ceramics. Journal of the Ceramic Society of Japan, 2013, 121, 589-592.</sub>	< <b>/su</b> b&g	ŗt;â <b>€</b> 2BiFeO&l <sup>.</sup>
43	Chemical composition dependence of ferroelectric properties for BaTiO <sub>3</sub> –Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3&amp; lead-free piezoelectric ceramics. Journal of the Ceramic Society of Japan, 2013, 121, 855-858.</sub>	< <b>/su</b> b&g	gt;â€2BiFeO&l
44	A-site cation off-centering contribution on ferroelectricity and piezoelectricity in pseudo-cubic perovskite structure of Bi-based lead-free piezoelectrics. Scripta Materialia, 2021, 205, 114176.	5.2	12
45	Nanostructure Control of Barium Titanate–Potassium Niobate Nanocomplex Ceramics and Their Enhanced Ferroelectric Properties. Japanese Journal of Applied Physics, 2012, 51, 09LC05.	1.5	12
46	Effect of sintering temperature on the growth of (K0.5Na0.5)NbO3 single crystals fabricated by the solid-state crystal growth method. Japanese Journal of Applied Physics, 2019, 58, SLLD01.	1.5	11
47	Preparation of barium titanate porous ceramics and their sensor properties. Journal of the Ceramic Society of Japan, 2013, 121, 698-701.	1.1	10
48	Ferroelectric properties of (Li,K,Na)NbO3epitaxial films fabricated by pulsed laser deposition. Japanese Journal of Applied Physics, 2014, 53, 09PA09.	1.5	10
49	Thermal annealing induced recovery of damaged surface layer for enhanced ferroelectricity in Bi-based ceramics. Japanese Journal of Applied Physics, 2019, 58, SLLD04.	1.5	10
50	Microstructure Control of Barium Titanate – Potassium Niobate Solid Solution System Ceramics by MPB Engineering and their Piezoelectric Properties. Key Engineering Materials, 2011, 485, 89-92.	0.4	9
51	Domain observation of potassium-modified NaNbO <sub>3</sub> epitaxial films by confocal laser scanning microscopy. Japanese Journal of Applied Physics, 2016, 55, 10TA02.	1.5	9
52	Crystal structure, photocatalytic and dielectric property of ATiM <sub>2</sub> O <sub>8</sub> (A: Mg,) Tj ETQq	0 0 0 rgBT 2.3	Oyerlock 10
53	Fabrication of 0.24Pb(In <sub>1/2</sub> Nb <sub>1/2</sub> )O <sub>3</sub> â€0.42Pb(Mg <sub>1/3</sub> Nb <sub>2/3</sub> transparent ceramics by conventional sintering technique. Journal of the American Ceramic Society, 2019, 102, 1240-1248.	)O{sub>3	8â€0.3
54	Fabrication of an antiferroelectric NaNbO <sub>3</sub> -CaZrO <sub>3</sub> film on a (001)SrTiO <sub>3</sub> substrate by pulsed laser deposition. Japanese Journal of Applied Physics, 2019, 58, SLLB05.	1.5	9

#	Article	IF	CITATIONS
55	Effects of AC- and DC-bias field poling on piezoelectric properties of Bi-based ceramics. Journal of the Ceramic Society of Japan, 2019, 127, 353-356.	1.1	9
56	Development of an apparatus for Bragg coherent X-ray diffraction imaging, and its application to the three dimensional imaging of BaTiO <sub>3</sub> nano-crystals. Japanese Journal of Applied Physics, 2019, 58, SLLA05.	1.5	9
57	Energy storage properties of antiferroelectric 0.92NaNbO3-0.08SrZrO3 film on (001)SrTiO3 substrate. Physics Letters, Section A: General, Atomic and Solid State Physics, 2020, 384, 126690.	2.1	9
58	Fabrication of $(111)$ -oriented Tetragonal BaTiO<sub>3</sub> Ceramics by an Electrophoretic Deposition in a High Magnetic Field. Transactions of the Materials Research Society of Japan, 2015, 40, 223-226.	0.2	8
59	Fabrication of an antiferroelectric NaNbO3–CaZrO3 film by pulsed laser deposition. Japanese Journal of Applied Physics, 2018, 57, 11UF12.	1.5	8
60	Effect of A-site off-stoichiometry on ferroelectric and piezoelectric properties of BaTiO <sub>3</sub> –Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3&amp;l ceramics. Journal of the Ceramic Society of Japan, 2019, 127, 369-373.</sub>	t; <b>/su</b> b>	;â <b>€</b> "BiFeO&l¹
61	Mn–Nb co-doping in barium titanate ceramics by different solid-state reaction routes for temperature stable and DC-bias free dielectrics. Ceramics International, 2022, 48, 2154-2160.	4.8	8
62	Effects of SrTiO <sub>3</sub> substrate orientations on crystal and domain structures and electric properties of NaNbO <sub>3</sub> â€"SrZrO <sub>3</sub> films. Japanese Journal of Applied Physics, 2018, 57, 11UF13.	1.5	7
63	Preparation and investigation of hexagonal-tetragonal BaTiO <sub>3</sub> powders. Journal of the Ceramic Society of Japan, 2021, 129, 91-96.	1.1	7
64	Bragg coherent diffraction imaging allowing simultaneous retrieval of three-dimensional shape and strain distribution for 40–500Ânm particles. Japanese Journal of Applied Physics, 2021, 60, SFFA07.	1.5	7
65	Material softening by cation off-centering in Bi-based lead-free piezoelectric ceramics. Japanese Journal of Applied Physics, 2021, 60, SFFD01.	1.5	7
66	Fabrication of (Bi0.5K0.5)TiO3 modified BaTiO3-Bi(Mg0.5Ti0.5)O3-BiFeO3 piezoelectric ceramics. Journal of the European Ceramic Society, 2021, 41, 4108-4115.	5.7	7
67	Effect of La doping in transparent 0.67Pb(Mg1/3Nb2/3)O3–0.33PbTiO3 ceramics fabricated by conventional sintering. Journal of Materials Research, 2014, 29, 2260-2265.	2.6	6
68	Fabrication of 〈110〉 grain-oriented 0.15BaTiO3–0.85(Bi0.5Na0.5)TiO3ceramics by a reactive templated growth method. Japanese Journal of Applied Physics, 2017, 56, 10PD06.	d grain	6
69	Fabrication and electro-optic properties of 0.9Pb[(Mg,Zn) <sub>1/3</sub> Nb <sub>2/3</sub> ]O <sub>3</sub> –0.1PbTiO <sub>3</sub> transparent ceramics by a conventional sintering technique. Japanese Journal of Applied Physics, 2017, 56, 10PC04.	1.5	6
70	Magnetic Properties of L1 <sub>O</sub> Ordered FePt Films Prepared on a Fe–Si–B–Nb–Cu Soft Magnetic Underlayer. Materials Transactions, 2006, 47, 47-51.	1.2	5
71	Fabrication and piezoelectric properties of BaTiO 3 /BaTiO 3 -Bi(Mg 1/2 Ti 1/2 )O 3 -BiFeO 3 composites. Ceramics International, 2018, 44, 10657-10662.	4.8	5
72	Effect of powder size in BiFeO <sub>3</sub> -based piezoelectric ceramics fabricated by spark plasma sintering. Journal of the Ceramic Society of Japan, 2018, 126, 311-315.	1.1	5

#	Article	IF	CITATIONS
73	Influence of post-annealing treatment on dielectric and ferroelectric properties of dense BaTiO <sub>3</sub> ceramics prepared by solvothermal solidification method. Journal of the Ceramic Society of Japan, 2019, 127, 414-420.	1.1	5
74	Optimization of preparation conditions of highly textured piezoelectric (Bi <sub>0.5</sub> K <sub>0.5</sub> )TiO <sub>3</sub> ceramics. Journal of the Ceramic Society of Japan, 2019, 127, 362-368.	1.1	5
75	Variation of leakage current conduction mechanism by heat treatment in Bi-based lead-free piezoelectric ceramics. Journal of Applied Physics, 2021, 129, .	2.5	5
76	The Dielectric and Piezoelectric Properties of KNbO <sub>3</sub> / BaTiO <sub>3</sub> Composites With A Wide BaTiO <sub>3</sub> Size Distribution. Transactions of the Materials Research Society of Japan, 2013, 38, 57-60.	0.2	5
77	Fabrication of 〈111〉-oriented BaTiO <sub>3</sub> ceramics by high magnetic field electrophoretic deposition using hexagonal-tetragonal co-existing BaTiO <sub>3</sub> powder. Journal of the Ceramic Society of Japan, 2020, 128, 469-474.	1.1	5
78	Crystal Structure of BaTiO3–KNbO3Nanocomposite Ceramics: Relationship between Dielectric Property and Structure of Heteroepitaxial Interface. Japanese Journal of Applied Physics, 2012, 51, 09LEO5.	1.5	5
79	Preparation and Characterization of Grain-Oriented Barium Titanate Ceramics Using Electrophoresis Deposition Method under a High Magnetic Field. Key Engineering Materials, 2011, 485, 313-316.	0.4	4
80	Microstructure Control of Barium Titanate Grain-Oriented Ceramics and their Piezoelectric Properties. Key Engineering Materials, 2011, 485, 77-80.	0.4	4
81	Enhanced piezoelectric properties of barium titanate–potassium niobate nano-structured ceramics by MPB engineering. Ceramics International, 2013, 39, S97-S102.	4.8	4
82	Influence of Li doping on domain wall motion in Pb(Zr0.52Ti0.48)O3 films. Journal of Materials Science, 2014, 49, 7883-7889.	3.7	4
83	Effect of ball-milling time and surfactant content for fabrication of 0.85(Bi <sub>0.5</sub> Na <sub>0.5</sub> )TiO <sub>3</sub> :0.15BaTiO <sub&g 126,="" 2018,="" 542-546.<="" by="" ceramic="" ceramics="" deposition.="" electrophoretic="" green="" japan,="" journal="" of="" society="" td="" the=""><td>;t;3<td>b&gt;</td></td></sub&g>	;t;3 <td>b&gt;</td>	b>
84	Short- and middle-range order structures of KNbO3 nanocrystals. Japanese Journal of Applied Physics, 2019, 58, SLLA03.	1.5	4
85	Fabrication of Textured BaTiO <sub>3</sub> Ceramics by Electrophoretic Deposition in A High Magnetic Field using Single-domain Particles. Transactions of the Materials Research Society of Japan, 2013, 38, 41-44.	0.2	4
86	Preparation of Potassium Niobate–Barium Titanate Ceramics Using Well-Dispersed Nanoparticles and their Dielectric Properties. Key Engineering Materials, 0, 485, 39-42.	0.4	3
87	Structural study of heat-treated BaTiO <sub>3</sub> –KNbO <sub>3</sub> nanocomposites with heteroepitaxial interface by synchrotron radiation powder diffraction. Journal of the Ceramic Society of Japan, 2013, 121, 602-605.	1.1	3
88	Domain structures of (Li,Na)NbO3 epitaxial films. Journal of Applied Physics, 2017, 122, 044104.	2.5	3
89	Synthesis of LaNiO <sub>3</sub> –(Bi <sub>1/2</sub> K <sub>1/2</sub> )TiO <sub>3<!-- core–shell nanoparticles with epitaxial interfaces by the hydrothermal method for use in boundary laver capacitors, lournal of the Ceramic Society of Iapan, 2018, 126, 306-310.</td--><td>sub&gt;</td><td>3</td></sub>	sub>	3
90	Structural fluctuation of Pb(Mg1/3Nb2/3)O3 in the cubic phase. Japanese Journal of Applied Physics, 2019, 58, SLLA06.	1.5	3

#	Article	IF	Citations
91	Fabrication of [Li <sub>0.05</sub> (K <sub>0.5</sub> Na <sub>0.5</sub> ) <sub>0.95</sub> ]NbO <sub>3</sub> transparent ceramics using conventional sintering technique. Journal of the Ceramic Society of Japan, 2019, 127, 905-911.	1.1	3
92	Phase evolution and <110>â€orientation mechanism in RTGGâ€processed BaTiO 3 ceramics with electrical properties. Journal of the American Ceramic Society, 2021, 104, 4649-4658.	3.8	3
93	The ferroelectric phase transition in a 500 nm sized single particle of BaTiO <sub>3</sub> tracked by coherent X-ray diffraction. Japanese Journal of Applied Physics, 2022, 61, SN1008.	1.5	3
94	Development of Electric Power Measurement for Energy Harvesting Using Unimorph-Type Piezoceramics. Key Engineering Materials, 2011, 485, 173-176.	0.4	2
95	Preparation and Dielectric Properties of Dense Barium Titanate Nanoparticle Accumulations by Electrophoresis Deposition Method. Key Engineering Materials, 2011, 485, 35-38.	0.4	2
96	Single Phase Formation and Electric Properties of Bismuth Niobium Based Perovskite-Type Oxides. Key Engineering Materials, 0, 485, 81-84.	0.4	2
97	Piezoelectric enhancement of new ceramics with artificial MPB engineering. Sensors and Actuators A: Physical, 2013, 200, 26-30.	4.1	2
98	Preparation of Barium Titanate Grain-Oriented Ceramics by Electrophoresis Deposition Method under High Magnetic Field Using Single-Domain Nanoparticles. Key Engineering Materials, 2013, 582, 27-31.	0.4	2
99	Preparation of Bismuth Copper Based Perovskite-Type Ceramics and their Piezoelectric Properties. Key Engineering Materials, 2013, 566, 85-88.	0.4	2
100	Microstructure and Piezoelectric Properties of BaTiO <sub>3</sub> -Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> -BiFeO <sub>3</sub> Ceramics. Key Engineering Materials, 2013, 566, 59-63.	0.4	2
101	Microstructure Control of Potassium Niobate Porous Ceramics and their Sensor Properties. Key Engineering Materials, 0, 566, 241-244.	0.4	2
102	Preparation of Potassium Niobate-Coated Barium Titanate Accumulation Ceramics by Solvothermal Synthesis and Enhancement of Piezoelectric Property. Key Engineering Materials, 2013, 566, 76-80.	0.4	2
103	Chemical Composition of Dielectric and Piezoelectric Properties for BaTiO <sub>3</sub> -Bi (Mg <sub>1/2</sub> 1/21/23-BiFeO <sub>3</sub> 5333 <td>&amp;g4</td> <td>2</td>	&g4	2
104	Hydrothermal Synthesis of BiFeO <sub>3</sub> Fine Particles. Transactions of the Materials Research Society of Japan, 2013, 38, 53-55.	0.2	2
105	Preparation of Mn-doped (Bi <sub>0.5</sub> K <sub>0.5</sub> )TiO <sub>3</sub> -Bi(Mg <sub>0.5</sub> Ti <sub>0.5</sub> )O <sub>3</sub> -Ceramics Using BiFeO <sub>3</sub> Particle Synthesized by Hydrothermal Method and Their Piezoelectric Properties, Transactions of the Materials Research Society of Japan, 2014, 39, 137-140.	·BiFeO <su 0.2</su 	b>3
106	Dielectric properties of BT-BT and BF-BT composites. Ferroelectrics, 2018, 533, 145-150.	0.6	2
107	Effect of oxygen partial pressure during sintering on electric properties of BiFeO <sub>3</sub> -based piezoelectric ceramics. Journal of the Ceramic Society of Japan, 2019, 127, 383-387.	1.1	2
108	Preparation of Strontium Titanate Nanocubes Using Titanium Alkoxide and their Accumulations by Capillary Force. Key Engineering Materials, 2011, 485, 309-312.	0.4	1

#	Article	IF	Citations
109	(Ag,Li)NbO <inf>3</inf> thin films fabricated on (001), (110), and (111)SrTiO <inf>3</inf> substrates by pulsed laser deposition., 2013,,.		1
110	Preparation of Barium Titanate Porous Ceramics and their Piezoelectric Power Generation Property. Key Engineering Materials, 0, 566, 41-44.	0.4	1
111	Laser scanning microscopy observation of domain switching in NaNbO <inf>3</inf> epitaxial film., 2013,,.		1
112	Microstructure Control of Porous Barium Titanate Ceramics and their Sensor Properties. Key Engineering Materials, 2013, 582, 32-35.	0.4	1
113	Preparation of BaZrO <sub>3</sub> Nanocrystals at Low Temperature. Key Engineering Materials, 0, 582, 165-168.	0.4	1
114	Enhanced piezoelectric properties of (Ba0.3Bi0.7)(Mg0.05Fe0.6Ti0.35)O3 piezoelectric ceramics with high Curie temperature. Journal of Advanced Dielectrics, 2014, 04, 1450005.	2.4	1
115	Synthesis and crystal structure of a new bismuth tin titanate with the pyrochlore-type structure. Journal of the Ceramic Society of Japan, 2019, 127, 952-957.	1.1	1
116	Fabrication of Textured Ceramics Using Mn and Nb-doped Hexagonal BaTiO <sub>3</sub> by an Electrophoretic Deposition in a High Magnetic Field. Transactions of the Materials Research Society of Japan, 2014, 39, 199-202.	0.2	1
117	Piezoelectric enhancement of relaxor-based lead-free piezoelectric ceramics by nanodomain engineering. , 2012, , .		0
118	Preparation and Characterization of Highly-Dispersed and Highly-Crystalline Barium Titanate Nanoparticles. Key Engineering Materials, 2013, 566, 273-276.	0.4	0
119	Fabrication of lead-free ferroelectric (Na,K)NbO <inf>3</inf> thin films by pulsed laser deposition. , 2013, , .		O
120	Preparation of Potassium Niobate/Barium Titanate Nanocomposite Ceramics with a Wide Barium Titanate Particle Size Distribution and their Dielectric Properties. Key Engineering Materials, 2013, 582, 76-79.	0.4	0
121	Preparation of Barium Titanate/Strontium Titanate Nanocube Accumulation Ceramics and their Dielectric Property. Key Engineering Materials, 0, 582, 169-173.	0.4	0
122	Preparation of Barium Titanate/Strontium Titanate Accumulation Ceramics with Necking Structure of Strontium Titanate Nanocubes. Key Engineering Materials, 2013, 582, 67-70.	0.4	0
123	Preparation of Grain-Oriented Ceramics with Bismuth Potassium Titanate-Barium Titanate and their Piezoelectric Properties. Key Engineering Materials, 0, 582, 80-83.	0.4	O
124	Preparation of (Bi <sub>1/2</sub> K <sub>1/2</sub> )TiO3-Bi(Mg <sub>1/2</sub> Ti <sub>1/2</sub> )O <sub>3</sub> -BiFeO <sub>Ceramics Withnanodomain Structure and their Piezoelectric Properties. Key Engineering Materials, 2013, 582, 88-91.</sub>	3 <sub>6</sub> /sub>	0
125	Preparation of Strontium Titanate Nanocube Particles Using Complex Titanium Raw Materials and their Accumulations. Key Engineering Materials, 0, 566, 298-301.	0.4	O
126	Effect of Hydrothermal Treatment on the Piezoelectric Response of Oriented Barium Titanate Ceramics. Key Engineering Materials, 2013, 566, 45-49.	0.4	0

#	Article	IF	Citations
127	Grain Size Dependence of the Microstructure and Dielectric Properties of Potassium Niobate-Barium Titanate Ceramics. Key Engineering Materials, 0, 566, 34-37.	0.4	0
128	Preparation of Strontium Titanate-Coated Barium Titanate Accumulation Ceramics by Solvothermal Synthesis and their Dielectric Property. Key Engineering Materials, 0, 566, 293-297.	0.4	0
129	Preparation of Barium Titanate-Coated Strontium Titanate Accumulation Ceramics by Solvothermal Synthesis and their Dielectric Property. Key Engineering Materials, 0, 566, 289-292.	0.4	0
130	Preparation of Ceramics/Polymer Film Capacitor Using Barium Titanate Nanoparticles with High Dielectric Property and their Dielectric Property. Key Engineering Materials, 0, 566, 54-58.	0.4	0
131	Synthesis of BaZrO <sub>3</sub> nanocrystals by wet chemical reaction. Transactions of the Materials Research Society of Japan, 2013, 38, 45-48.	0.2	0
132	Preparation of Porous KNbO <sub>3</sub> Ceramics by Solvothermal Solidification Method. Transactions of the Materials Research Society of Japan, 2015, 40, 305-308.	0.2	0
133	Preparation of DC-bias-free (Ba, Sr)TiO <sub>3</sub> -Bi(Mg, Ti)O <sub>3</sub> -NaNbO <sub>3</sub> -Ceramics with Reduced Temperature Dependent Dielectric Properties. Transactions of the Materials Research Society of Japan, 2015, 40, 409-412.	0.2	0
134	Large Electric-field-induced Strain in Pseudo-cubic BaTiO <sub>3</sub> -0.5-0.5-0.5-0.5-0.5-0.5-0.5-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5<-0.5&	su <b>b</b> >-B	iFe <b>©</b> <sub&
135	Structural Study of Ferroelectrics under Applied Electric Field. Nihon Kessho Gakkaishi, 2016, 58, 167-173.	0.0	0
136	Fabrication of (K, Na)NbO3 films by pulsed laser deposition and their domain observation., 2019,, 61-80.		0
137	Fabrication of $<111>$ c-oriented (K0.5Na0.5)NbO3 Single Crystal by Solid-State Cyrstal Growth Method., 2020,,.		0
138	Preparation of Bismuthï½Based Perovskites with Non-integer A and B Site Valence and Their Properties. Transactions of the Materials Research Society of Japan, 2013, 38, 49-52.	0.2	0
139	Piezoelectric and Dielectric Enhancement of New Nano-structured Ceramics with Heteroepitaxial Interfaces. Additional Conferences (Device Packaging HiTEC HiTEN & CICMT), 2013, 2013, 000001-000004.	0.2	0
140	Dielectric and Piezoelectric Properties of Barium Titanate – Potassium Niobate Nano-structured Ceramics with Artificial MPB Structure. Transactions of the Materials Research Society of Japan, 2014, 39, 113-115.	0.2	0