

# Sulaiman W Harun

## List of Publications by Year in descending order

Source: <https://exaly.com/author-pdf/9517225/publications.pdf>

Version: 2024-02-01

964  
papers

12,321  
citations

44444

50  
h-index

134545

62  
g-index

969  
all docs

969  
docs citations

969  
times ranked

4835  
citing authors

#	ARTICLE	IF	CITATIONS
1	Passively Femtosecond Mode-Locked Erbium-Doped Fiber Oscillator with External Pulse Compressor for Frequency Comb Generation. <i>Journal of Optical Communications</i> , 2024, 44, s683-s690.	4.0	1
2	Lanthanum hexaboride for Q-switching and mode-locking applications. <i>Optics Communications</i> , 2022, 502, 127396.	1.0	7
3	Q-switched fiber laser with tunable wavelength operation utilizing a nonlinear saturable absorption of vanadium pentoxide. <i>Indian Journal of Physics</i> , 2022, 96, 281-287.	0.9	4
4	Optical properties enhancement with multilayer coating technique of additive-enhanced zinc oxide nanostructure for fiber Bragg grating humidity sensor. <i>Microwave and Optical Technology Letters</i> , 2022, 64, 184-189.	0.9	1
5	Gain clamping in band zirconium-erbium co-doped fiber amplifier with FBG based lasing control. <i>Microwave and Optical Technology Letters</i> , 2022, 64, 389.	0.9	0
6	Chromium aluminum carbide as Q-switcher for the near-infrared erbium-doped fiber laser. <i>Optik</i> , 2022, 250, 168362.	1.4	9
7	Poly(3,4-ethylenedioxythiophene): Poly(styrenesulfonate) spin-coated onto polyvinyl alcohol film as saturable absorber for generating Q-switched laser at 1.5 $\mu\text{m}$ region. <i>Optical Fiber Technology</i> , 2022, 68, 102763.	1.4	3
8	Sequential generation of self-starting diverse operations in all-fiber laser based on thulium-doped fiber saturable absorber. <i>Chinese Physics B</i> , 2022, 31, 064204.	0.7	2
9	Vanadium pentoxide film for microsecond pulse generation in 1.5 $\mu\text{m}$ region. <i>Optoelectronics Letters</i> , 2022, 18, 29-34.	0.4	2
10	A Review: Surface Plasmon Resonance-Based Biosensor for Early Screening of SARS-CoV2 Infection. <i>IEEE Access</i> , 2022, 10, 1228-1244.	2.6	13
11	Iron pyrite absorber for ultrashort pulse generation. <i>Infrared Physics and Technology</i> , 2022, 120, 103999.	1.3	1
12	Development of FBG Humidity Sensor via Controlled Annealing Temperature of Additive Enhanced ZnO Nanostructure Coating. <i>Optical Fiber Technology</i> , 2022, 68, 102802.	1.4	6
13	Nanosecond Q-switched laser with PEDOT: PSS saturable absorber. <i>Applied Optics</i> , 2022, 61, 1292.	0.9	6
14	Ultrashort pulse generation in All-fiber Erbium-doped fiber cavity with thulium doped fiber saturable absorber. <i>Optics and Laser Technology</i> , 2022, 149, 107888.	2.2	5
15	Broadband ASE source for S + C + L bands using hafnia-bismuth based erbium co-doped fibers. <i>Optik</i> , 2022, 255, 168723.	1.4	2
16	Graphene Oxide/Gold Coated Kretschmann Surface Plasmon Resonance Setup for Relative Humidity Detection. , 2022, 6, 1-4.		1
17	Mode-Locked YDFL Using Topological Insulator Bismuth Selenide Nanosheets as the Saturable Absorber. <i>Crystals</i> , 2022, 12, 489.	1.0	21
18	Q-switched neodymium-doped fiber laser with a gold nanoparticle saturable absorber. <i>Microwave and Optical Technology Letters</i> , 2022, 64, 1302-1309.	0.9	6

#	ARTICLE	IF	CITATIONS
19	Effect of MAX phase chromium aluminum carbide thin film thickness on Q-switched Erbium-doped fiber lasers. <i>Optical Fiber Technology</i> , 2022, 70, 102853.	1.4	8
20	Generation of Kelly and dip type sidebands soliton employing Topological insulator (Bi <sub>2</sub> Te <sub>3</sub> ) as saturable absorber. <i>Infrared Physics and Technology</i> , 2022, 123, 104154.	1.3	14
21	Review: Dark pulse generation in fiber laser system. <i>Optics and Laser Technology</i> , 2022, 151, 108056.	2.2	6
22	Picosecond Soliton Pulse Generation with a Zinc Phthalocyanine Thin-Film Saturable Absorber Via Mode Locking in an Erbium-Doped Fiber Laser Cavity. <i>Journal of Russian Laser Research</i> , 2022, 43, 193.	0.3	1
23	Passively mode-locked erbium-doped fiber laser based on a nanodiamond saturable absorber. <i>Applied Optics</i> , 2022, 61, 4047.	0.9	7
24	Soliton picosecond pulse generation with a spin-coated PEDOT: PSS thin film. <i>Journal of Luminescence</i> , 2022, 247, 118879.	1.5	6
25	Characteristics of the 11-Mercaptoundecanoic Acid (11-MUA) Binding to Gold Surface as Self-Assembled Monolayer (SAM) for SPR based Biosensor. , 2022, , .		0
26	Rare-earth Yttrium oxide as Q-switcher in fiber laser system. <i>Results in Optics</i> , 2022, 8, 100252.	0.9	1
27	Mode-locked ytterbium-doped fiber laser with zinc phthalocyanine thin film saturable absorber. <i>Frontiers of Optoelectronics</i> , 2022, 15, .	1.9	3
28	Q-switched fiber laser in C-band region using metal ceramic-based saturable absorber. <i>Optik</i> , 2022, 264, 169395.	1.4	7
29	Passively mode-locked laser using HfSe <sub>2</sub> as saturable absorber at 1.5 $\mu$ m and 2.0 $\mu$ m. <i>Optics and Laser Technology</i> , 2022, 155, 108397.	2.2	3
30	Yttrium Oxide (Y <sub>2</sub> O <sub>3</sub> ) as a Pulse Initiator in a Mode-Locking Erbium-Doped Fiber Laser. <i>Photonics</i> , 2022, 9, 486.	0.9	5
31	Q-switched tunable fiber laser with aluminum oxide saturable absorber and Sagnac loop mirror. <i>Indian Journal of Physics</i> , 2021, 95, 1887-1893.	0.9	2
32	Q-switched tunable fiber laser utilizing silver nanoparticles deposited onto PVA film as saturable absorber. <i>Indian Journal of Physics</i> , 2021, 95, 141-145.	0.9	1
33	Single-Mode Modified Tapered Fiber Structure Functionalized With GO-PVA Composite Layer for Relative Humidity Sensing. <i>Photonic Sensors</i> , 2021, 11, 314-324.	2.5	17
34	Mode-locked operation with 9kW peak power using Au nanoparticles saturable absorber. <i>Optik</i> , 2021, 227, 165976.	1.4	9
35	C-band tunable Q-switched fiber laser based on Alq <sub>3</sub> as a saturable absorber. <i>Results in Optics</i> , 2021, 2, 100036.	0.9	3
36	8-Hydroxyquinolino cadmium chloride hydrate for generating nanosecond and picosecond pulses in erbium-doped fiber laser cavity. <i>Optical Fiber Technology</i> , 2021, 61, 102439.	1.4	6

#	ARTICLE	IF	CITATIONS
37	Reduction-controlled graphene oxide saturable absorbers and its effect on ultrashort Er-doped fibre laser. IET Optoelectronics, 2021, 15, 61-68.	1.8	0
38	Performance analysis of WDM-SDM system with employing Phase-Conjugated twin waves technique. Materials Today: Proceedings, 2021, 42, 2490-2496.	0.9	3
39	Characterization of hysteresis free, low-temperature hydrothermally synthesized zinc oxide for enhanced humidity sensing. Sensors International, 2021, 2, 100106.	4.9	3
40	Passively Q-switched Ytterbium-doped fiber laser using zinc phthalocyanine thin film as saturable absorber. Optik, 2021, 228, 165736.	1.4	2
41	Ultra-short pulse generating in erbium-doped fiber laser cavity with 8-Hydroxyquinolino cadmium chloride hydrate ( $8\text{-HQCdCl}_2 \cdot 2\text{H}_2\text{O}$ ) saturable absorber. Journal of Modern Optics, 2021, 68, 237-245.	0.6	9
42	Effect of agarose concentration on coated micro-bottle resonators for humidity detection. Microwave and Optical Technology Letters, 2021, 63, 1826-1831.	0.9	2
43	Passively Q-Switched Pulses Generation from Erbium-Doped Fiber Laser Using Lutetium Oxide as Saturable Absorber. Journal of Microwaves, Optoelectronics and Electromagnetic Applications, 2021, 20, 118-125.	0.4	1
44	Passively mode-locked laser at $1\frac{1}{4}\mu\text{m}$ region based on tungsten trioxide ( $\text{WO}_3$ ) saturable absorber. Optik, 2021, 231, 166377.	1.4	16
45	Aluminium zinc oxide as a saturable absorber for passively Q-switched and mode-locked erbium-doped fiber laser. Laser Physics, 2021, 31, 055101.	0.6	15
46	Gain clamping performance of Hafnia-bismuth-erbium co-doped fibre amplifier using lasing controlled structure with FBG. Journal of Modern Optics, 2021, 68, 457-462.	0.6	2
47	Passively Q-switched erbium-doped fiber laser with graphene oxide film as saturable absorber. Journal of Physics: Conference Series, 2021, 1869, 012158.	0.3	3
48	Ultrafast soliton mode-locked fiber laser at $1560\text{nm}$ based on $\text{Znq}_2$ as a saturable absorber. Applied Optics, 2021, 60, 3149.	0.9	8
49	HEC/PVDF coated microbottle resonators for relative humidity detection. Optik, 2021, 232, 166534.	1.4	1
50	Ultrashort pulse laser at $1564.3\text{Ånm}$ wavelength with E-beam deposited copper nanoparticles saturable absorber. Optics and Laser Technology, 2021, 136, 106791.	2.2	8
51	Ultrashort pulse generation with MXene $\text{Ti}_3\text{C}_2\text{T}_x$ embedded in PVA and deposited onto D-shaped fiber. Optics and Laser Technology, 2021, 136, 106780.	2.2	13
52	Bismuth-doped fiber Q-switcher in erbium-doped fiber laser cavity. Microwave and Optical Technology Letters, 2021, 63, 2214-2218.	0.9	5
53	Q-switched and mode-locked laser based on aluminium zinc oxide deposited onto D-shape fiber as a saturable absorber. Results in Optics, 2021, 3, 100057.	0.9	10
54	Applied whispering gallery modes on ZnO nanorods coated glass for humidity sensing application. Optoelectronics Letters, 2021, 17, 298-301.	0.4	2

#	ARTICLE	IF	CITATIONS
55	Agarose coated micro-bottle sensor for relative humidity detection. Optoelectronics Letters, 2021, 17, 328-333.	0.4	2
56	Sodium Carbonate for Generating Q-Switched Pulses in 1550 nm Region. Fiber and Integrated Optics, 2021, 40, 292-303.	1.7	2
57	Ultrafast laser soliton mode-locked at 1.5 $\mu$ m region based on Cr <sub>2</sub> AlC MAX phase as a saturable absorber. Optical Engineering, 2021, 60, .	0.5	20
58	Simple Fabrication of Bismuth Telluride Used as Saturable Absorber for Generating Microsecond Pulse Fiber Laser. , 2021, , .		0
59	Nanosecond passively Q-switched fiber laser in the 1.5 $\mu$ m region using turmeric saturable absorber. Optics and Laser Technology, 2021, 139, 106971.	2.2	12
60	Gold nanoparticles film for Q-switched pulse generation in thulium doped fiber laser cavity. Optoelectronics Letters, 2021, 17, 449-453.	0.4	3
61	Humidity sensing using microfiber-ZnO nanorods coated glass structure. Optik, 2021, 238, 166715.	1.4	11
62	Titanium carbide MXene for generating Q-switched pulses in erbium-doped fiber laser cavity. Microwave and Optical Technology Letters, 2021, 63, 2893-2897.	0.9	0
63	Q-switched pulse generation in a bidirectionally pumped EDFL utilizing Lu <sub>2</sub> O <sub>3</sub> as saturable absorber. Optoelectronics Letters, 2021, 17, 529-533.	0.4	2
64	Lawsone dye material as potential saturable absorber for Q-switched erbium doped fiber laser. Optical Fiber Technology, 2021, 64, 102537.	1.4	6
65	Formaldehyde sensor with enhanced performance using microsphere resonator-coupled ZnO nanorods coated glass. Optics and Laser Technology, 2021, 139, 106853.	2.2	10
66	Nanosecond Q-switched pulse generation using poly(3,4 ethylenedioxythiophene): Poly(4-styrenesulfonate) thin film as saturable absorber. Infrared Physics and Technology, 2021, 116, 103788.	1.3	8
67	Acetone Liquid Sensing Based on Fiber Optic Mach-Zehnder Interferometer. , 2021, , .		1
68	Thermally stable and fast responsive mesoporous cresol red functionalized silica and titania nanomaterials: fiber optic pH sensors. Journal of Sol-Gel Science and Technology, 2021, 99, 497-511.	1.1	5
69	Application of black phosphorus for pulse generation in erbium-doped fiber laser. Results in Optics, 2021, 4, 100091.	0.9	8
70	MXene Ti <sub>3</sub> C <sub>2</sub> T <sub>x</sub> thin film as a saturable absorber for passively mode-locked and Q-switched fibre laser. Journal of Modern Optics, 2021, 68, 984-993.	0.6	7
71	Passively Q-switched erbium-doped fiber laser with mechanical exfoliation of 8-HQCDCL <sub>2</sub> H <sub>2</sub> O as saturable absorber. Optik, 2021, 242, 167073.	1.4	14
72	Micro-bottle resonator for sodium hypochlorite sensor. Optik, 2021, 242, 167328.	1.4	1

#	ARTICLE	IF	CITATIONS
73	Concentration measurement of opaque dye solution using a non-contact fiber displacement sensor. <i>Optical Fiber Technology</i> , 2021, 65, 102624.	1.4	1
74	Effect of polyvinyl alcohol coating microbottle resonator for sodium hypochlorite concentration sensing. <i>Optik</i> , 2021, 242, 166824.	1.4	2
75	Hygroscopicity Enhancement of Low Temperature Hydrothermally Synthesized Zinc Oxide Nanostructure with Heterocyclic Organic Compound for Humidity Sensitization. <i>Sensors and Actuators B: Chemical</i> , 2021, 345, 130010.	4.0	8
76	Optically functionalized hierarchical hematite assembled silica-titania nanocomposites for hydrocarbon detection: Fiber optic chemical sensor. <i>Microporous and Mesoporous Materials</i> , 2021, 326, 111398.	2.2	4
77	Synthesis of silver nanoparticles using chemical reduction techniques for Q-switcher at 1.5 $\mu\text{m}$ region. <i>Optik</i> , 2021, 244, 167621.	1.4	8
78	Polyvinyl alcohol coating microbottle resonator on whispering gallery modes for ethanol liquid sensor. <i>Optics and Laser Technology</i> , 2021, 143, 107379.	2.2	4
79	Ti <sub>3</sub> AlC <sub>2</sub> MAX phase thin film as saturable absorber for generating soliton mode-locked fiber laser. <i>Optik</i> , 2021, 245, 167767.	1.4	11
80	Integrating microsphere resonator and ZnO nanorods coated glass for humidity sensing application. <i>Optics and Laser Technology</i> , 2021, 143, 107356.	2.2	9
81	The effects of different parameters and interaction angles of a 532 $\text{nm}$ pulsed Nd: YAG laser on the properties of laser-ablated silver nanoparticles. <i>Optics Communications</i> , 2021, 501, 127366.	1.0	7
82	Absorption, fluorescence and sensing quality of Rose Bengal dye-encapsulated cinnamon nanoparticles. <i>Sensors and Actuators A: Physical</i> , 2021, 332, 113055.	2.0	5
83	Stretched-pulse generation in all-fiber mode-locked erbium-doped fiber laser using Lawsone dye saturable absorber. <i>Results in Optics</i> , 2021, 5, 100148.	0.9	2
84	Generation of Q-switched fiber laser at 1.0-, 1.55- and 2.0 $\mu\text{m}$ employing a spent coffee ground based saturable absorber. <i>Optical Fiber Technology</i> , 2021, 61, 102434.	1.4	7
85	Graphene/PVA coated D-shaped fiber for sodium nitrate sensing. <i>Sensors and Actuators A: Physical</i> , 2021, 332, 113163.	2.0	5
86	Evanescent field interaction of 1550 $\text{nm}$ pulsed laser with silver nanomaterial coated D-shape fiber. <i>Infrared Physics and Technology</i> , 2021, 119, 103920.	1.3	4
87	Dark Pulse Mode-locked Laser based on Aluminum Zinc Oxide coated D-shape fiber as Saturable Absorber. <i>Fiber and Integrated Optics</i> , 2021, 40, 322-334.	1.7	1
88	Enhanced fiber mounting and etching technique for optimized optical power transmission at critical cladding thickness for fiber-sensing application. <i>Laser Physics</i> , 2021, 31, 126201.	0.6	4
89	Surface plasmon resonance optical sensor for COVID-19 detection. <i>Nanosystems: Physics, Chemistry, Mathematics</i> , 2021, 12, 575-582.	0.2	1
90	Hafnium Bismuth Erbium Co-Doped Fiber Based Dark Pulses Generation With Black Phosphorus As Saturable Absorber. <i>Journal of Physics: Conference Series</i> , 2021, 2075, 012018.	0.3	0

#	ARTICLE	IF	CITATIONS
91	The generation of nanosecond pulses at C-band region with titanium dioxide as a saturable absorber. Journal of Physics: Conference Series, 2021, 2075, 012013.	0.3	1
92	Optical Microfiber Sensor : A Review. Journal of Physics: Conference Series, 2021, 2075, 012021.	0.3	4
93	Q-switched Ytterbium-doped fibre laser using an 8 cm long Hafnium bismuth erbium co-doped fibre saturable absorber. Journal of Physics: Conference Series, 2021, 2075, 012020.	0.3	0
94	Generation of Passive Q-switched by using Graphene Oxide in Erbium Doped Fiber Laser. , 2021, , .		0
95	The Design of Optical Waveguide Sensor Based on Surface Plasmon Resonance. , 2021, , .		0
96	Nanosecond pulses generation with rose gold nanoparticles saturable absorber. Indian Journal of Physics, 2020, 94, 1079-1083.	0.9	6
97	Effect of PMMA and PVA coating on the performance of optical microbottle resonator humidity sensors. Microwave and Optical Technology Letters, 2020, 62, 993-998.	0.9	10
98	Q-switching pulses generation with samarium oxide film saturable absorber. Microwave and Optical Technology Letters, 2020, 62, 1049-1055.	0.9	4
99	Soliton mode-locked Er-doped fiber laser by using Alq3 saturable absorber. Optics and Laser Technology, 2020, 123, 105893.	2.2	15
100	All fiber multiwavelength Tm-doped double-clad fiber laser assisted by four-wave mixing in highly nonlinear fiber and Sagnac loop mirror. Optics Communications, 2020, 456, 124589.	1.0	14
101	Enhanced triple-pass hybrid erbium doped fiber amplifier using distribution pumping scheme in a dual-stage configuration. Optik, 2020, 204, 164191.	1.4	15
102	Bundled plastic optical fiber based sensor for ECG signal detection. Optik, 2020, 203, 164077.	1.4	6
103	Poly(3-hexylthiophene-2,5-diyl) regioregular (P3HT) thin film as saturable absorber for passively Q-switched and mode-locked Erbium-doped fiber laser. Optical Fiber Technology, 2020, 54, 102073.	1.4	17
104	Indium tin oxide coated D-shape fiber as saturable absorber for passively Q-switched erbium-doped fiber laser. Optics and Laser Technology, 2020, 124, 105998.	2.2	23
105	Alq 3 saturable absorber for generating Q-switched pulses in erbium-doped fiber laser. Microwave and Optical Technology Letters, 2020, 62, 1028-1032.	0.9	1
106	Low-profile folded dipole UHF RFID tag antenna with outer strip lines for metal mounting application. Turkish Journal of Electrical Engineering and Computer Sciences, 2020, 28, 2643-2656.	0.9	5
107	MAX phase Ti3AlC2 embedded in PVA and deposited onto D-shaped fiber as a passive Q-switcher for erbium-doped fiber laser. Optik, 2020, 224, 165682.	1.4	23
108	Q-switched erbium-doped fiber laser with silicon oxycarbide saturable absorber. Optik, 2020, 219, 165234.	1.4	9

#	ARTICLE	IF	CITATIONS
109	Tungsten trioxide (WO <sub>3</sub> ) film absorber for generating soliton mode-locked pulses in erbium laser. Optics and Laser Technology, 2020, 131, 106429.	2.2	26
110	Optical fiber coated with zinc oxide nanorods toward light side coupling for sensing application. , 2020, , 293-304.		4
111	Q-switched and tunable wavelength fiber laser utilizing nickel oxide saturable absorber and sagnac loop mirror filter. Infrared Physics and Technology, 2020, 109, 103433.	1.3	11
112	Dark pulse mode-locked fibre laser with zirconia-based erbium-doped fibre (Zr-EDF) and Black phosphorus saturable absorber. Optik, 2020, 223, 165635.	1.4	25
113	Rose gold nanoparticles film for generating Q-switched and mode-locked pulses. Results in Optics, 2020, 1, 100007.	0.9	2
114	Mechanical exfoliation of indium tin oxide as saturable absorber for Q-switched Ytterbium-doped and Erbium-doped fiber lasers. Optics Communications, 2020, 475, 126217.	1.0	18
115	Generation of Q-switched Erbium-Doped Fiber Laser Using Titanium Dioxide Film Based Saturable Absorber. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012018.	0.3	4
116	Microsecond Pulse Generation using Bismuth Salenide as Saturable Absorber in 1.5 $\mu$ m Region. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012037.	0.3	0
117	Q-switched Erbium-Doped Fiber Laser Incorporating Multi-Walled Carbon Nanotubes as a Saturable Absorber. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012059.	0.3	0
118	Fibre-based Saturable Absorbers for Pulsed Generations in the 1-micron Region. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012071.	0.3	0
119	Microbottle-Resonator Ethanol Liquid Sensor. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012075.	0.3	4
120	NiS <sub>2</sub> as a broadband saturable absorber for ultrafast pulse lasers. Optics and Laser Technology, 2020, 132, 106492.	2.2	16
121	Non-contact Fiber Optic Displacement Sensor for Sugar Concentration Detection. Journal of Physics: Conference Series, 2020, 1484, 012006.	0.3	1
122	D-shape Fiber Coated with Indium Tin Oxide for Temperature Sensor Application. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012016.	0.3	1
123	Inducing Q-switching operation at 1-micron all-fiber laser via lutetium oxide film saturable absorber. Optik, 2020, 219, 165267.	1.4	5
124	Sc <sub>2</sub> O <sub>3</sub> PVA Film for Switching and Mode-Locking Application in Erbium-Doped Fiber Laser Cavity. Fiber and Integrated Optics, 2020, 39, 137-148.	1.7	4
125	Optical and Photoacoustic Properties of Laser-Ablated Silver Nanoparticles in a Carbon Dots Solution. Molecules, 2020, 25, 5798.	1.7	5
126	Passively Q-switched Erbium-doped Fiber Laser using Tungsten Disulfide deposited D-shaped Fiber as Saturable Absorber. IOP Conference Series: Materials Science and Engineering, 2020, 854, 012021.	0.3	0



#	ARTICLE	IF	CITATIONS
127	Femtosecond mode-locked laser at 1.5 $\mu$ m region using turmeric-based saturable absorber. Infrared Physics and Technology, 2020, 111, 103548.	1.3	13
128	Power-dependent nonlinear optical behaviours of ponceau BS chromophore at 532 nm via Z-scan technique. Journal of Photochemistry and Photobiology A: Chemistry, 2020, 397, 112574.	2.0	17
129	Bismuth-doped fiber as Q-switcher in hafnium bismuth erbium co-doped fiber laser. Microwave and Optical Technology Letters, 2020, 62, 3634-3639.	0.9	5
130	Electron beam deposited silver (Ag) saturable absorber as passive Q-switcher in 1.5- and 2-micron fiber lasers. Optik, 2020, 207, 164455.	1.4	8
131	Zinc phthalocyanine thin film as saturable absorber for Q-switched pulse generation. Optical Fiber Technology, 2020, 57, 102235.	1.4	5
132	MXene Ti3C2Tx as a passive Q-switcher for erbium-doped fiber laser. Optical Fiber Technology, 2020, 58, 102289.	1.4	20
133	Indium Tin Oxide Coated D-Shape Fiber as a Saturable Absorber for Generating a Dark Pulse Mode-Locked Laser*. Chinese Physics Letters, 2020, 37, 054202.	1.3	24
134	Sodium nitrate sensor based on D-shaped fiber structure. Measurement: Journal of the International Measurement Confederation, 2020, 163, 107927.	2.5	7
135	Humidity Effects on the Growth of ZnO Nanorods using Hydrothermal Method. Journal of Physics: Conference Series, 2020, 1552, 012004.	0.3	1
136	MEH-PPV organic material as saturable absorber for Q-switching and mode-locking applications. Journal of Modern Optics, 2020, 67, 746-753.	0.6	5
137	Generation of Q-switched and mode-locked pulses with Eu2O3 saturable absorber. Optics and Laser Technology, 2020, 127, 106163.	2.2	27
138	Side-Polished Optical Fiber Structure for Sodium Nitrate Sensor. IEEE Sensors Journal, 2020, 20, 5929-5934.	2.4	3
139	U-Shaped Inductively Coupled Feed UHF RFID Tag Antenna With DMS for Metal Objects. IEEE Antennas and Wireless Propagation Letters, 2020, 19, 907-911.	2.4	10
140	FBG Sensors for Environmental and Biochemical Applications—A Review. IEEE Sensors Journal, 2020, 20, 7614-7627.	2.4	70
141	MAX phase based saturable absorber for mode-locked erbium-doped fiber laser. Optics and Laser Technology, 2020, 127, 106186.	2.2	53
142	Mode-locked laser at 1066nm by using Alq3 as saturable absorber in all-fiber based cavity. Optik, 2020, 219, 165179.	1.4	10
143	Thulium oxide film as a passive saturable absorber for pulsed fiber laser generation. Optical Fiber Technology, 2020, 58, 102249.	1.4	5
144	Copper nanoparticles-chitosan based saturable absorber in passively Q-switched erbium doped fiber laser. AIP Conference Proceedings, 2020, , .	0.3	4

#	ARTICLE	IF	CITATIONS
145	Tungsten tri-oxide (WO <sub>3</sub> ) film absorber for generating Q-switched pulses in erbium laser. Journal of Modern Optics, 2020, 67, 374-382.	0.6	18
146	Mode-locked erbium-doped fiber laser via evanescent field interaction with indium tin oxide. Optical Fiber Technology, 2020, 55, 102124.	1.4	15
147	PMMA microfiber and Microball Resonator for formaldehyde liquid sensing. Sensors and Actuators A: Physical, 2020, 304, 111828.	2.0	2
148	ZnO nanorods coated microfiber loop resonator for relative humidity sensing. Optical Fiber Technology, 2020, 54, 102080.	1.4	10
149	Optimizing waist diameter of microfiber-ZnO nanorods structure for humidity sensing application. AIP Conference Proceedings, 2020, , .	0.3	1
150	Precursors to non-invasive clinical dengue screening: Multivariate signature analysis of in-vivo diffuse skin reflectance spectroscopy on febrile patients in Malaysia. PLoS ONE, 2020, 15, e0228923.	1.1	2
151	Detection of seismograph signal using fiber bundle sensor. Optik, 2020, 208, 164554.	1.4	5
152	Efficiency enhancement of phase-conjugated twin waves technique by shaping envelopes of subcarriers in all-optical OFDM systems. Optics Communications, 2020, 472, 125864.	1.0	1
153	ZnO nanorod-coated tapered plastic fiber sensors for relative humidity. Optics Communications, 2020, 473, 125924.	1.0	12
154	Q-switched and mode-locked erbium-doped fiber laser using gadolinium oxide as saturable absorber. Optical Fiber Technology, 2020, 57, 102209.	1.4	15
155	Femtosecond mode-locked erbium-doped fibre laser with Alq 3 saturable absorber. IET Optoelectronics, 2020, 14, 234-241.	1.8	4
156	Gain-flattened hybrid EDFA operating in C+L band with parallel pumping distribution technique. IET Optoelectronics, 2020, 14, 447-451.	1.8	12
157	Q-Switched YDFL generation by a MAX phase saturable absorber. Applied Optics, 2020, 59, 5408.	0.9	19
158	Soliton mode-locked pulse generation with a bulk structured MXene Ti <sub>3</sub> AlC <sub>2</sub> deposited onto a D-shaped fiber. Applied Optics, 2020, 59, 8759.	0.9	13
159	Passively Q-switched pulses from ytterbium-doped fiber laser (YDFL) using copper oxide (CuO) nanoparticles as a saturable absorber. Optical Materials Express, 2020, 10, 2896.	1.6	9
160	Formaldehyde sensing using micro-loop resonator. AIP Conference Proceedings, 2020, , .	0.3	0
161	Relative Humidity Sensor based on Tapered Plastic Optical Fibre with Full-and Spiral-Patterned Agarose Gel Coating. , 2020, , .		0
162	Generation of passively Q-switched ytterbium laser by using tungsten trioxide film absorber. IET Optoelectronics, 2020, 14, 278-284.	1.8	11

#	ARTICLE	IF	CITATIONS
163	Generation of Q-switched and mode-locked pulses using neodymium oxide as saturable absorber. Results in Optics, 2020, 1, 100032.	0.9	5
164	A tunable optical frequency comb source using cascaded frequency modulator and Mach-Zehnder modulators. Journal of Optical Communications, 2020, .	4.0	3
165	Nanosecond mode-locked erbium doped fiber laser based on zinc oxide thin film saturable absorber. Indian Journal of Physics, 2019, 93, 93-99.	0.9	25
166	Dual-wavelength mode-locked erbium-doped fiber laser based on tin disulfide thin film as saturable absorber. Journal of Applied Physics, 2019, 125, .	1.1	23
167	Investigation of Surface Plasmon Resonance (SPR) in MoS <sub>2</sub> - and WS <sub>2</sub> -Protected Titanium Side-Polished Optical Fiber as a Humidity Sensor. Micromachines, 2019, 10, 465.	1.4	26
168	Effect of tapering diameters with microbottle resonator for formaldehyde (CH <sub>2</sub> O) liquid sensing. Sensing and Bio-Sensing Research, 2019, 25, 100292.	2.2	4
169	Passively Q-switched erbium-doped fiber laser utilizing lutetium oxide deposited onto D-shaped fiber as saturable absorber. Optik, 2019, 193, 162972.	1.4	6
170	Optimization of sensing performance factor ( $T_j \text{ ETQq0 0 0 rgBT /Overlock 10 Tf 50 472 Td}$ (xmlns:mml="http://www.w3.org/...)) microfiber-coupled ZnO nanorods humidity scheme. Optical Fiber Technology, 2019, 52, 101983.	1.4	7
171	Q-switched fiber laser operating at 1 $\mu$ m region with electron beam deposited titanium nanoparticles. Optics and Laser Technology, 2019, 120, 105702.	2.2	5
172	Miniature Compact Folded Dipole for Metal Mountable UHF RFID Tag Antenna. Electronics (Switzerland), 2019, 8, 713.	1.8	17
173	Nanosecond Pulse Generation with Silver Nanoparticle Saturable Absorber*. Chinese Physics Letters, 2019, 36, 054202.	1.3	14
174	Holmium oxide thin film as a saturable absorber for generating Q-switched and mode-locked erbium-doped fiber lasers. Optical Fiber Technology, 2019, 52, 101996.	1.4	27
175	Optical fiber coated Zinc Oxide (ZnO) nanorods decorated with Palladium (Pd) for hydrogen sensing. Optical Materials, 2019, 96, 109291.	1.7	8
176	Generation of sub-nanosecond pulse in dual-wavelength praseodymium fluoride fibre laser. Laser Physics, 2019, 29, 105101.	0.6	2
177	Nanosecond Pulses Generation with Samarium Oxide Film Saturable Absorber*. Chinese Physics Letters, 2019, 36, 074203.	1.3	7
178	Dissipative soliton generation in Er-doped fibre laser using SnS <sub>2</sub> as a saturable absorber. Applied Physics Express, 2019, 12, 102008.	1.1	17
179	Holmium based nanoseconds pulsed fibre laser generation in the 2-micron region. Optik, 2019, 195, 163157.	1.4	3
180	Wide-band flat-gain optical amplifier using Hafnia and zirconia erbium co-doped fibres in double-pass parallel configuration. Journal of Modern Optics, 2019, 66, 1711-1716.	0.6	6

#	ARTICLE	IF	CITATIONS
181	Microfiber loop resonator for formaldehyde liquid sensing. <i>Optik</i> , 2019, 196, 163174.	1.4	13
182	Formaldehyde sensing using ZnO nanorods coated glass integrated with microfiber. <i>Optics and Laser Technology</i> , 2019, 120, 105750.	2.2	16
183	Q-switched erbium-doped fiber laser using silver nanoparticles deposited onto side-polished D-shaped fiber by electron beam deposition method. <i>Optical Fiber Technology</i> , 2019, 53, 101997.	1.4	8
184	An efficient $L$ -band Zirconia Yttria Aluminum Erbium co-doped fiber amplifier with 1480nm pumping. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2019, 28, 1950018.	1.1	3
185	An efficient wideband hafnia-bismuth erbium co-doped fiber amplifier with flat-gain over 80nm wavelength span. <i>Optical Fiber Technology</i> , 2019, 48, 186-193.	1.4	18
186	Wideband optical fiber amplifier with short length of enhanced erbium-zirconia-yttria-aluminum co-doped fiber. <i>Optik</i> , 2019, 182, 194-200.	1.4	10
187	Detection of Formaldehyde Vapor Using Glass Substrate Coated With Zinc Oxide Nanorods. <i>IEEE Photonics Journal</i> , 2019, 11, 1-9.	1.0	19
188	Generation of bound state of solitons pulses with graphene in Erbium-doped fiber laser cavity. <i>Journal of Physics: Conference Series</i> , 2019, 1151, 012017.	0.3	4
189	Erbium Oxide as new Saturable Absorber for Short-Pulse Generation at 1.55-micron region. <i>Journal of Physics: Conference Series</i> , 2019, 1151, 012025.	0.3	2
190	Sodium nitrate (NaNO <sub>3</sub> ) sensor based on graphene coated microfiber. <i>Measurement: Journal of the International Measurement Confederation</i> , 2019, 146, 208-214.	2.5	14
191	Flat-gain and wide-band partial double-pass erbium co-doped fiber amplifier with hybrid gain medium. <i>Optical Fiber Technology</i> , 2019, 52, 101952.	1.4	11
192	Nickel Oxide as a Q-switcher for Short Pulsed Thulium Doped Fiber Laser Generation. <i>Journal of Physics: Conference Series</i> , 2019, 1151, 012029.	0.3	1
193	Mode-locked thulium doped fibre laser with copper thin film saturable absorber. <i>Journal of Modern Optics</i> , 2019, 66, 1381-1385.	0.6	16
194	Passively Q-switched erbium-doped fiber laser using quantum dots CdSe embedded in polymer film as saturable absorber. <i>Optical and Quantum Electronics</i> , 2019, 51, 1.	1.5	6
195	All fibre Q-switched Thulium-doped fibre laser incorporating Thulium-Holmium co-doped fibre as a saturable absorber. <i>Optics Communications</i> , 2019, 450, 160-165.	1.0	6
196	Q-switched and mode-locked thulium doped fiber lasers with nickel oxide film saturable absorber. <i>Optics Communications</i> , 2019, 447, 6-12.	1.0	35
197	Lutetium (III) oxide film as passive mode locker device for erbium-doped fibre laser cavity. <i>Optics Communications</i> , 2019, 446, 51-55.	1.0	24
198	NaNO <sub>3</sub> sensing based on microfiber coated with multi-walled carbon nanotubes. <i>Optik</i> , 2019, 185, 936-942.	1.4	2

#	ARTICLE	IF	CITATIONS
199	Flrpic thin film as saturable absorber for passively Q-switched and mode-locked erbium-doped fiber laser. Optical Fiber Technology, 2019, 50, 256-262.	1.4	49
200	Investigation of cladding thicknesses on silver SPR based side-polished optical fiber refractive-index sensor. Results in Physics, 2019, 13, 102255.	2.0	53
201	Bismuth (III) Telluride-Polyethylene Oxide as passive saturable absorber. Journal of Physics: Conference Series, 2019, 1151, 012002.	0.3	1
202	Microbottle resonator formaldehyde sensor. Journal of Physics: Conference Series, 2019, 1151, 012021.	0.3	2
203	Wideband and flat gain series erbium doped fiber amplifier using hybrid active fiber with backward pumping distribution technique. Results in Physics, 2019, 13, 102186.	2.0	14
204	Whispering gallery modes on optical micro-bottle resonator for humidity sensor application. Optik, 2019, 185, 558-565.	1.4	18
205	Multimode interference based fiber-optic sensor for temperature measurement. Journal of Physics: Conference Series, 2019, 1151, 012023.	0.3	14
206	Lutetium oxide film as a passive saturable absorber for generating Q-switched fiber laser at 1570nm wavelength. Optical Fiber Technology, 2019, 50, 82-86.	1.4	23
207	Pure gold saturable absorber for generating Q-switching pulses at 2µm in Thulium-doped fiber laser cavity. Optical Fiber Technology, 2019, 50, 23-30.	1.4	22
208	Ytterbium doped fiber saturable absorber for a stable passively Q-switched fiber laser in the 1-micron region. Journal of Physics: Conference Series, 2019, 1151, 012008.	0.3	3
209	Passively Q-switched Erbium doped fiber laser by incorporating a segment of Thulium doped fiber saturable absorber. Journal of Physics: Conference Series, 2019, 1151, 012010.	0.3	1
210	Nickel oxide nanoparticles for Q-switching pulses generation. Journal of Physics: Conference Series, 2019, 1151, 012027.	0.3	0
211	The effect of 980 nm and 1480 nm pumping on the performance of newly Hafnium Bismuth Erbium-doped fiber amplifier. Journal of Physics: Conference Series, 2019, 1151, 012013.	0.3	6
212	Polymer microfiber coated with ZnO for humidity sensing. Journal of Physics: Conference Series, 2019, 1151, 012019.	0.3	1
213	Passively Q-switched fiber laser utilizing new hafnium-bismuth-erbium co-doped fiber as saturable absorber. Indian Journal of Physics, 2019, 93, 1489-1493.	0.9	2
214	Self-generating Brillouin fiber laser using highly nonlinear hafnium bismuth erbium-doped fiber. Microwave and Optical Technology Letters, 2019, 61, 1651-1655.	0.9	6
215	Q-Switched Thulium-Doped Fiber Laser with Pure Titanium-Film-Based Saturable Absorber. Fiber and Integrated Optics, 2019, 38, 137-147.	1.7	2
216	Mode-locked Pulsed Fiber Laser with Graphene Solution as Saturable Absorber Deposited in Photonic Crystal Fiber. , 2019, , .		0

#	ARTICLE	IF	CITATIONS
217	Tris(8-hydroxyquinoline) aluminium thin film as saturable absorber for passively Q-switched erbium-doped fibre laser. IET Optoelectronics, 2019, 13, 247-253.	1.8	18
218	Microsecond pulse erbium-doped fiber laser using WS <sub>2</sub> deposited on D-shaped fiber fabricated by polishing wheel technique. Journal of Physics: Conference Series, 2019, 1371, 012001.	0.3	1
219	Q-switched ytterbium-doped fiber laser using graphene oxide as passive saturable absorber. Journal of Physics: Conference Series, 2019, 1371, 012004.	0.3	2
220	Optimization of ZnO nanorods growth duration for humidity sensing application. Journal of Physics: Conference Series, 2019, 1371, 012005.	0.3	1
221	Microbottle resonator for temperature sensing. Journal of Physics: Conference Series, 2019, 1371, 012006.	0.3	9
222	Q-Switched dual-wavelength erbium-doped fiber laser using graphene as a saturable absorber. Journal of Physics: Conference Series, 2019, 1371, 012007.	0.3	0
223	PMMA microball resonator for formaldehyde liquid sensing. Journal of Physics: Conference Series, 2019, 1371, 012012.	0.3	0
224	Q-switched Thulium-doped fiber laser with Bismuth-doped fiber saturable absorber. Journal of Physics: Conference Series, 2019, 1371, 012024.	0.3	0
225	A study on relative humidity sensors using PVA and PMMA coating. Journal of Physics: Conference Series, 2019, 1371, 012027.	0.3	5
226	Q-switched erbium-doped fiber lasers based on copper nanoparticles saturable absorber. Journal of Physics: Conference Series, 2019, 1371, 012028.	0.3	4
227	A study of relative humidity sensor on micro-ball resonator. Journal of Physics: Conference Series, 2019, 1371, 012009.	0.3	1
228	Q-switching Zirconia-Erbium-doped Pulsed Fiber Laser with MWCNTs-PEO as Saturable Absorber. Journal of Physics: Conference Series, 2019, 1372, 012003.	0.3	0
229	Q-switched Thulium-doped fibre laser using Bismuth (III) Telluride-based saturable absorber. Journal of Physics: Conference Series, 2019, 1371, 012008.	0.3	0
230	Titanium dioxide-based picoseconds pulsed fiber laser performances comparison in the 1.5-micron region. Journal of Physics: Conference Series, 2019, 1371, 012023.	0.3	6
231	Samarium (III) oxide thin film as a saturable absorber for the passively Q-switched Tm-doped fiber laser. Journal of Physics: Conference Series, 2019, 1371, 012026.	0.3	1
232	Passively Q-switched fibre laser utilizing erbium-doped fibre saturable absorber for operation in C-band region. Journal of Modern Optics, 2019, 66, 235-239.	0.6	5
233	PAPR reduction in all-optical OFDM based on time interleaving odd and even subcarriers. Optics Communications, 2019, 437, 237-245.	1.0	12
234	Passively Q-switched and mode-locked Erbium-doped fiber laser with topological insulator Bismuth Selenide (Bi <sub>2</sub> Se <sub>3</sub> ) as saturable absorber at C-band region. Optical Fiber Technology, 2019, 48, 117-122.	1.4	37

#	ARTICLE	IF	CITATIONS
235	Low-Cost Integrated Zinc Oxide Nanorod-Based Humidity Sensors for Arduino Platform. IEEE Sensors Journal, 2019, 19, 2442-2449.	2.4	12
236	Passively Q-switched fiber laser tunable by Sagnac interferometer operation. Optik, 2019, 179, 1-7.	1.4	4
237	Performance comparison of high temperature sensor based on non-adiabatic silica microfiber and single mode-multimode-single mode fiber structure. Microwave and Optical Technology Letters, 2019, 61, 431-435.	0.9	5
238	Optical characterization of different waist diameter on microfiber loop resonator humidity sensor. Sensors and Actuators A: Physical, 2019, 285, 200-209.	2.0	23
239	Investigation of the Brillouin effect in highly nonlinear hafnium bismuth erbium doped fiber. Microwave and Optical Technology Letters, 2019, 61, 173-177.	0.9	5
240	Q-switched Ytterbium doped fibre laser using gold nanoparticles saturable absorber fabricated by electron beam deposition. Optik, 2019, 182, 241-248.	1.4	15
241	Newly developed chromium-doped fiber as a saturable absorber at 1.55- and 2.0- $\mu\text{m}$ regions for Q-switching pulses generation. Optical Fiber Technology, 2019, 48, 144-150.	1.4	5
242	Theoretical Study on Passively Mode-Locked Fiber Lasers with Saturable Absorber. Fiber and Integrated Optics, 2019, 38, 76-89.	1.7	6
243	Multiwavelength Q-switched pulse operation with gold nanoparticles as saturable absorber. Optical Engineering, 2019, 58, 1.	0.5	3
244	Titanium dioxide fiber saturable absorber for Q-switched fiber laser generation in the 1-micrometer region. Applied Optics, 2019, 58, 3495.	0.9	10
245	Nanosecond pulse laser generation at 155 and 2- $\mu\text{m}$ regions by integrating a piece of newly developed chromium-doped fiber-based saturable absorber. Applied Optics, 2019, 58, 6528.	0.9	2
246	Q-switched ytterbium-doped fiber laser based on evanescent field interaction with lutetium oxide. Applied Optics, 2019, 58, 9670.	0.9	3
247	Passively Q-switched erbium-doped fiber laser utilizing tungsten oxide as a saturable absorber. Applied Optics, 2019, 58, 9768.	0.9	3
248	Nanosecond passively Q-switched fibre laser using a NiS <sub>2</sub> based saturable absorber. Optics Express, 2019, 27, 19843.	1.7	14
249	High-energy Q-switched ytterbium-doped all-fiber laser with tris-(8-hydroxyquinoline) aluminum as saturable absorber. Optical Materials Express, 2019, 9, 3215.	1.6	17
250	Nanosecond pulse generation with a gallium nitride saturable absorber. OSA Continuum, 2019, 2, 134.	1.8	7
251	Q-switched ytterbium-doped fiber laser by using Flrpc as a saturable absorber. OSA Continuum, 2019, 2, 2145.	1.8	4
252	Broadband optical frequency comb generator based on driving N-cascaded modulators by Gaussian-shaped waveform. Optical Fiber Technology, 2018, 42, 75-83.	1.4	8



#	ARTICLE	IF	CITATIONS
253	Polyaniline-Doped Poly (Methyl Methacrylate) Microfiber for Methanol Sensing. IEEE Sensors Journal, 2018, 18, 2801-2806.	2.4	15
254	Multi-Wavelength Q-Switched Ytterbium-Doped Fiber Laser with Multi-Walled Carbon Nanotubes. Fiber and Integrated Optics, 2018, 37, 92-102.	1.7	12
255	Experimental Observation of Bright and Dark Solitons Mode-Locked with Zirconia-Based Erbium-Doped Fiber Laser. Chinese Physics Letters, 2018, 35, 024203.	1.3	11
256	Mode-Locked Erbium-Doped Fiber Laser Using Vanadium Oxide as Saturable Absorber. Chinese Physics Letters, 2018, 35, 044204.	1.3	38
257	Molybdenum disulfide saturable absorber for eye-safe mode-locked fiber laser generation. Journal of Nonlinear Optical Physics and Materials, 2018, 27, 1850010.	1.1	15
258	Optical dynamic range maximization for humidity sensing by controlling growth of zinc oxide nanorods. Photonics and Nanostructures - Fundamentals and Applications, 2018, 30, 57-64.	1.0	13
259	Uric acid sensing using tapered silica optical fiber coated with zinc oxide nanorods. Microwave and Optical Technology Letters, 2018, 60, 645-650.	0.9	6
260	Q-switched and mode-locked thulium-doped fiber laser with pure Antimony film Saturable absorber. Optics Communications, 2018, 421, 99-104.	1.0	34
261	Titanium dioxide doped fiber as a new saturable absorber for generating mode-locked erbium doped fiber laser. Optik, 2018, 158, 1327-1333.	1.4	28
262	Multi-walled carbon nanotubes doped Poly(Methyl MethAcrylate) microfiber for relative humidity sensing. Sensors and Actuators A: Physical, 2018, 272, 274-280.	2.0	27
263	All-fibre Q-switching YDFL operation with bismuth-doped fibre as saturable absorber. Journal of Modern Optics, 2018, 65, 946-950.	0.6	1
264	Polyaniline (PANI) optical sensor in chloroform detection. Sensors and Actuators B: Chemical, 2018, 261, 97-105.	4.0	40
265	Applied microfiber evanescent wave on ZnO nanorods coated glass surface towards temperature sensing. Sensors and Actuators A: Physical, 2018, 277, 103-111.	2.0	28
266	Short-pulsed Q-switched Thulium doped fiber laser with graphene oxide as a saturable absorber. Optik, 2018, 168, 462-466.	1.4	12
267	Graphene coated silica microfiber for highly sensitive magnesium sensor. Sensors and Actuators A: Physical, 2018, 273, 67-71.	2.0	10
268	Passively Q-switched Erbium-Doped Fiber Laser based on Graphene Oxide as Saturable Absorber. Journal of Optical Communications, 2018, 39, 307-310.	4.0	6
269	Singlemode-multimode-singlemode fiber structure as compressive strain sensor on a reinforced concrete beam. Optik, 2018, 154, 705-710.	1.4	6
270	Pure antimony film as saturable absorber for Q-switched erbium-doped fiber laser. Journal of Modern Optics, 2018, 65, 811-817.	0.6	7



#	ARTICLE	IF	CITATIONS
271	Generation of an ultrafast femtosecond soliton fiber laser by carbon nanotube as saturable absorber. <i>Journal of Physics: Conference Series</i> , 2018, 1027, 012011.	0.3	0
272	EFFECT OF SIZE ON SINGLE AND DOUBLE OPTICAL MICROBOTTLE RESONATOR HUMIDITY SENSORS. <i>Sensors and Actuators A: Physical</i> , 2018, 284, 286-291.	2.0	22
273	Effect of Polymerization Temperatures on Polyaniline Coated Fiber Bragg Grating Sensor for Chloroform Detection. <i>Macromolecular Symposia</i> , 2018, 382, 1800088.	0.4	4
274	Nickel oxide film saturable absorber for mode-locking operation at 1.55-micron region. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2018, 27, 1850020.	1.1	12
275	A Microfiber Knot Incorporating a Tungsten Disulfide Saturable Absorber Based Multi-Wavelength Mode-Locked Erbium-Doped Fiber Laser. <i>Journal of Lightwave Technology</i> , 2018, 36, 5633-5639.	2.7	25
276	Q-Switched Erbium-Doped Fiber Laser Using Cadmium Selenide Coated onto Side-Polished D-Shape Fiber as Saturable Absorber. <i>Chinese Physics Letters</i> , 2018, 35, 104201.	1.3	10
277	Deposition of silver nanoparticles on polyvinyl alcohol film using electron beam evaporation and its application as a passive saturable absorber. <i>Results in Physics</i> , 2018, 11, 232-236.	2.0	18
278	A few-picosecond and high-peak-power passively mode-locked erbium-doped fibre laser based on zinc oxide polyvinyl alcohol film saturable absorber. <i>Laser Physics</i> , 2018, 28, 075105.	0.6	27
279	Compact and flat-gain fiber optical amplifier with Hafnia-Bismuth-Erbium co-doped fiber. <i>Optik</i> , 2018, 170, 56-60.	1.4	14
280	Nickel oxide nanoparticles thin film saturable absorber for 1-micron pulsed all-fibre lasers operation. <i>Journal of Modern Optics</i> , 2018, 65, 1801-1808.	0.6	13
281	Ultrashort Pulse Soliton Fiber Laser Generation With Integration of Antimony Film Saturable Absorber. <i>Journal of Lightwave Technology</i> , 2018, 36, 3522-3527.	2.7	26
282	Q-switched and mode-locked ytterbium-doped fibre lasers with Sb <sub>2</sub> Te <sub>3</sub> topological insulator saturable absorber. <i>IET Optoelectronics</i> , 2018, 12, 180-184.	1.8	13
283	Ultrashort pulse generation with an erbium-doped fiber laser ring cavity based on a copper oxide saturable absorber. <i>Applied Optics</i> , 2018, 57, 5180.	0.9	44
284	Q-switched ytterbium-doped fiber laser via a thulium-doped fiber saturable absorber. <i>Applied Optics</i> , 2018, 57, 6510.	0.9	20
285	A Flat-Gain Double-Pass Amplifier with New Hafnia-Bismuth-Erbium Codoped Fiber. <i>Chinese Physics Letters</i> , 2018, 35, 054206.	1.3	9
286	Multimode interference in single mode-multimode-single mode fiber structure for steel beam compressive strain measurement. <i>Microwave and Optical Technology Letters</i> , 2018, 60, 1971-1975.	0.9	5
287	Cobalt oxide nanocubes thin film as saturable absorber for generating Q-switched fiber lasers at 1 and 1.5 $\mu\text{m}$ in ring cavity configuration. <i>Optical Fiber Technology</i> , 2018, 45, 128-136.	1.4	20
288	Microbottle resonator for formaldehyde liquid sensing. <i>Optik</i> , 2018, 173, 180-184.	1.4	20

#	ARTICLE	IF	CITATIONS
289	MWCNTs coated silica microfiber sensor for detecting Mg <sup>2+</sup> in de-ionized water. <i>Optik</i> , 2018, 171, 65-70.	1.4	5
290	Copper oxide nanomaterial saturable absorber as a new passive Q-switcher in erbium-doped fiber laser ring cavity configuration. <i>Results in Physics</i> , 2018, 10, 264-269.	2.0	45
291	An 8â€m long holmium-doped fiber saturable absorber for Q-switched fiber laser generation at 2-Âµm region. <i>Optical Fiber Technology</i> , 2018, 43, 67-71.	1.4	21
292	Theoretical and experimental studies on a Q-switching operation in an erbium-doped fiber laser using vanadium oxide as saturable absorber. <i>Laser Physics</i> , 2018, 28, 085106.	0.6	12
293	Generation of Mode-Locked Ytterbium Doped Fiber Ring Laser Using Few-Layer Black Phosphorus as a Saturable Absorber. <i>IEEE Journal of Selected Topics in Quantum Electronics</i> , 2017, 23, 39-43.	1.9	105
294	Passively Q-switched erbium-doped fibre laser using cobalt oxide nanocubes as a saturable absorber. <i>Journal of Modern Optics</i> , 2017, 64, 1315-1320.	0.6	18
295	Passively Q-switched Ytterbium doped fiber laser with mechanically exfoliated MoS <sub>2</sub> saturable absorber. <i>Indian Journal of Physics</i> , 2017, 91, 575-580.	0.9	4
296	Mode-locking pulse generation in cladding pumped Erbium-Ytterbium co-doped fiber laser with graphene PVA film. <i>Optik</i> , 2017, 136, 531-535.	1.4	1
297	TEMPERATURE SENSING BY SIDE COUPLING OF LIGHT THROUGH ZINC OXIDE NANORODS ON OPTICAL FIBERS. <i>Sensors and Actuators A: Physical</i> , 2017, 257, 15-19.	2.0	8
298	Transition Metal Dichalcogenides (WS <sub>2</sub> and MoS <sub>2</sub> ) Saturable Absorbers for Mode-Locked Erbium-Doped Fiber Lasers. <i>Chinese Physics Letters</i> , 2017, 34, 014202.	1.3	24
299	Quantum dot cadmium selenide as a saturable absorber for Q-switched and mode-locked double-clad ytterbium-doped fiber lasers. <i>Optics Communications</i> , 2017, 397, 147-152.	1.0	18
300	Multiwavelength Brillouin fibre laser in two-mode fiber. <i>Journal of Modern Optics</i> , 2017, 64, 1744-1750.	0.6	3
301	Q-Switching Pulse Operation in 1.5-1.7µm Region Using Copper Nanoparticles as Saturable Absorber. <i>Chinese Physics Letters</i> , 2017, 34, 034205.	1.3	31
302	Q-switched ytterbium-doped fiber laser with topological insulator-based saturable absorber. <i>Optical Engineering</i> , 2017, 56, 056103.	0.5	19
303	Nickel oxide nanoparticles as a saturable absorber for an all-fiber passively Q-switched erbium-doped fiber laser. <i>Laser Physics</i> , 2017, 27, 065105.	0.6	53
304	PMMA microfiber loop resonator for humidity sensor. <i>Sensors and Actuators A: Physical</i> , 2017, 260, 112-116.	2.0	27
305	Zinc Oxide-Based Q-Switched Erbium-Doped Fiber Laser. <i>Chinese Physics Letters</i> , 2017, 34, 044202.	1.3	33
306	Relative Humidity Sensing Using a PMMA Doped Agarose Gel Microfiber. <i>Journal of Lightwave Technology</i> , 2017, 35, 3940-3944.	2.7	48

#	ARTICLE	IF	CITATIONS
307	Mechanically exfoliated 2D nanomaterials as saturable absorber for Q-switched erbium doped fiber laser. Indian Journal of Physics, 2017, 91, 1259-1264.	0.9	22
308	Stretched and soliton femtosecond pulse generation with graphene saturable absorber by manipulating cavity dispersion. Optik, 2017, 138, 250-255.	1.4	10
309	A PMMA microfiber loop resonator based humidity sensor with ZnO nanorods coating. Measurement: Journal of the International Measurement Confederation, 2017, 99, 128-133.	2.5	47
310	All-fiber dual-wavelength Q-switched and mode-locked EDFL by SMF-THDF-SMF structure as a saturable absorber. Optics Communications, 2017, 389, 29-34.	1.0	47
311	Performance comparison of enhanced Erbium-Zirconia-Yttria-Aluminum co-doped conventional erbium-doped fiber amplifiers. Optik, 2017, 132, 75-79.	1.4	16
312	Passively mode-locked ytterbium-doped fiber laser operation with few layer MoS <sub>2</sub> PVA saturable absorber. Optik, 2017, 145, 543-548.	1.4	8
313	Graphene Oxide saturable absorber for generating eye-safe Q-switched fiber laser. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012042.	0.3	0
314	Cadmium Selenide Polymer Microfiber Saturable Absorber for Q-Switched Fiber Laser Applications. Chinese Physics Letters, 2017, 34, 094202.	1.3	10
315	Demonstration of passive saturable absorber by utilizing MWCNT-ABS filament as starting material. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012030.	0.3	2
316	Optical Microfiber Sensing of Adulterated Honey. IEEE Sensors Journal, 2017, 17, 5510-5514.	2.4	14
317	Growth of well-arrayed ZnO nanorods on single-mode silica fiber and evaluation of its light scattering. Microwave and Optical Technology Letters, 2017, 59, 2196-2201.	0.9	3
318	Mode-locked ytterbium-doped fiber laser using mechanically exfoliated black phosphorus as saturable absorber. Optik, 2017, 147, 52-58.	1.4	21
319	Bi <sub>2</sub> Te <sub>3</sub> based passively Q-switched at 1042.76 and 1047.6 nm wavelength. Laser Physics, 2017, 27, 125102.	0.6	9
320	Gold nanoparticle based saturable absorber for Q-switching in 1.5 μm laser application. Laser Physics, 2017, 27, 115101.	0.6	10
321	Relative humidity sensor employing tapered plastic optical fiber coated with seeded Al-doped ZnO. Optik, 2017, 144, 257-262.	1.4	19
322	Water wave gauge based on singlemode-multimode-singlemode fiber structure. Optik, 2017, 144, 232-239.	1.4	4
323	S-band Q-switched fiber laser using MoSe <sub>2</sub> saturable absorber. Optics Communications, 2017, 382, 93-98.	1.0	51
324	A generation of 2 μm Q-switched thulium-doped fibre laser based on anatase titanium(IV) oxide film saturable absorber. Journal of Modern Optics, 2017, 64, 187-190.	0.6	26

#	ARTICLE	IF	CITATIONS
325	Titanium Dioxide (TiO <sub>2</sub> ) film as a new saturable absorber for generating mode-locked Thulium-Holmium doped all-fiber laser. Optics and Laser Technology, 2017, 89, 16-20.	2.2	72
326	Application of MoS <sub>2</sub> thin film in multi-wavelength and Q-switched EDFL. Journal of Modern Optics, 2017, 64, 457-461.	0.6	8
327	Passively Q-switched Erbium-doped and Ytterbium-doped fibre lasers with topological insulator bismuth selenide (Bi <sub>2</sub> Se <sub>3</sub> ) as saturable absorber. Optics and Laser Technology, 2017, 88, 121-127.	2.2	66
328	Black phosphorus saturable absorber for Q-switched technique pulse generation. , 2017, , .		2
329	Passively Q-switched of EDFL employing multi-walled carbon nanotubes with diameter less than 8 nm as saturable absorber. EPJ Web of Conferences, 2017, 162, 01014.	0.1	2
330	Relative humidity sensor based on MWCNTs-doped polymer microfiber. , 2017, , .		1
331	Printed silver nanoparticles on kapton tape as passive saturable absorber. , 2017, , .		2
332	Application of Fiber Bragg Grating Sensor coated with Polyaniline as an optical Sensor for chloroform detection. Polymers and Polymer Composites, 2017, 25, 555-562.	1.0	3
333	Ultrafast soliton mode-locked Zirconia-based Erbium-doped fiber laser with carbon nanotubes saturable absorber. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012051.	0.3	0
334	Continues-wave Brillouin-Raman fiber ring laser using 7.7 km long dispersion compensating fiber at 1563 nm wavelength. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012047.	0.3	0
335	Investigation of Brillouin Raman fiber laser operating at 1558 nm using THDF saturable absorber. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012048.	0.3	0
336	Potassium permanganate (KMnO <sub>4</sub> ) sensing based on microfiber sensors. Applied Optics, 2017, 56, 224.	2.1	13
337	Temperature sensing using CdSe quantum dot doped poly(methyl methacrylate) microfiber. Applied Optics, 2017, 56, 4675.	2.1	18
338	Bismuth (III) Telluride (Bi <sub>2</sub> Te <sub>3</sub> ) Based Topological Insulator Embedded in PVA as Passive Saturable Absorber in Erbium-Doped Fiber Laser. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012032.	0.3	3
339	Erbium-Doped Zirconia-Alumina Silica Glass-Based Fiber as a Saturable Absorber for High Repetition Rate Q-Switched All-Fiber Laser Generation. Chinese Physics Letters, 2017, 34, 084203.	1.3	1
340	The generation of Q-switched erbium-doped fiber laser using black phosphorus saturable absorber with 8% modulation depth. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012043.	0.3	3
341	Tunable wavelength generation in the 1 <math>\mu</math>m region incorporating a 16-channel arrayed waveguide grating (AWG). Laser Physics, 2017, 27, 125101.	0.6	6
342	Q-switched erbium doped fiber laser using antimony telluride-polyvinyl alcohol (Sb <sub>2</sub> Te <sub>3</sub> -PVA) as saturable absorber. EPJ Web of Conferences, 2017, 162, 01011.	0.1	0

#	ARTICLE	IF	CITATIONS
343	1563 nm Q-Switched Brillouin-Raman fiber laser using Graphene as a saturable absorber. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012055.	0.3	0
344	Q-switched double-clad Ytterbium-doped fiber laser using MoS <sub>2</sub> flakes saturable absorber. IOP Conference Series: Materials Science and Engineering, 2017, 210, 012054.	0.3	0
345	Holmium Oxide Film as a Saturable Absorber for 2 $\mu$ m Q-Switched Fiber Laser. Chinese Physics Letters, 2017, 34, 054201.	1.3	15
346	Optical Humidity Sensor Based on Tapered Fiber with Multi-walled Carbon Nanotubes Slurry. Indonesian Journal of Electrical Engineering and Computer Science, 2017, 6, 97.	0.7	12
347	Femtoseconds soliton mode-locked erbium-doped fiber laser based on nickel oxide nanoparticle saturable absorber. Chinese Optics Letters, 2017, 15, 100602.	1.3	18
348	Q-switched Erbium-doped Fiber Laser with a Black Phosphorus Saturable Absorber. Photonics Letters of Poland, 2017, 9, 72.	0.2	11
349	Q-switched fiber laser with tungsten disulfide saturable absorber prepared by drop casting method. Photonics Letters of Poland, 2017, 9, 103.	0.2	1
350	Graphene Oxide Film as Passive Q-switcher in Erbium-doped Fiber Laser Cavity. Photonics Letters of Poland, 2017, 9, 100.	0.2	3
351	Switchable Brillouin frequency multiwavelength and pulsed fiber laser. Chinese Optics Letters, 2017, 15, 101401.	1.3	0
352	Enhanced Relative Humidity Sensing Based on a Tapered Fiber Bragg Grating with Zinc Oxide Nanostructure-Embedded Coatings. Advanced Science Letters, 2017, 23, 5452-5456.	0.2	0
353	Detection of Honey Adulteration by Addition of Glucose via a Microfiber Coupler. Advanced Science Letters, 2017, 23, 5561-5564.	0.2	0
354	Q-Switched Raman Fiber Laser with Molybdenum Disulfide-Based Passive Saturable Absorber. Chinese Physics Letters, 2016, 33, 074208.	1.3	10
355	A WIDEBAND AND FLAT-GAIN OF AN AMPLIFIER BY USING ZIRCONIA-BASED ERBIUM-DOPED FIBER (ZR-EDF) FOR SINGLE PASS OPERATION. Jurnal Teknologi (Sciences and Engineering), 2016, 78, .	0.3	0
356	GRAPHENE OXIDE-POLYETHYLENE OXIDE (PEO) FILM AS SATURABLE ABSORBER ON MODE-LOCKED ERBIUM DOPED FIBER LASER GENERATION. Jurnal Teknologi (Sciences and Engineering), 2016, 78, .	0.3	0
357	Multi-wavelength Brillouin Erbium Fiber laser with Pulsing characteristics. , 2016, , .		0
358	Dual-wavelength nano-engineered Thulium-doped fiber laser via bending of singlemode-multimode-singlemode fiber structure. Optical Fiber Technology, 2016, 32, 96-101.	1.4	8
359	Molybdenum Disulphide Tape Saturable Absorber for Mode-Locked Double-Clad Ytterbium-Doped All-Fiber Laser Generation. Chinese Physics Letters, 2016, 33, 114201.	1.3	13
360	Optical based relative humidity sensor using tapered optical fiber coated with graphene oxide. , 2016, , .		3

#	ARTICLE	IF	CITATIONS
361	Q-Switched Ytterbium-Doped Fiber Laser Using Black Phosphorus as Saturable Absorber. Chinese Physics Letters, 2016, 33, 054206.	1.3	41
362	Mode-locking pulse generation with MoS <sub>2</sub> PVA saturable absorber in both anomalous and ultra-long normal dispersion regimes. Applied Optics, 2016, 55, 4247.	2.1	14
363	Tunable Q-switched fiber laser using zinc oxide nanoparticles as a saturable absorber. Applied Optics, 2016, 55, 4277.	2.1	50
364	Effectiveness of phase-conjugated twin waves on fiber nonlinearity in spatially multiplexed all-optical OFDM system. Optical Fiber Technology, 2016, 30, 147-152.	1.4	9
365	Domain-wall dark pulse generation in fiber laser incorporating MoS <sub>2</sub> . Applied Physics B: Lasers and Optics, 2016, 122, 1.	1.1	27
366	Generation of Q-Switched Mode-Locked Erbium-Doped Fiber Laser Operating in Dark Regime. Chinese Physics Letters, 2016, 33, 034201.	1.3	2
367	Q-switched 2 μm thulium bismuth co-doped fiber laser with multi-walled carbon nanotubes saturable absorber. Optics and Laser Technology, 2016, 83, 89-93.	2.2	4
368	Multi-wavelength mode-locked erbium-doped fiber laser with photonic crystal fiber in figure-of-eight cavity. Optik, 2016, 127, 5894-5898.	1.4	3
369	Fabrication and characterization of high order filter based on resonance in hybrid multi-knots microfiber structure. Optics and Laser Technology, 2016, 78, 120-124.	2.2	9
370	Light backscattering (e.g. reflectance) by ZnO nanorods on tips of plastic optical fibres with application for humidity and alcohol vapour sensing. Micro and Nano Letters, 2016, 11, 832-836.	0.6	10
371	Mode-locked generation in thulium-doped fiber linear cavity laser. Optik, 2016, 127, 11119-11123.	1.4	8
372	Generating 2 micron continuous-wave ytterbium-doped fiber laser-based optical parametric effect. Laser Physics Letters, 2016, 13, 105109.	0.6	0
373	Comparison of cladding shaped of Tm/Yb doped fiber laser for optimum lasing efficiency. , 2016, , .		1
374	Soliton mode-locked erbium-doped fibre laser with mechanically exfoliated molybdenum disulphide saturable absorber. IET Optoelectronics, 2016, 10, 169-173.	1.8	6
375	Silver nanoparticle-film based saturable absorber for passively Q-switched erbium-doped fiber laser (EDFL) in ring cavity configuration. Laser Physics, 2016, 26, 095103.	0.6	29
376	Applied light-side coupling with optimized spiral-patterned zinc oxide nanorod coatings for multiple optical channel alcohol vapor sensing. Journal of Nanophotonics, 2016, 10, 036009.	0.4	12
377	A black phosphorus-based tunable Q-switched ytterbium fiber laser. Laser Physics Letters, 2016, 13, 095103.	0.6	36
378	Ultrafast erbium-doped fiber laser mode-locked with a black phosphorus saturable absorber. Laser Physics Letters, 2016, 13, 095104.	0.6	49

#	ARTICLE	IF	CITATIONS
379	Switchable soliton mode-locked and multi-wavelength operation in thulium-doped all-fiber ring laser. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2016, 25, 1650034.	1.1	10
380	Dual-Wavelength Holmium-Doped Fiber Laser Pumped by Thulium-Ytterbium Co-Doped Fiber Laser. <i>Chinese Physics Letters</i> , 2016, 33, 054202.	1.3	2
381	Black phosphorus crystal as a saturable absorber for both a Q-switched and mode-locked erbium-doped fiber laser. <i>RSC Advances</i> , 2016, 6, 72692-72697.	1.7	83
382	Q-switched erbium-doped fiber laser operating at 1502nm with molybdenum disulfide saturable absorber. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2016, 25, 1650025.	1.1	12
383	Zinc oxide (ZnO) nanoparticles as saturable absorber in passively Q-switched fiber laser. <i>Optics Communications</i> , 2016, 381, 72-76.	1.0	85
384	Dye Concentrations Measurement Using Mach-Zehnder Interferometer Sensor and Modeled by ANFIS. <i>IEEE Sensors Journal</i> , 2016, 16, 8044-8050.	2.4	3
385	Black phosphorus as a saturable absorber for generating mode-locked fiber laser in normal dispersion regime. , 2016, , .		2
386	Q-switched ytterbium-doped fiber laser with zinc oxide based saturable absorber. <i>Laser Physics</i> , 2016, 26, 115107.	0.6	25
387	High-power Q-switched erbium-ytterbium codoped fiber laser using multiwalled carbon nanotubes saturable absorber. <i>Optical Engineering</i> , 2016, 55, 106112.	0.5	8
388	Refractive index sensor based on SPR in symmetrically etched plastic optical fibers. <i>Sensors and Actuators A: Physical</i> , 2016, 246, 163-169.	2.0	45
389	Tunable passively Q-switched thulium-doped fiber laser operating at 1.9 $\mu$ m using arrayed waveguide grating (AWG). <i>Optics Communications</i> , 2016, 380, 195-200.	1.0	11
390	Passively Q-switched flashlamp pumped Nd:YAG laser using liquid graphene oxide as saturable absorber. <i>Optics and Laser Technology</i> , 2016, 80, 28-32.	2.2	9
391	Generation of stable and narrow spacing dual-wavelength ytterbium-doped fiber laser using a photonic crystal fiber. <i>Journal of Modern Optics</i> , 2016, 63, 968-973.	0.6	3
392	Broadband tuning in a passively Q-switched erbium doped fiber laser (EDFL) via multiwall carbon nanotubes/polyvinyl alcohol (MWCNT/PVA) saturable absorber. <i>Optics Communications</i> , 2016, 365, 54-60.	1.0	10
393	Dye concentration determination with cross-sensitivity compensation. <i>Sensors and Actuators B: Chemical</i> , 2016, 226, 450-456.	4.0	3
394	Femtosecond mode-locked erbium-doped fiber laser based on MoS <sub>2</sub> -PVA saturable absorber. <i>Optics and Laser Technology</i> , 2016, 82, 145-149.	2.2	36
395	Steel Beam Compressive Strain Sensor Using Single-Mode-Multimode-Single-Mode Fiber Structure. <i>IEEE Photonics Journal</i> , 2016, 8, 1-6.	1.0	13
396	Demonstration of a Periodic Passband Filter Based on Coupled Microfiber Knots. <i>IEEE Photonics Technology Letters</i> , 2016, 28, 1061-1064.	1.3	8



#	ARTICLE	IF	CITATIONS
397	Side coupling of multiple optical channels by spiral patterned zinc oxide coatings on large core plastic optical fibers. <i>Micro and Nano Letters</i> , 2016, 11, 122-126.	0.6	14
398	Highly stable and tunable narrow-spacing dual-wavelength ytterbium-doped fiber using a microfiber Mach-Zehnder interferometer. <i>Optical Engineering</i> , 2016, 55, 026114.	0.5	7
399	Multi-walled carbon nanotubes saturable absorber in Q-switching flashlamp pumped Nd:YAG laser. <i>Optics and Laser Technology</i> , 2016, 79, 193-197.	2.2	7
400	Passively Q-switched erbium-doped fiber laser at C-band region based on WS <sub>2</sub> saturable absorber. <i>Applied Optics</i> , 2016, 55, 1001.	2.1	60
401	C-Band Q-Switched Fiber Laser Using Titanium Dioxide (TiO <sub>2</sub> ) As Saturable Absorber. <i>IEEE Photonics Journal</i> , 2016, 8, 1-7.	1.0	92
402	Tunable dual-wavelength ytterbium-doped fiber laser using a strain technique on microfiber Mach-Zehnder interferometer. <i>Applied Optics</i> , 2016, 55, 778.	2.1	17
403	Single-mode D-shaped optical fiber sensor for the refractive index monitoring of liquid. <i>Journal of Modern Optics</i> , 2016, 63, 750-755.	0.6	14
404	S-band Q-switched fiber laser using molybdenum disulfide (MoS <sub>2</sub> ) saturable absorber. <i>Laser Physics Letters</i> , 2016, 13, 035103.	0.6	33
405	A simple load sensor based on a bent single-mode-multimode-single-mode fiber structure. <i>Sensors and Actuators A: Physical</i> , 2016, 242, 106-110.	2.0	3
406	Realization of spectral tunable filter based on thermal effect in microfiber structure. <i>Optical Fiber Technology</i> , 2016, 28, 38-41.	1.4	1
407	Flat-gain wide-band erbium doped fiber amplifier with hybrid gain medium. <i>Optik</i> , 2016, 127, 2481-2484.	1.4	8
408	Generation of an ultra-stable dual-wavelength ytterbium-doped fiber laser using a photonic crystal fiber. <i>Laser Physics</i> , 2016, 26, 025101.	0.6	6
409	Optical Fiber Relative Humidity Sensor Based on Inline Mach-Zehnder Interferometer With ZnO Nanowires Coating. <i>IEEE Sensors Journal</i> , 2016, 16, 312-316.	2.4	54
410	Effects of the Dopant Ratio on Polyaniline Coated Fiber Bragg Grating for pH detection. <i>Synthetic Metals</i> , 2016, 211, 132-141.	2.1	11
411	Highly responsive NaCl detector based on inline microfiber Mach-Zehnder interferometer. <i>Sensors and Actuators A: Physical</i> , 2016, 237, 56-61.	2.0	38
412	Q-switched Erbium-doped fiber laser using MoSe <sub>2</sub> as saturable absorber. <i>Optics and Laser Technology</i> , 2016, 79, 20-23.	2.2	42
413	Generation of soliton and bound soliton pulses in mode-locked erbium-doped fiber laser using graphene film as saturable absorber. <i>Journal of Modern Optics</i> , 2016, 63, 777-782.	0.6	29
414	Q-switched thulium-doped fiber laser operating at 1940 nm region using a pencil-core as saturable absorber. <i>Journal of Modern Optics</i> , 2016, 63, 783-787.	0.6	4



#	ARTICLE	IF	CITATIONS
415	Highly Efficient Cladding Pumped Dual-Wavelength Thulium Ytterbium Co-Doped Fiber Laser. Acta Physica Polonica A, 2016, 130, 1332-1335.	0.2	1
416	Development of CW and Pulsed Thulium Ytterbium Co-doped Fiber Lasers Using Nano-engineered Yttria-alumina-silica Based Gain Medium in Conjunction with Cladding Pumping Technique. Current Nanoscience, 2016, 12, 299-308.	0.7	2
417	Dual-wavelength passively Q-switched Erbium-doped fiber laser with MWCNTs slurry as saturable absorber. Photonics Letters of Poland, 2016, 8, 98.	0.2	5
418	Bismuth (III) Telluride (Bi <sub>2</sub> Te <sub>3</sub> ) topological insulator embed in PVA as passive Q-switcher at 2 micron region. Photonics Letters of Poland, 2016, 8, 101.	0.2	4
419	Mode-locked Thulium Ytterbium co-Doped Fiber Laser with Graphene Saturable Absorber. Photonics Letters of Poland, 2016, 8, 104.	0.2	3
420	SOLITON MODE-LOCKED GENERATION BASED ON ERBIUM-DOPED FIBER LASER EMBEDDED WITH SINGLE-WALLED CARBON NANOTUBES AS SATURABLE ABSORBER. Jurnal Teknologi (Sciences and Engineering), 2016, 78, .	0.3	0
421	GENERATION OF Q-SWITCHED THULIUM-DOPED FIBER LASER (TDFL) USING DIFFERENT SATURABLE ABSORBERS. Jurnal Teknologi (Sciences and Engineering), 2016, 78, .	0.3	0
422	Peak-to-average power ratio reduction in all-optical orthogonal frequency division multiplexing system using rotated constellation approach. Optical Fiber Technology, 2015, 25, 88-93.	1.4	9
423	Q-switching and mode-locking pulse generation with graphene oxide paper-based saturable absorber. Journal of Engineering, 2015, 2015, 208-214.	0.6	4
424	Investigation of thermal effects in a resonance condition of microfiber double-knot resonators as high-order filter. Micro and Nano Letters, 2015, 10, 580-582.	0.6	1
425	PMMA microfiber coated with ZnO nanostructure for the measurement of relative humidity. IOP Conference Series: Materials Science and Engineering, 2015, 99, 012025.	0.3	6
426	A Stable Dual-wavelength Thulium-doped Fiber Laser at 1.9 $\mu$ m Using Photonic Crystal Fiber. Scientific Reports, 2015, 5, 14537.	1.6	73
427	Four wave mixing techniques in measuring HNLF. AIP Conference Proceedings, 2015, , .	0.3	1
428	Fabrication of polymer microfiber by direct drawing. Microwave and Optical Technology Letters, 2015, 57, 820-823.	0.9	15
429	PMMA microfiber coated with Al-doped ZnO nanostructures for detecting uric acid. Microwave and Optical Technology Letters, 2015, 57, 2455-2457.	0.9	12
430	Observation violet emission of microfiber knot resonator. Microwave and Optical Technology Letters, 2015, 57, 2929-2931.	0.9	1
431	DETECTION OF DIFFERENT CONCENTRATIONS OF URIC ACID USING TAPERED SILICA OPTICAL SENSOR COATED WITH ZINC OXIDE (ZNO). Jurnal Teknologi (Sciences and Engineering), 2015, 74, .	0.3	4
432	Effect of the doped fibre length on soliton pulses of a bidirectional mode-locked fibre laser. Quantum Electronics, 2015, 45, 713-716.	0.3	2

#	ARTICLE	IF	CITATIONS
433	Q-SWITCHED THULIUM-DOPED FIBER LASER AT 2 MICRON REGION BY 802 NM PUMPING. Jurnal Teknologi (Sciences and Engineering), 2015, 74, .	0.3	0
434	Relative Humidity Sensor Employing Optical Fibers Coated with ZnO Nanostructures. Indian Journal of Science and Technology, 2015, 8, .	0.5	18
435	Development of Nano-engineered Thulium-doped Fiber Laser With Low Threshold Pump Power and Tunable Operating Wavelength. IEEE Photonics Journal, 2015, , 1-1.	1.0	2
436	Switchable dual-wavelength CNT-based Q-switched using arrayed waveguide gratings (AWG). Applied Physics B: Lasers and Optics, 2015, 118, 269-274.	1.1	6
437	Generation of switchable domain wall and Cubic-Quintic nonlinear Schrödinger equation dark pulse. Optics and Laser Technology, 2015, 73, 127-129.	2.2	18
438	Passively dual-wavelength Q-switched ytterbium doped fiber laser using Selenium Bismuth as saturable absorber. Journal of Modern Optics, 2015, 62, 1550-1554.	0.6	16
439	Q-switched thulium-ytterbium co-doped fibre laser using newly developed octagonal shaped inner cladding double-clad active fibre and multi-walled carbon nanotubes passive saturable absorber. IET Optoelectronics, 2015, 9, 131-135.	1.8	4
440	Dual Output Approach in Dye Concentrations Determination Using Non-Adiabatic Tapered Fiber. IEEE Sensors Journal, 2015, 15, 3903-3908.	2.4	4
441	Fiber Bragg grating sensor for humidity measurement. , 2015, , .		1
442	Generation of Cubic-Quintic nonlinear schrödinger equation dark pulse. , 2015, , .		0
443	Investigation of nitrogen doped graphene as saturable absorber in Thulium-Doped Fiber Laser. , 2015, , .		1
444	Fabrication and Characterization of a Refractive Index Sensor Based on SPR in an Etched Plastic Optical Fiber. Procedia Engineering, 2015, 120, 969-974.	1.2	9
445	Enhanced Erbium-Zirconia-Yttria-Aluminum Co-Doped Fiber Amplifier. IEEE Photonics Journal, 2015, 7, 1-7.	1.0	19
446	Low-Cost Transducer Based On Surface Scattering Using Side-Polished D-Shaped Optical Fibers. IEEE Photonics Journal, 2015, 7, 1-10.	1.0	11
447	Tunable S-Band Q-Switched Fiber Laser Using Bi <sub>2</sub> Se <sub>3</sub> as the Saturable Absorber. IEEE Photonics Journal, 2015, 7, 1-8.	1.0	28
448	Optical frequency comb generation based on chirping of Mach-Zehnder Modulators. Optics Communications, 2015, 344, 139-146.	1.0	30
449	Biosensing enhancement of dengue virus using microballoon mixers on centrifugal microfluidic platforms. Biosensors and Bioelectronics, 2015, 67, 424-430.	5.3	38
450	A Switchable Figure Eight Erbium-Doped Fiber Laser Based on Inter-Modal Beating By Means of Non-Adiabatic Microfiber. Journal of Lightwave Technology, 2015, 33, 528-534.	2.7	29

#	ARTICLE	IF	CITATIONS
451	Dual-wavelength passively Q-switched Erbium Ytterbium codoped fiber laser based on a nonlinear polarization rotation technique. <i>Microwave and Optical Technology Letters</i> , 2015, 57, 530-533.	0.9	7
452	Application of Fano resonance effects in optical antennas formed by regular clusters of nanospheres. <i>Applied Physics A: Materials Science and Processing</i> , 2015, 118, 139-150.	1.1	6
453	Mode-Locked Thulium Ytterbium Co-Doped Fiber Laser with Graphene Oxide Paper Saturable Absorber. <i>Chinese Physics Letters</i> , 2015, 32, 014204.	1.3	8
454	Tapered fiber coated with hydroxyethyl cellulose/polyvinylidene fluoride composite for relative humidity sensor. <i>Sensors and Actuators A: Physical</i> , 2015, 225, 128-132.	2.0	11
455	Tunable dual-wavelength thulium-doped fiber laser at 1.8 $\mu$ m region using spatial-mode beating. <i>Journal of Modern Optics</i> , 2015, 62, 892-896.	0.6	20
456	A passively harmonically mode-locked soliton erbium-doped fiber laser with low pumping threshold using a single-walled carbon nanotubes. <i>Microwave and Optical Technology Letters</i> , 2015, 57, 799-803.	0.9	3
457	Modeling the Concentric Fiber Optic Bundle Displacement Sensor Using a Quasi-Gaussian Beam Approach. <i>IEEE Sensors Journal</i> , 2015, 15, 4777-4781.	2.4	3
458	Application of multiple linear regression, central composite design, and ANFIS models in dye concentration measurement and prediction using plastic optical fiber sensor. <i>Measurement: Journal of the International Measurement Confederation</i> , 2015, 74, 78-86.	2.5	43
459	Mitigation of phase noise in all-optical OFDM systems based on minimizing interaction time between subcarriers. <i>Optics Communications</i> , 2015, 355, 313-320.	1.0	11
460	Reversible thermo-pneumatic valves on centrifugal microfluidic platforms. <i>Lab on A Chip</i> , 2015, 15, 3358-3369.	3.1	32
461	Performance of passively Q-switched ring erbium-doped fiber laser using a multiwalled carbon nanotubes polyethylene oxide (PEO) polymer composite-based saturable absorber. <i>Microwave and Optical Technology Letters</i> , 2015, 57, 1897-1901.	0.9	4
462	Multi-lobed double-clad Erbium-Ytterbium co-doped Q-switched fiber laser based on nonlinear polarisation rotation technique. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2015, 24, 1550002.	1.1	8
463	Q-switched Brillouin fibre laser with multi-wall carbon nanotube saturable absorber. <i>IET Optoelectronics</i> , 2015, 9, 96-100.	1.8	4
464	Performance enhancement of pre-spectrum slicing technique for wavelength conversion. <i>Optics Communications</i> , 2015, 350, 154-159.	1.0	3
465	Fundamental and harmonic soliton mode-locked erbium-doped fiber laser using a single-walled carbon nanotubes embedded in poly (ethylene oxide) film saturable absorber. <i>Proceedings of SPIE</i> , 2015, , .	0.8	0
466	Passively mode-locked laser using an entirely centred erbium-doped fiber. <i>Laser Physics</i> , 2015, 25, 045105.	0.6	2
467	A passively Q-switched ytterbium-doped fiber laser based on a few-layer Bi <sub>2</sub> Se <sub>3</sub> saturable absorber. <i>Laser Physics</i> , 2015, 25, 065102.	0.6	15
468	Multi-wavelength Q-switched Erbium-doped fiber laser with photonic crystal fiber and graphene Polyethylene oxide saturable absorber. <i>Optik</i> , 2015, 126, 1495-1498.	1.4	10

#	ARTICLE	IF	CITATIONS
469	Performance analysis of an all-optical OFDM system in presence of non-linear phase noise. Optics Express, 2015, 23, 3886.	1.7	22
470	Passively Q-switched fiber lasers using a multi-walled carbon nanotube polymer composite based saturable absorber. Optik, 2015, 126, 2950-2954.	1.4	8
471	Experimental realization and performance evaluation of refractive index SPR sensor based on unmasked short tapered multimode-fiber operating in aqueous environments. Sensors and Actuators A: Physical, 2015, 236, 38-43.	2.0	39
472	Fabrication of polymer microfiber through direct drawing and splicing of silica microfiber via vapor spray and flame treatment. Applied Optics, 2015, 54, 3863.	2.1	8
473	Inline Mach-Zehnder interferometer with ZnO nanowires coating for the measurement of uric acid concentrations. Sensors and Actuators A: Physical, 2015, 234, 206-211.	2.0	9
474	Q-Switched Yb-Doped Fiber Ring Laser with a Saturable Absorber Based on a Graphene Polyvinyl Alcohol Film. Journal of Russian Laser Research, 2015, 36, 389-394.	0.3	7
475	Influence of design parameters on the performance of a refractive index sensor based on SPR in plastic optical fibers. , 2015, , .		1
476	Enhancement of Thulium-Ytterbium doped fiber laser efficiency using dual-pumping method. Microwave and Optical Technology Letters, 2015, 57, 285-287.	0.9	1
477	Tapered Plastic Optical Fiber Coated With Al-Doped ZnO Nanostructures for Detecting Relative Humidity. IEEE Sensors Journal, 2015, 15, 845-849.	2.4	38
478	Effective use of an EDFA and Raman pump residual powers via a Bi-EDF in L-band multi-wavelength fiber laser generation. Laser Physics, 2015, 25, 015104.	0.6	3
479	Single mode EDF fiber laser using an ultra-narrow bandwidth tunable optical filter. Optik, 2015, 126, 179-183.	1.4	12
480	A Study of Relative Humidity Fiber-Optic Sensors. IEEE Sensors Journal, 2015, 15, 1945-1950.	2.4	58
481	Dynamic characteristics of a multi-wavelength Brillouin-Raman fiber laser assisted by multiple four-wave mixing processes in a ring cavity. Optics and Laser Technology, 2015, 66, 63-67.	2.2	3
482	Q-switched erbium doped fiber laser based on single and multiple walled carbon nanotubes embedded in polyethylene oxide film as saturable absorber. Optics and Laser Technology, 2015, 65, 25-28.	2.2	42
483	Dumbbell shaped inline Mach-Zehnder interferometer for glucose detection. Measurement: Journal of the International Measurement Confederation, 2015, 59, 167-170.	2.5	21
484	Sideband-controllable soliton pulse with bismuth-based erbium-doped fiber. Chinese Optics Letters, 2015, 13, 111406-111408.	1.3	10
485	AMPLIFICATION AND LASING CHARACTERISTICS OF THULIUM YTTERBIUM CO-DOPED FIBER. Jurnal Teknologi (Sciences and Engineering), 2015, 74, .	0.3	0
486	Q-switched multi-wavelength Brillouin erbium fiber laser. Journal of Nonlinear Optical Physics and Materials, 2014, 23, 1450010.	1.1	4

#	ARTICLE	IF	CITATIONS
487	Evaluation of the tapered PMMA fiber sensor response due to the ionic interaction within electrolytic solutions. Journal of Modern Optics, 2014, 61, 154-160.	0.6	6
488	Nonadiabatic microfiber based mode-locked erbium-doped fiber laser using graphene. Microwave and Optical Technology Letters, 2014, 56, 1670-1673.	0.9	1
489	Nonlinear Polarization Rotation-Based Mode-Locked Erbium-Doped Fiber Laser with Three Switchable Operation States. Chinese Physics Letters, 2014, 31, 094206.	1.3	17
490	S-band SLM distributed Bragg reflector fiber laser. Laser Physics, 2014, 24, 065109.	0.6	2
491	Optical fiber humidity sensor based on a tapered fiber with hydroxyethylcellulose/polyvinylidene fluoride composite. Microwave and Optical Technology Letters, 2014, 56, 380-382.	0.9	25
492	Study of a fiber optic humidity sensor based on agarose gel. Journal of Modern Optics, 2014, 61, 244-248.	0.6	26
493	Temperature Compensation in Determining of Remazol Black B Concentrations Using Plastic Optical Fiber Based Sensor. Sensors, 2014, 14, 15836-15848.	2.1	9
494	Q-switched thulium-doped fibre laser operating at 1900 nm using multi-layered graphene based saturable absorber. IET Optoelectronics, 2014, 8, 155-160.	1.8	6
495	Q-switched Yb-doped fiber laser operating at 1073 nm using a carbon nanotubes saturable absorber. Microwave and Optical Technology Letters, 2014, 56, 1770-1773.	0.9	20
496	Q-Switching and Mode-Locking in Highly Doped Zr <sub>2</sub> O <sub>3</sub> :Al <sub>2</sub> O <sub>3</sub> :Er <sub>2</sub> O <sub>3</sub> -Doped Fiber Lasers Using Graphene as a Saturable Absorber. IEEE Journal of Selected Topics in Quantum Electronics, 2014, 20, 9-16.	1.9	5
497	1.9&#x00E2; &#x03BC;m gain shifted TBDFAs employing different Tm-Bi concentration ratio. , 2014, , .		0
498	Tunable single Stokes extraction from 20 GHz Brillouin fiber laser using ultranarrow bandwidth optical filter. Applied Optics, 2014, 53, 6944.	0.9	4
499	Excitation of core modes through side coupling to multimode optical fiber by hydrothermal growth of ZnO nanorods for wide angle optical reception. Journal of the Optical Society of America B: Optical Physics, 2014, 31, 2232.	0.9	9
500	Gain-shift induced by dopant concentration ratio in a thulium-bismuth doped fiber amplifier. Optics Express, 2014, 22, 7075.	1.7	6
501	All-fiber dual wavelength passive Q-switched fiber laser using a dispersion-decreasing taper fiber in a nonlinear loop mirror. Optics Express, 2014, 22, 22794.	1.7	5
502	Mode-locked thulium bismuth codoped fiber laser using graphene saturable absorber in ring cavity: reply. Applied Optics, 2014, 53, 555.	0.9	1
503	Q-Switching Pulse Generation with Thulium-Doped Fiber Saturable Absorber. Chinese Physics Letters, 2014, 31, 124203.	1.3	15
504	Investigation of Bending Sensitivity in Partially Doped Core Fiber for Sensing Applications. IEEE Sensors Journal, 2014, 14, 1295-1303.	2.4	7

#	ARTICLE	IF	CITATIONS
505	Performance evaluation of a bilayer SPR-based fiber optic RI sensor with TiO <sub>2</sub> using FDTD solutions. <i>Photonic Sensors</i> , 2014, 4, 289-294.	2.5	10
506	Tapered Plastic Optical Fiber Coated With Graphene for Uric Acid Detection. <i>IEEE Sensors Journal</i> , 2014, 14, 1704-1709.	2.4	36
507	Mode-locked soliton erbium-doped fiber laser using a single-walled carbon nanotubes embedded in polyethylene oxide thin film saturable absorber. <i>Journal of Modern Optics</i> , 2014, 61, 541-545.	0.6	8
508	Evanescent wave optical trapping and transport of polystyrene microspheres on microfibers. <i>Microwave and Optical Technology Letters</i> , 2014, 56, 2630-2634.	0.9	9
509	Q-switched erbium doped fiber laser using single-walled carbon nanotubes embedded in polyethylene oxide film saturable absorber. <i>Microwave and Optical Technology Letters</i> , 2014, 56, 2734-2737.	0.9	6
510	Classification of reflected signals from cavitated tooth surfaces using an artificial intelligence technique incorporating a fiber optic displacement sensor. <i>Journal of Biomedical Optics</i> , 2014, 19, 057009.	1.4	3
511	Passively Q-Switched EDFL Using a Multi-Walled Carbon Nanotube Polymer Composite Based on a Saturable Absorber. <i>Chinese Physics Letters</i> , 2014, 31, 034204.	1.3	13
512	Investigation of spontaneous Brillouin scattering generation based on non-adiabatic microfibres. <i>Laser Physics Letters</i> , 2014, 11, 125105.	0.6	3
513	Brillouin Lasing with a Reduced Self-Pulsing Characteristic Using a Short-Length Erbium-Doped Fiber as the Nonlinear Gain Medium. <i>Chinese Physics Letters</i> , 2014, 31, 054202.	1.3	0
514	A Mode-Locked Soliton Erbium-Doped Fiber Laser with a Single-Walled Carbon Nanotube Poly-Ethylene Oxide Film Saturable Absorber. <i>Chinese Physics Letters</i> , 2014, 31, 094202.	1.3	2
515	Square pulse emission with ultra-low repetition rate utilising non-linear polarisation rotation technique. <i>Journal of Engineering</i> , 2014, 2014, 517-521.	0.6	1
516	Tapered plastic optical fiber coated with single wall carbon nanotubes polyethylene oxide composite for measurement of uric acid concentration. <i>Sensor Review</i> , 2014, 34, 75-79.	1.0	9
517	Multiwall carbon nanotube polyvinyl alcohol-based saturable absorber in passively Q-switched fiber laser. <i>Applied Optics</i> , 2014, 53, 7025.	0.9	16
518	Q-switched fibre laser using 21cm Bismuth-erbium doped fibre and graphene oxide as saturable absorber. <i>Optics Communications</i> , 2014, 310, 53-57.	1.0	7
519	Mode-locked L-band bismuth-erbium fiber laser using carbon nanotubes. <i>Applied Physics B: Lasers and Optics</i> , 2014, 115, 407-412.	1.1	22
520	Passive Q-switched Erbium-doped fiber laser with graphene-polyethylene oxide saturable absorber in three different gain media. <i>Indian Journal of Physics</i> , 2014, 88, 727-731.	0.9	12
521	Tapered plastic optical fiber coated with ZnO nanostructures for the measurement of uric acid concentrations and changes in relative humidity. <i>Sensors and Actuators A: Physical</i> , 2014, 210, 190-196.	2.0	54
522	Conducting polymer coated optical microfiber sensor for alcohol detection. <i>Sensors and Actuators A: Physical</i> , 2014, 205, 58-62.	2.0	45



#	ARTICLE	IF	CITATIONS
523	A review of recent developed and applications of plastic fiber optic displacement sensors. Measurement: Journal of the International Measurement Confederation, 2014, 48, 333-345.	2.5	74
524	Optical Fiber Sensing of Salinity and Liquid Level. IEEE Photonics Technology Letters, 2014, 26, 1742-1745.	1.3	34
525	Soliton Mode-Locked Erbium-Doped Fiber Laser Using Non-Conductive Graphene Oxide Paper. IEEE Journal of Quantum Electronics, 2014, 50, 85-87.	1.0	9
526	Tunable microwave output over a wide RF region generated by an optical dual-wavelength fiber laser. Laser Physics, 2014, 24, 105116.	0.6	9
527	Enhanced performance of an S-band fiber laser using a thulium-doped photonic crystal fiber. Laser Physics, 2014, 24, 115201.	0.6	1
528	Multi-wavelength fiber laser generation by using optical wavelength conversion. Laser Physics, 2014, 24, 065105.	0.6	5
529	Latex micro-balloon pumping in centrifugal microfluidic platforms. Lab on A Chip, 2014, 14, 988.	3.1	58
530	Q-switched thulium-doped fiber laser operating at 1920 nm region with multiwalled carbon nanotubes embedded in polyvinyl alcohol. Microwave and Optical Technology Letters, 2014, 56, 2817-2819.	0.9	8
531	Stable narrow spacing dual-wavelength Q-switched graphene oxide embedded in a photonic crystal fiber. Laser Physics, 2014, 24, 105101.	0.6	11
532	Thulium Bismuth Co-Doped Fiber Lasers at 1901 nm by 802 nm Pumping. IEEE Journal of Selected Topics in Quantum Electronics, 2014, 20, 132-137.	1.9	1
533	Q-switched erbium-doped fiber laser using multi-layer graphene based saturable absorber. Journal of Nonlinear Optical Physics and Materials, 2014, 23, 1450009.	1.1	7
534	Photonic crystal fiber based dual-wavelength Q-switched fiber laser using graphene oxide as a saturable absorber. Applied Optics, 2014, 53, 3581.	0.9	29
535	Single-longitudinal-mode operation in tunable novel zirconia-yttria-alumina-erbium-doped fiber laser. Laser Physics, 2014, 24, 085106.	0.6	3
536	Closely spaced dual-wavelength fiber laser using an ultranarrow bandwidth optical filter for low radio frequency generation. Applied Optics, 2014, 53, 4123.	0.9	0
537	Refractive index and strain sensing using inline Mach-Zehnder interferometer comprising perfluorinated graded-index plastic optical fiber. Sensors and Actuators A: Physical, 2014, 219, 94-99.	2.0	41
538	Multi-wavelength Q-switched Erbium-doped fiber laser with photonic crystal fiber and multi-walled carbon nanotubes. Journal of Modern Optics, 2014, 61, 1133-1139.	0.6	16
539	Circuit Model of Fano Resonance on Tetramers, Pentamers, and Broken Symmetry Pentamers. Plasmonics, 2014, 9, 1303-1313.	1.8	19
540	Supercontinuum generation from a sub-megahertz repetition rate femtosecond pulses based on nonlinear polarization rotation technique. Journal of Modern Optics, 2014, 61, 1333-1338.	0.6	1

#	ARTICLE	IF	CITATIONS
541	A tuneable, power efficient and narrow single longitudinal mode fibre ring laser using an inline dual-taper fibre Mach-Zehnder filter. <i>Laser Physics</i> , 2014, 24, 085111.	0.6	11
542	Multi-wavelength Brillouin Raman erbium-doped fiber laser generation in a linear cavity. <i>Journal of Optics (United Kingdom)</i> , 2014, 16, 035203.	1.0	17
543	All fiber mode-locked Erbium-doped fiber laser using single-walled carbon nanotubes embedded into polyvinyl alcohol film as saturable absorber. <i>Optics and Laser Technology</i> , 2014, 62, 40-43.	2.2	29
544	Controlled side coupling of light to cladding mode of ZnO nanorod coated optical fibers and its implications for chemical vapor sensing. <i>Sensors and Actuators B: Chemical</i> , 2014, 202, 543-550.	4.0	31
545	Introduction to the Issue on Fiber Lasers. <i>IEEE Journal of Selected Topics in Quantum Electronics</i> , 2014, 20, 5-7.	1.9	10
546	Electrostatic charge interaction: a case study on tapered PMMA fiber for calcium nitrate detection. <i>Sensor Review</i> , 2014, 34, 424-427.	1.0	1
547	Q-switched thulium-doped fibre laser operating at 1900 nm using multi-walled carbon nanotubes saturable absorber. <i>Journal of Engineering</i> , 2014, 2014, 297-301.	0.6	3
548	Dark pulse emission in nonlinear polarization rotation-based multiwavelength mode-locked erbium-doped fiber laser. <i>Chinese Optics Letters</i> , 2014, 12, 113202-113204.	1.3	18
549	Q-Switched Ultrafast TDFL Using MWCNTs-SA at 2 μm Region. <i>International Journal of Computer and Communication Engineering</i> , 2014, 3, 446-449.	0.2	7
550	Q-Switched Erbium-Doped Fiber Laser Based on Nonlinear Polarisation Rotation Technique. <i>Journal of Nanoelectronics and Optoelectronics</i> , 2014, 9, 525-528.	0.1	0
551	Distributed feedback multimode Brillouin-Raman random fiber laser in the S-band. <i>Laser Physics Letters</i> , 2013, 10, 055102.	0.6	33
552	A Multi-Wavelength Brillouin Erbium Fiber Laser With Double Brillouin Frequency Spacing and Q-Switching Characteristics. <i>IEEE Journal of Quantum Electronics</i> , 2013, 49, 595-598.	1.0	9
553	Generation of efficient 20 GHz optical combs in a Brillouin-erbium fiber laser. <i>Laser Physics</i> , 2013, 23, 015103.	0.6	2
554	Extraction of a single Stokes line from a Brillouin fibre laser using a silicon oxynitride microring filter. <i>Laser Physics</i> , 2013, 23, 095102.	0.6	3
555	Visible and near infrared up-conversion luminescence in Yb <sup>3+</sup> /Tm <sup>3+</sup> co-doped yttria-alumino-silicate glass based optical fibers. <i>Journal of Luminescence</i> , 2013, 143, 393-401.	1.5	23
556	All-Fiber Dual-Wavelength Thulium-Bismuth Codoped Fiber Laser. <i>Microwave and Optical Technology Letters</i> , 2013, 55, 2324-2326.	0.9	3
557	AQ-switched thulium-doped fiber laser with a graphene thin film based saturable absorber. <i>Laser Physics</i> , 2013, 23, 115102.	0.6	6
558	Ultra-narrow linewidth single longitudinal mode Brillouin fiber ring laser using highly nonlinear fiber. <i>Laser Physics Letters</i> , 2013, 10, 105105.	0.6	21



#	ARTICLE	IF	CITATIONS
559	All-fiber graphene passively Q-switched nanosecond Thulium doped fiber laser at 1900 nm. , 2013, , .		0
560	Q-switched and soliton pulses generation based on carbon nanotubes saturable absorber. , 2013, , .		3
561	Closely Spaced, Dual-Wavelength Fiber Laser for Microwave Generation With A Single Fbg. Microwave and Optical Technology Letters, 2013, 55, 2011-2015.	0.9	0
562	Relative humidity measurement using tapered plastic fiber coated with HEC/PVDF. , 2013, , .		2
563	A Tm-Bi Co-Doped Fiber Laser with Dual Pumping Operation. Chinese Physics Letters, 2013, 30, 034204.	1.3	3
564	Comparison between the single and dual-pumping method of large mode area Yb <sup>3+</sup> /Tm <sup>3+</sup> co-doped air-clad fiber laser. , 2013, , .		0
565	A Polyaniline-Coated Integrated Microfiber Resonator for UV Detection. IEEE Sensors Journal, 2013, 13, 2020-2025.	2.4	9
566	A Passively Mode-Locked Erbium-Doped Fiber Laser Based on a Single-Wall Carbon Nanotube Polymer. Chinese Physics Letters, 2013, 30, 054210.	1.3	20
567	Graphene Oxide-Based Q -Switched Erbium-Doped Fiber Laser. Chinese Physics Letters, 2013, 30, 024208.	1.3	13
568	A Q-switched multi-wavelength Brillouin erbium fiber laser with a single-walled carbon nanotube saturable absorber. Laser Physics, 2013, 23, 055101.	0.6	11
569	Thermal Regeneration in Etched-Core Fiber Bragg Grating. IEEE Sensors Journal, 2013, 13, 2581-2585.	2.4	15
570	Stability analysis in a soliton fiber ring laser with a hybrid saturable absorber. Microwave and Optical Technology Letters, 2013, 55, 164-170.	0.9	0
571	Demonstration of microfiber hybrid Mach-Zehnder and knot resonator structure. Microwave and Optical Technology Letters, 2013, 55, 100-102.	0.9	8
572	S + C + L Band tunable wavelength conversion using FWM dual-wavelength fiber laser in a highly nonlinear fiber. Microwave and Optical Technology Letters, 2013, 55, 379-382.	0.9	1
573	Effect of loop diameter on the performance of MKR-based dual-wavelength erbium-doped fiber laser. Microwave and Optical Technology Letters, 2013, 55, 236-238.	0.9	4
574	Q-switched Zr-EDF laser using single-walled CNT/PEO polymer composite as a saturable absorber. Optical Materials, 2013, 35, 347-352.	1.7	7
575	Fiber optic salinity sensor using beam-through technique. Optik, 2013, 124, 679-681.	1.4	15
576	Fiber optic displacement sensor for scanning and reconstructing occlusal surface of human tooth. , 2013, , .		0

#	ARTICLE	IF	CITATIONS
577	A Q-switched erbium-doped fiber laser with a graphene saturable absorber. <i>Laser Physics Letters</i> , 2013, 10, 025102.	0.6	51
578	Current sensor based on inline microfiber Mach-Zehnder interferometer. <i>Sensors and Actuators A: Physical</i> , 2013, 192, 9-12.	2.0	26
579	Non-adiabatic silica microfiber for strain and temperature sensors. <i>Sensors and Actuators A: Physical</i> , 2013, 192, 130-132.	2.0	39
580	Theoretical analysis and fabrication of tapered fiber. <i>Optik</i> , 2013, 124, 538-543.	1.4	83
581	Effects of Yb/Tm Concentration and Pump Wavelength on the Performance of Ytterbium-Sensitized Thulium-Doped Fiber Laser. <i>IEEE Journal of Quantum Electronics</i> , 2013, 49, 95-99.	1.0	3
582	Compact Dual-Wavelength Laser Generation Using Highly Concentrated Erbium-Doped Fiber Loop Attached to Microfiber Coupler. <i>IEEE Journal of Quantum Electronics</i> , 2013, 49, 586-588.	1.0	7
583	Tunable graphene-based Q-switched erbium-doped fiber laser using fiber Bragg grating. <i>Journal of Modern Optics</i> , 2013, 60, 202-212.	0.6	28
584	Inline Microfiber Mach-Zehnder Interferometer for High Temperature Sensing. <i>IEEE Sensors Journal</i> , 2013, 13, 626-628.	2.4	41
585	Fiber optic displacement sensor for imaging of tooth surface roughness. <i>Measurement: Journal of the International Measurement Confederation</i> , 2013, 46, 546-551.	2.5	21
586	Detection of stain formation on teeth by oral antiseptic solution using fiber optic displacement sensor. <i>Optics and Laser Technology</i> , 2013, 45, 336-341.	2.2	5
587	Passively mode-locked erbium doped zirconia fiber laser using a nonlinear polarisation rotation technique. <i>Optics and Laser Technology</i> , 2013, 47, 22-25.	2.2	12
588	A new compact micro-ball lens structure at the cleaved tip of microfiber coupler for displacement sensing. <i>Sensors and Actuators A: Physical</i> , 2013, 189, 177-181.	2.0	18
589	Multi-wavelength Brillouin-Raman fiber laser generation assisted by multiple four-wave mixing processes in a ring cavity. <i>Laser Physics</i> , 2013, 23, 075108.	0.6	14
590	Self-Starting Harmonic Mode-Locked Thulium-Doped Fiber Laser with Carbon Nanotubes Saturable Absorber. <i>Chinese Physics Letters</i> , 2013, 30, 094204.	1.3	19
591	Wideband tunable Q-switched fiber laser using graphene as a saturable absorber. <i>Journal of Modern Optics</i> , 2013, 60, 1563-1568.	0.6	11
592	Narrow Spacing Dual-Wavelength Fiber Laser Based on Polarization Dependent Loss Control. <i>IEEE Photonics Journal</i> , 2013, 5, 1502706-1502706.	1.0	29
593	Investigation of Q-Switching Characteristics in Single- and Double-Spacing Multi-Wavelength Brillouin Erbium Fiber Laser. <i>IEEE Photonics Journal</i> , 2013, 5, 1400206-1400206.	1.0	2
594	Proposal and Performance Evaluation of an Efficient RZ-DQPSK Modulation Scheme in All-Optical OFDM Transmission Systems. <i>Journal of Optical Communications and Networking</i> , 2013, 5, 932.	3.3	14

#	ARTICLE	IF	CITATIONS
595	Demonstration of side coupling to cladding modes through zinc oxide nanorods grown on multimode optical fiber. <i>Optics Letters</i> , 2013, 38, 3620.	1.7	20
596	S-band multiwavelength Brillouin/Raman distributed Bragg reflector fiber lasers. <i>Applied Optics</i> , 2013, 52, 3753.	0.9	8
597	Highly stable graphene-assisted tunable dual-wavelength erbium-doped fiber laser. <i>Applied Optics</i> , 2013, 52, 818.	0.9	13
598	High resolution interrogation system for fiber Bragg grating (FBG) sensor application using radio frequency spectrum analyser. , 2013, , .		1
599	1.9 $\mu$ m lasing with Tm <sup>3+</sup> /Yb <sup>3+</sup> co-doped air-clad fiber and 931 nm pumping. <i>Microwave and Optical Technology Letters</i> , 2013, 55, 1124-1126.	0.9	0
600	Fibre Optic Sensors for Selected Wastewater Characteristics. <i>Sensors</i> , 2013, 13, 8640-8668.	2.1	53
601	Nanosecond pulse fibre laser based on nonlinear polarisation rotation effect. <i>Electronics Letters</i> , 2013, 49, 1240-1241.	0.5	3
602	Quantification of Mesenchymal Stem Cell Growth Rates through Secretory and Excretory Biomolecules in Conditioned Media via Fresnel Reflection. <i>Sensors</i> , 2013, 13, 13276-13288.	2.1	2
603	Temperature-Insensitive Bend Sensor Using Entirely Centered Erbium Doping in the Fiber Core. <i>Sensors</i> , 2013, 13, 9536-9546.	2.1	5
604	Demonstration of acoustic vibration sensor based on microfiber knot resonator. <i>Microwave and Optical Technology Letters</i> , 2013, 55, 1138-1141.	0.9	13
605	Mode-locked thulium-bismuth codoped fiber laser using graphene saturable absorber in ring cavity. <i>Applied Optics</i> , 2013, 52, 1226.	0.9	16
606	2.0- $\mu$ m Q-Switched Thulium-Doped Fiber Laser With Graphene Oxide Saturable Absorber. <i>IEEE Photonics Journal</i> , 2013, 5, 1501108-1501108.	1.0	59
607	Nanosecond Pulse Generation Using the Stimulated Brillouin Scattering Effect in a Photonic Crystal Fiber. <i>Chinese Physics Letters</i> , 2013, 30, 114204.	1.3	4
608	Controllable stretched pulse and dissipative soliton emission using nonlinear polarisation rotation and cavity loss tuning mechanism. <i>IET Optoelectronics</i> , 2013, 7, 38-41.	1.8	0
609	Tapered Fiber Coated with Hydroxyethyl Cellulose/Polyvinylidene Fluoride Composite for Relative Humidity Sensor. <i>Advances in Materials Science and Engineering</i> , 2013, 2013, 1-4.	1.0	4
610	Tapered Plastic Optical Fiber Coated With HEC/PVDF for Measurement of Relative Humidity. <i>IEEE Sensors Journal</i> , 2013, 13, 4702-4705.	2.4	24
611	Tunable S-band output based on Raman shift in dispersion shifted fiber. <i>Journal of Modern Optics</i> , 2013, 60, 737-740.	0.6	2
612	Brillouin erbium fiber laser generation in a figure-of-eight configuration with double brillouin frequency spacing. , 2013, , .		1

#	ARTICLE	IF	CITATIONS
613	Fiber Optic Displacement Sensor Using Multimode Plastic Fiber Probe and Tooth Surface. IEEE Sensors Journal, 2013, 13, 294-298.	2.4	11
614	Switchable pulse and multi-wavelength laser based on non-linear polarization rotation. , 2013, , .		0
615	Micro-Ball Lensed Fiber-Based Glucose Sensor. IEEE Sensors Journal, 2013, 13, 348-350.	2.4	30
616	S â€“ C â€“ L triple wavelength superluminescent source based on an ultra-wideband SOA and FBGs. Quantum Electronics, 2013, 43, 923-926.	0.3	1
617	Graphene-Based Mode-Locked Spectrum-Tunable Fiber Laser Using Machâ€“Zehnder Filter. IEEE Photonics Journal, 2013, 5, 1501709-1501709.	1.0	29
618	MULTIWAVELENGTH BRILLOUIN-ERBIUM FIBER LASER GENERATION WITH DOUBLE-BRILLOUIN-FREQUENCY SPACING IN A RING CAVITY. Journal of Nonlinear Optical Physics and Materials, 2013, 22, 1350021.	1.1	3
619	Fiber optic displacement sensor using fiber coupler probe and real objects. Sensor Review, 2012, 32, 212-216.	1.0	3
620	DC current sensing capability of microfiber Mach-Zehnder interferometer. Electronics Letters, 2012, 48, 943.	0.5	8
621	OPTICAL AMPLIFIER WITH FLAT-GAIN AND WIDEBAND OPERATION UTILIZING HIGHLY CONCENTRATED ERBIUM-DOPED FIBERS. Journal of Nonlinear Optical Physics and Materials, 2012, 21, 1250005.	1.1	3
622	Integrated Microfiber Device for Refractive Index and Temperature Sensing. Sensors, 2012, 12, 11782-11789.	2.1	61
623	Double spacing multi-wavelength L-band Brillouin erbium fiber laser with Raman pump. Journal of Modern Optics, 2012, 59, 1690-1694.	0.6	4
624	Dual-wavelength laser generation using highly concentrated erbium-doped fibre coupling with microfiber knot resonator. Electronics Letters, 2012, 48, 278.	0.5	2
625	1880-nm Broadband ASE Generation With Bismuthâ€“Thulium Codoped Fiber. IEEE Photonics Journal, 2012, 4, 2176-2181.	1.0	5
626	Four-wave mixing in zirconia-erbium doped fiber â€“ a comparison between ring and linear cavities. Laser Physics Letters, 2012, 9, 819-825.	0.6	5
627	Wideband and flat-gain amplifier based on high concentration erbium-doped fibres in parallel double-pass configuration. Quantum Electronics, 2012, 42, 241-243.	0.3	4
628	Thermal response of chalcogenide microsphere resonators. Quantum Electronics, 2012, 42, 462-464.	0.3	5
629	Feasibility of fiber optic displacement sensor scanning system for imaging of dental cavity. Journal of Biomedical Optics, 2012, 17, 071308.	1.4	4
630	Optical non-contact micrometer thickness measurement system for silica thick films. , 2012, , .		1

#	ARTICLE	IF	CITATIONS
631	S-band multiwavelength ring Brillouin/Raman fiber laser with 20 GHz channel spacing. Applied Optics, 2012, 51, 1811.	0.9	39
632	Nanosecond soliton pulse generation by mode-locked erbium-doped fiber laser using single-walled carbon-nanotube-based saturable absorber. Applied Optics, 2012, 51, 8621.	0.9	56
633	Micro-bending based optical band-pass filter and its application in S-band Thulium-doped fiber amplifier. Optics Express, 2012, 20, 29784.	1.7	9
634	Fabrication and application of zirconia-erbium doped fibers. Optical Materials Express, 2012, 2, 1690.	1.6	15
635	Broadband amplifier and high performance tunable laser with an extinction ratio of higher than 60dB using bismuth oxide-based erbium-doped fiber. Journal of Modern Optics, 2012, 59, 1106-1112.	0.6	2
636	Wideband and flat-gain amplifier using high concentration Erbium doped fibers in series double-pass configuration. , 2012, , .		1
637	Publisher's Note: Spreading profile of evaporative liquid drops in thin porous layer [Phys. Rev. E85, 016314 (2012)]. Physical Review E, 2012, 85, .	0.8	0
638	Microfiber structures and its sensor and laser applications. , 2012, , .		1
639	Spreading profile of evaporative liquid drops in thin porous layer. Physical Review E, 2012, 85, 016314.	0.8	1
640	MICROFIBER STRUCTURES FOR SENSOR APPLICATIONS. Journal of Nonlinear Optical Physics and Materials, 2012, 21, 1250003.	1.1	2
641	Comparison of linear and ring lasers of thulium-ytterbium co-doped fiber. , 2012, , .		1
642	Fiber optic displacement sensor for micro-thickness measurement. Sensor Review, 2012, 32, 230-235.	1.0	7
643	Microfibre Mach-Zehnder interferometer and its application as a current sensor. IET Optoelectronics, 2012, 6, 298-302.	1.8	8
644	Fabrication and Characterization of a 2-2 Microfiber Knot Resonator Coupler. Chinese Physics Letters, 2012, 29, 084204.	1.3	7
645	Comparison between Analytical Solution and Experimental Setup of a Short Long Ytterbium Doped Fiber Laser. Optics and Photonics Journal, 2012, 02, 65-72.	0.3	5
646	Erbium-Doped Fiber Laser With a Microfiber Coupled to Silica Microsphere. IEEE Photonics Journal, 2012, 4, 1065-1070.	1.0	3
647	Compact Brillouin Fiber Laser Based on Highly Nonlinear Fiber With 51 Double Spacing Channels. IEEE Photonics Journal, 2012, 4, 1087-1094.	1.0	16
648	Compact and Tunable Erbium-Doped Fiber Laser With Microfiber Mach-Zehnder Interferometer. IEEE Journal of Quantum Electronics, 2012, 48, 1165-1168.	1.0	11

#	ARTICLE	IF	CITATIONS
649	Fano resonance on plasmonic nanostructures. , 2012, , .		4
650	Quantitative analysis of energy transfer processes in Thuliumâ€“Bismuth germanate co-doped fiber amplifier. Optical Materials, 2012, 35, 231-239.	1.7	3
651	Compact and wide-band bismuth-based erbium-doped fibre amplifier based on two-stage and double-pass approaches. IET Optoelectronics, 2012, 6, 127.	1.8	3
652	Wideband Spectrum-Sliced ASE Source Operating at 1900-nm Region Based on a Double-Clad Ytterbium-Sensitized Thulium-Doped Fiber. IEEE Photonics Journal, 2012, 4, 14-18.	1.0	19
653	S-band gain and noise figure improvements in thulium-doped fiber amplifier by using macro-bending approach. Applied Physics B: Lasers and Optics, 2012, 108, 807-813.	1.1	4
654	Theoretical and experimental studies on coupler based fiber optic displacement sensor with concave mirror. Optik, 2012, 123, 2105-2108.	1.4	4
655	56 dB Gain EYDFA with improved noise figure with dual-stage partial double pass configuration. Optik, 2012, 123, 1884-1887.	1.4	10
656	Graphene-Oxide-Based Saturable Absorber for All-Fiber Q-Switching With a Simple Optical Deposition Technique. IEEE Photonics Journal, 2012, 4, 2205-2213.	1.0	34
657	Microfiber coupler devices. , 2012, , .		0
658	Wideband spectrum-sliced ASE source operating at 2 micron region based on double clad ytterbium-sensitized thulium-doped fiber. , 2012, , .		0
659	Add-Drop Filter Based on Microfiber Machâ€“Zehnder/Sagnac Interferometer. IEEE Journal of Quantum Electronics, 2012, 48, 1411-1414.	1.0	11
660	System tolerance of NRZ-DQPSK all-optical OFDM in long-haul transmission system using DCF. , 2012, , .		0
661	Study of Dual-Wavelength Mode Competition in an Erbium-Doped Fiber Laser (EDFL) Produced by Acoustic Waves. IEEE Journal of Quantum Electronics, 2012, 48, 1499-1504.	1.0	9
662	A new fiber optic salinity sensing device based on beam-through technique. , 2012, , .		0
663	Flat-Gain Single-Stage Amplifier Using High Concentration Erbium Doped Fibers in Single-Pass and Double-Pass Configurations. , 2012, , .		1
664	The effects of placement and geometry on thermo-pneumatic pumping on centrifugal microfluidic compact disc (CD) platforms. , 2012, , .		0
665	Direct airborne acoustic wave modulation of Fabryâ€“Perot fiber laser (FPFL) over 100ÅkHz of operating bandwidth. Applied Optics, 2012, 51, 2772.	0.9	7
666	Demonstration of DC current sensing through Microfiber Knot Resonator. , 2012, , .		1

#	ARTICLE	IF	CITATIONS
667	A Q-Switched Erbium-Doped Fiber Laser with a Carbon Nanotube Based Saturable Absorber. Chinese Physics Letters, 2012, 29, 114202.	1.3	67
668	Performance Comparison of Mode-Locked Erbium-Doped Fiber Laser with Nonlinear Polarization Rotation and Saturable Absorber Approaches. Chinese Physics Letters, 2012, 29, 054216.	1.3	20
669	Analytical Model for Broadband Thulium-Bismuth-Doped Fiber Amplifier. IEEE Journal of Quantum Electronics, 2012, 48, 1052-1058.	1.0	13
670	Passively Q-Switched 11-Channel Stable Brillouin Erbium-Doped Fiber Laser With Graphene as the Saturable Absorber. IEEE Photonics Journal, 2012, 4, 2050-2056.	1.0	4
671	Dual-cavity dual-output multi-wavelength fiber laser based on nonlinear polarization rotation effect. Laser Physics, 2012, 22, 1601-1605.	0.6	1
672	Temperature Sensing Using Frequency Beating Technique From Single-Longitudinal Mode Fiber Laser. IEEE Sensors Journal, 2012, 12, 2496-2500.	2.4	21
673	Alloying aluminum with Fe using laser induced plasma technique. Laser Physics, 2012, 22, 1364-1367.	0.6	9
674	Modeling and experimental analysis of wide-band flat-gain amplifier utilizing high concentration of EDFA. , 2012, , .		1
675	Thermally tunable microfiber knot resonator based erbium-doped fiber laser. Optics Communications, 2012, 285, 4684-4687.	1.0	5
676	Tunable single longitudinal mode S-band fiber laser using a 3â€‰m length of erbium-doped fiber. Journal of Modern Optics, 2012, 59, 268-273.	0.6	15
677	Fiber-Optic Salinity Sensor Using Fiber-Optic Displacement Measurement With Flat and Concave Mirror. IEEE Journal of Selected Topics in Quantum Electronics, 2012, 18, 1529-1533.	1.9	41
678	Fiber Optic Displacement Sensor for Temperature Measurement. IEEE Sensors Journal, 2012, 12, 1361-1364.	2.4	39
679	Upconversion luminescence in Tm <sup>3+</sup> /Yb <sup>3+</sup> co-doped double-clad silica fibers under 980â€‰nm cladding pumping. Journal of Modern Optics, 2012, 59, 527-532.	0.6	11
680	New Design of a Thulium-Aluminum-Doped Fiber Amplifier Based on Macro-Bending Approach. Journal of Lightwave Technology, 2012, 30, 3263-3272.	2.7	12
681	Broad spectral sliced multiwavelength source with a mode locked fiber laser. Laser Physics, 2012, 22, 212-215.	0.6	3
682	Multi-wavelength ytterbium doped fiber laser based on longitudinal mode interference. Laser Physics, 2012, 22, 252-255.	0.6	7
683	Wideband and compact erbium-doped fiber amplifier using parallel double-pass configuration. Microwave and Optical Technology Letters, 2012, 54, 629-631.	0.9	4
684	Generation of high power pulse of Bi-EDF and octave spanning supercontinuum using highly nonlinear fiber. Microwave and Optical Technology Letters, 2012, 54, 983-987.	0.9	3



#	ARTICLE	IF	CITATIONS
685	Passively mode-locked soliton fiber laser using a combination of saturable absorber and nonlinear polarization rotation technique. <i>Microwave and Optical Technology Letters</i> , 2012, 54, 1430-1432.	0.9	5
686	Investigation on threshold power of stimulated Brillouin scattering in photonic crystal fiber. <i>Optik</i> , 2012, 123, 1149-1152.	1.4	1
687	Synchronous tunable wavelength spacing dual-wavelength SOA fiber ring laser using Fiber Bragg grating pair in a hybrid tuning package. <i>Optics Communications</i> , 2012, 285, 1326-1330.	1.0	4
688	All fiber passively mode locked zirconium-based erbium-doped fiber laser. <i>Optics and Laser Technology</i> , 2012, 44, 534-537.	2.2	9
689	Microfiber Mach-Zehnder interferometer embedded in low index polymer. <i>Optics and Laser Technology</i> , 2012, 44, 1186-1189.	2.2	20
690	Regenerated fibre Bragg grating fabricated on high germanium concentration photosensitive fibre for sensing at high temperature. <i>Optics and Laser Technology</i> , 2012, 44, 821-824.	2.2	16
691	Supercontinuum generation using a passive mode-locked stretched-pulse bismuth-based erbium-doped fiber laser. <i>Optics and Laser Technology</i> , 2012, 44, 741-743.	2.2	2
692	Transmission characteristic of multi-turn microfiber coil resonator. <i>Optics and Laser Technology</i> , 2012, 44, 1791-1795.	2.2	5
693	Wide-band fanned-out supercontinuum source covering O-, E-, S-, C-, L- and U-bands. <i>Optics and Laser Technology</i> , 2012, 44, 2168-2174.	2.2	3
694	Tunable Radio Frequency Generation Using a Graphene-Based Single Longitudinal Mode Fiber Laser. <i>Journal of Lightwave Technology</i> , 2012, 30, 2097-2102.	2.7	8
695	Spacing-Switchable Multiwavelength Fiber Laser Based on Nonlinear Polarization Rotation and Brillouin Scattering in Photonic Crystal Fiber. <i>IEEE Photonics Journal</i> , 2012, 4, 34-38.	1.0	33
696	Graphene-Based Saturable Absorber for Single-Longitudinal-Mode Operation of Highly Doped Erbium-Doped Fiber Laser. <i>IEEE Photonics Journal</i> , 2012, 4, 467-475.	1.0	36
697	Electrically Tunable Microfiber Knot Resonator Based Erbium-Doped Fiber Laser. <i>IEEE Journal of Quantum Electronics</i> , 2012, 48, 443-446.	1.0	29
698	Enhancement of Brillouin Stokes generation in the S-band region using a combination S-band Depressed Cladding Erbium Doped Fiber and Semiconductor Optical Amplifier. <i>Laser Physics</i> , 2012, 22, 598-604.	0.6	1
699	Multi-wavelength Brillouin fiber laser generation using dual-pass approach. <i>Laser Physics</i> , 2012, 22, 584-587.	0.6	5
700	Tunable laser generation with erbium-doped microfiber knot resonator. <i>Laser Physics</i> , 2012, 22, 588-591.	0.6	14
701	Stable zirconia-erbium doped multiwavelength fiber laser by precise control of polarization states. <i>Laser Physics</i> , 2012, 22, 982-985.	0.6	3
702	Stable double spacing multiwavelength Brillouin-Erbium doped fiber laser based on highly nonlinear fiber. <i>Laser Physics</i> , 2012, 22, 977-981.	0.6	12



#	ARTICLE	IF	CITATIONS
703	Multi-wavelength fiber laser based on nonlinear polarization rotation in semiconductor optical amplifier and photonic crystal fiber. <i>Laser Physics</i> , 2012, 22, 1257-1259.	0.6	9
704	Effect of doped fiber length on the stretch pulses of a mode-locked erbium-doped fiber laser. <i>Laser Physics</i> , 2012, 22, 1240-1243.	0.6	4
705	Supercontinuum from Zr-EDF using Zr-EDF mode-locked fiber laser. <i>Laser Physics Letters</i> , 2012, 9, 44-49.	0.6	15
706	Fiber laser at 2 micron region using double-clad thulium/ytterbium co-doped yttria-alumino-silicate fiber. <i>Laser Physics Letters</i> , 2012, 9, 50-53.	0.6	12
707	Ytterbium-sensitized thulium-doped fiber laser with a single-mode output operating at 1900-nm region. <i>Chinese Optics Letters</i> , 2012, 10, 101401-101403.	1.3	9
708	An Efficient Photonic Crystal Fiber-Based Brillouin Erbium Fiber Laser Using a Fiber Bragg Grating for Multi-Wavelength Generation. <i>Fiber and Integrated Optics</i> , 2011, 30, 259-264.	1.7	2
709	Investigation of the effects of SOA locations in the linear cavity of an O-band Brillouin SOA fiber laser. <i>Journal of Modern Optics</i> , 2011, 58, 580-586.	0.6	4
710	Wavelength conversion based on FWM in a HNLF by using a tunable dual-wavelength erbium doped fibre laser source. <i>Journal of Modern Optics</i> , 2011, 58, 566-572.	0.6	5
711	Fabrication and characterization of optical microfiber structures. , 2011, , .		2
712	Microfiber-based devices: Current sensor and tunable laser. , 2011, , .		0
713	Quantum coherence effects in a Raman amplifier. <i>Journal of Modern Optics</i> , 2011, 58, 11-13.	0.6	1
714	Stable power multi-wavelength fibre laser based on four-wave mixing in a short length of highly non-linear fibre. <i>Journal of Optics (United Kingdom)</i> , 2011, 13, 075401.	1.0	5
715	S-Band Bismuth-Doped Fiber Amplifier With Double-Pass Configuration. <i>IEEE Photonics Technology Letters</i> , 2011, 23, 1860-1862.	1.3	10
716	Resonance condition of a microfiber knot resonator immersed in liquids. <i>Applied Optics</i> , 2011, 50, 5912.	2.1	40
717	Theoretical and experimental studies on concave mirror-based fiber optic displacement sensor. <i>Sensor Review</i> , 2011, 31, 65-69.	1.0	8
718	S-band multiwavelength Brillouin Raman Fiber Laser. <i>Optics Communications</i> , 2011, 284, 4971-4974.	1.0	13
719	Tapered plastic multimode fiber sensor for salinity detection. <i>Sensors and Actuators A: Physical</i> , 2011, 171, 219-222.	2.0	79
720	High output power, narrow linewidth Brillouin fibre laser master-oscillator/power-amplifier source. <i>IET Optoelectronics</i> , 2011, 5, 181-183.	1.8	4

#	ARTICLE	IF	CITATIONS
721	Low-cost spectral tunable microfibre knot resonator. IET Optoelectronics, 2011, 5, 281.	1.8	7
722	Experimental and theoretical studies on ytterbium sensitized erbium-doped fiber amplifier. Optik, 2011, 122, 1783-1786.	1.4	7
723	Temperature sensor based on fluorescence measurement of Cerium Ytterbium doped fiber. Optics and Spectroscopy (English Translation of Optika I Spektroskopiya), 2011, 111, 312-314.	0.2	3
724	Compact fiber laser at L-band region using Erbium-doped Zirconia fiber. Laser Physics, 2011, 21, 176-179.	0.6	10
725	Operation of brillouin fiber laser in the O-band region as compared to that in the C-band region. Laser Physics, 2011, 21, 210-214.	0.6	4
726	Hybrid flat gain C-band optical amplifier with Zr-based erbium-doped fiber and semiconductor optical amplifier. Laser Physics, 2011, 21, 202-204.	0.6	18
727	Multi-wavelength Brillouin fiber laser using dual-cavity configuration. Laser Physics, 2011, 21, 205-209.	0.6	24
728	Micro-displacement sensor with multimode fused coupler and concave mirror. Laser Physics, 2011, 21, 729-732.	0.6	6
729	Tunable high power fiber laser using an AWG as the tuning element. Laser Physics, 2011, 21, 712-717.	0.6	12
730	Investigation of dispersion characteristic in tapered fiber. Laser Physics, 2011, 21, 945-947.	0.6	6
731	Stable mode-locked fiber laser using 49 cm long bismuth oxide based erbium doped fiber and slow saturable absorber. Laser Physics, 2011, 21, 913-918.	0.6	6
732	High gain S-band semiconductors optical amplifier with double-pass configuration. Laser Physics, 2011, 21, 1208-1211.	0.6	3
733	Supercontinuum generation in photonic crystal fiber using femtosecond pulses. Laser Physics, 2011, 21, 1215-1218.	0.6	7
734	Highly efficient short length Bismuth-based erbium-doped fiber amplifier. Laser Physics, 2011, 21, 1793-1796.	0.6	5
735	Gain-flattened S-band depressed cladding erbium doped fiber amplifier with a flat bandwidth of 12 nm using a Tunable Mach-Zehnder Filter. Laser Physics, 2011, 21, 1633-1637.	0.6	13
736	Numerical Modelling of C-Band Bismuth-Based Erbium Doped Amplifier. , 2011, , .		0
737	Flatly broadened supercontinuum generation in nonlinear fibers using a mode locked bismuth oxide based erbium doped fiber laser. Laser Physics Letters, 2011, 8, 369-375.	0.6	55
738	Mode-locked bismuth-based erbium-doped fiber laser with stable and clean femtosecond pulses output. Laser Physics Letters, 2011, 8, 449-452.	0.6	48

#	ARTICLE	IF	CITATIONS
739	Wavelength conversion based on four-wave mixing in a highly nonlinear fiber in ring configuration. <i>Laser Physics Letters</i> , 2011, 8, 742-746.	0.6	5
740	67 cm long bismuth-based erbium doped fiber amplifier with wideband operation. <i>Laser Physics Letters</i> , 2011, 8, 814-817.	0.6	9
741	Fabrication of microfiber loop resonator-based comb filter. <i>Microwave and Optical Technology Letters</i> , 2011, 53, 1119-1121.	0.9	7
742	Investigation on stimulated Brillouin scattering effect in Photonic crystal fiber. <i>Microwave and Optical Technology Letters</i> , 2011, 53, 1450-1453.	0.9	5
743	Tunable microwave photonic frequencies generation based on stimulated Brillouin scattering operating in the L-band region. <i>Microwave and Optical Technology Letters</i> , 2011, 53, 1710-1713.	0.9	1
744	Fiber optic chemical sensor using fiber coupler probe based on intensity modulation for alcohol detection. <i>Microwave and Optical Technology Letters</i> , 2011, 53, 1935-1938.	0.9	5
745	Environment-independent liquid level sensing based on fiber-optic displacement sensors. <i>Microwave and Optical Technology Letters</i> , 2011, 53, 2451-2453.	0.9	12
746	Four-wave mixing in dual wavelength fiber laser utilizing SOA for wavelength conversion. <i>Optik</i> , 2011, 122, 754-757.	1.4	3
747	Flat and compact switchable dual wavelength output at 1060nm from ytterbium doped fiber laser with an AWG as a wavelength selector. <i>Optics and Laser Technology</i> , 2011, 43, 550-554.	2.2	10
748	0.16nm spaced multi-wavelength Brillouin fiber laser in a figure-of-eight configuration. <i>Optics and Laser Technology</i> , 2011, 43, 866-869.	2.2	61
749	Double-pass erbium-doped zirconia fiber amplifier for wide-band and flat-gain operations. <i>Optics and Laser Technology</i> , 2011, 43, 1279-1281.	2.2	13
750	Current sensor based on microfiber knot resonator. <i>Sensors and Actuators A: Physical</i> , 2011, 167, 60-62.	2.0	120
751	Non-membrane optical microphone based on longitudinal modes competition. <i>Sensors and Actuators A: Physical</i> , 2011, 168, 281-285.	2.0	10
752	Effect of Q-switched pulses exposure on morphology, hydroxyapatite composition, and microhardness properties of human enamel. <i>Journal of Laser Applications</i> , 2011, 23, 032006.	0.8	3
753	Dual-wavelength tunable fibre laser with a 15-dBm peak power. <i>Quantum Electronics</i> , 2011, 41, 709-714.	0.3	0
754	An ultra-wideband tunable multi-wavelength Brillouin fibre laser based on a semiconductor optical amplifier and dispersion compensating fibre in a linear cavity configuration. <i>Quantum Electronics</i> , 2011, 41, 602-605.	0.3	1
755	Theoretical and experimental studies on liquid refractive index sensor based on bundle fiber. <i>Sensor Review</i> , 2011, 31, 173-177.	1.0	6
756	DUAL WAVELENGTH HIGH POWER DOUBLE-CLAD ERBIUM/YTTERBIUM-DOPED FIBER LASER. <i>Journal of Nonlinear Optical Physics and Materials</i> , 2011, 20, 443-451.	1.1	0

#	ARTICLE	IF	CITATIONS
757	20 GHz Optical Combs Generation in Brillouin Fiber Laser with a Compact Ring Cavity. , 2011, , .		0
758	Fiber optical based parametric amplifier in a highly nonlinear fiber (HNLF) by using a ring configuration. Journal of Modern Optics, 2011, 58, 1065-1069.	0.6	3
759	Fabrication of optical comb filter using tapered fiber based ring resonator. Proceedings of SPIE, 2010, , .	0.8	1
760	Comparisons of multi-wavelength oscillations using Sagnac loop mirror and Mach-Zehnder interferometer for ytterbium doped fiber lasers. Laser Physics, 2010, 20, 516-521.	0.6	23
761	Bismuth-based erbium-doped fiber as a gain medium for L-band amplification and Brillouin fiber laser. Laser Physics, 2010, 20, 716-719.	0.6	60
762	Diode-pumped 1028 nm Ytterbium-doped fiber laser with near 90% slope efficiency. Laser Physics, 2010, 20, 656-660.	0.6	23
763	Estimation of metal surface roughness using fiber optic displacement sensor. Laser Physics, 2010, 20, 904-909.	0.6	18
764	Effect of tilting angles on the performance of reflective and transmitting types of fiber optic-based displacement sensors. Laser Physics, 2010, 20, 824-829.	0.6	5
765	FWM-based multi-wavelength erbium-doped fiber laser using Bi-EDF. Laser Physics, 2010, 20, 1414-1417.	0.6	30
766	Optimization of gain flattened C-band EDFA using macro-bending. Laser Physics, 2010, 20, 1433-1437.	0.6	7
767	Fabrication of tapered fiber based ring resonator. Laser Physics, 2010, 20, 1629-1631.	0.6	19
768	Highly efficient and high output power of erbium doped fiber laser in a linear cavity configuration. Laser Physics, 2010, 20, 1894-1898.	0.6	1
769	High output power Erbium-Ytterbium doped cladding pumped fiber amplifier. Laser Physics, 2010, 20, 1899-1901.	0.6	15
770	Performance comparison between plastic-based fiber bundle and multimode fused coupler as probes in displacement sensors. Laser Physics, 2010, 20, 1890-1893.	0.6	8
771	A simple linear cavity dual-wavelength fiber laser using AWC as wavelength selective mechanism. Laser Physics, 2010, 20, 2006-2010.	0.6	17
772	Investigation on stimulated Brillouin scattering characteristics in a highly doped Bismuth-based Erbium-doped fiber. Laser Physics, 2010, 20, 1973-1977.	0.6	5
773	Temperature-sensitive dual-segment polarization maintaining fiber Sagnac loop mirror. Optics and Laser Technology, 2010, 42, 377-381.	2.2	25
774	Theoretical and experimental study on the fiber optic displacement sensor with two receiving fibers. Microwave and Optical Technology Letters, 2010, 52, 373-375.	0.9	25

#	ARTICLE	IF	CITATIONS
775	Displacement sensing with two asymmetrical inclined fibers. Microwave and Optical Technology Letters, 2010, 52, 1271-1274.	0.9	9
776	Multiple Brillouin Stokes generation with bismuth-based erbium-doped fiber. Microwave and Optical Technology Letters, 2010, 52, 1416-1418.	0.9	3
777	Broadband ASE source using bismuth-based erbium-doped fibers in double-pass set-up. Microwave and Optical Technology Letters, 2010, 52, 1636-1638.	0.9	5
778	Effect of gain medium on the performance of Brillouin fiber laser. Microwave and Optical Technology Letters, 2010, 52, 2158-2160.	0.9	2
779	Brillouin fiber laser with a 49 cm long Bismuth-based erbium-doped fiber. Laser Physics Letters, 2010, 7, 60-62.	0.6	24
780	Novel O-band tunable fiber laser using an array waveguide grating. Laser Physics Letters, 2010, 7, 164-167.	0.6	19
781	Multi-wavelength fiber laser in the S-band region using a Sagnac loop mirror as a comb generator in an SOA gain medium. Laser Physics Letters, 2010, 7, 673-676.	0.6	60
782	Linear all-fiber temperature sensor based on macro-bent erbium doped fiber. Laser Physics Letters, 2010, 7, 739-742.	0.6	13
783	Enhanced bundle fiber displacement sensor based on concave mirror. Sensors and Actuators A: Physical, 2010, 162, 8-12.	2.0	21
784	A theoretical study of double-pass thulium-doped fiber amplifiers. Optik, 2010, 121, 1257-1262.	1.4	4
785	120nm wide band switchable fiber laser. Optics Communications, 2010, 283, 4333-4337.	1.0	1
786	Experimental and theoretical studies on a double-pass C-band bismuth-based erbium-doped fiber amplifier. Optics and Laser Technology, 2010, 42, 790-793.	2.2	22
787	Multi-wavelength bismuth-based erbium-doped fiber laser based on four-wave mixing effect in photonic crystal fiber. Optics and Laser Technology, 2010, 42, 1250-1252.	2.2	32
788	TEMPERATURE INSENSITIVE BROAD AND FLAT GAIN C-BAND EDFA BASED ON MACRO-BENDING. Progress in Electromagnetics Research C, 2010, 15, 37-48.	0.6	4
789	WIDE-BAND HYBRID AMPLIFIER OPERATING IN S-BAND REGION. Progress in Electromagnetics Research, 2010, 102, 301-313.	1.6	31
790	SINGLE MODE ERBIUM YTTERBIUM-DOPED FIBER LASER WITH MULTIMODE PUMPING. Journal of Nonlinear Optical Physics and Materials, 2010, 19, 203-208.	1.1	0
791	Semiconductor optical amplifier-based multi-wavelength ring laser utilizing photonic crystal fiber. Journal of Modern Optics, 2010, 57, 637-640.	0.6	8
792	O-BAND MULTI-WAVELENGTH FIBER LASER. Journal of Nonlinear Optical Physics and Materials, 2010, 19, 229-236.	1.1	2

#	ARTICLE	IF	CITATIONS
793	BRILLOUINâ€™RAMAN MULTI-WAVELENGTH LASER COMB GENERATION BASED ON <font>Bi-EDF</font> BY USING DUAL-WAVELENGTH IN DISPERSION COMPENSATING FIBER. Journal of Nonlinear Optical Physics and Materials, 2010, 19, 123-130.	1.1	5
794	Numerical study of macro bending effect on high concentration EDFA. , 2010, , .		0
795	Efficient diode pumped ytterbium-doped fibre laser. Electronics Letters, 2010, 46, 68.	0.5	4
796	Effects of Pumping Scheme and Double-Propagation on the Performance of ASE Source using Dual-Stage Bismuth-Based Erbium-Doped Fiber. Journal of Electromagnetic Waves and Applications, 2010, 24, 373-381.	1.0	4
797	O-band to C-band wavelength converter by using four-wave mixing effect in 1310â€™nm SOA. Journal of Modern Optics, 2010, 57, 2147-2153.	0.6	2
798	Dual wavelength erbium-doped fiber laser using a tapered fiber. Journal of Modern Optics, 2010, 57, 2111-2113.	0.6	21
799	Performance comparison of Zr-based and Bi-based erbium-doped fiber amplifiers. Optics Letters, 2010, 35, 2882.	1.7	38
800	Wideband EDFA Based on Erbium Doped Crystalline Zirconia Yttria Alumino Silicate Fiber. Journal of Lightwave Technology, 2010, 28, 2919-2924.	2.7	43
801	Application of macro-bending for flat and broad gain EDFA. Journal of Modern Optics, 2010, 57, 1534-1541.	0.6	1
802	Filtering characteristic of the microfiber loop resonator embedded in low refractive index polymer. , 2010, , .		1
803	Investigation on the nonlinear parameters of a photonic crystal fiber by four-wave mixing. , 2010, , .		0
804	Efficient and Compact Optical Amplifier Using EYDF. IJUM Engineering Journal, 2010, 8, 17-23.	0.5	0
805	FIBER LOOP MIRROR FILTER WITH TWO-STAGE HIGH BIREFRINGENCE FIBERS. Progress in Electromagnetics Research C, 2009, 9, 101-108.	0.6	9
806	CONTROLLABLE WAVELENGTH CHANNELS FOR MULTIWAVELENGTH BRILLOUIN BISMUTH/ERBIUM BASED FIBER LASER. Progress in Electromagnetics Research Letters, 2009, 9, 9-18.	0.4	4
807	L-BAND AMPLIFICATION AND MULTI-WAVELENGTH LASING WITH BISMUTH-BASED ERBIUM DOPED FIBER. Progress in Electromagnetics Research C, 2009, 6, 1-12.	0.6	9
808	OPTIMIZATION OF THE 1050nm PUMP POWER AND FIBER LENGTH IN SINGLE-PASS AND DOUBLE-PASS THULIUM DOPED FIBER AMPLIFIERS. Progress in Electromagnetics Research B, 2009, 14, 431-448.	0.7	16
809	Optimization of fiber length and bending Diameter in depressed cladding Erbium-doped Fiber Amplifier. , 2009, , .		2
810	THE COMPARISON NONLINEARITY BEHAVIORS OF PHOTONIC CRYSTAL FIBER BY TWO REDUCED LENGTHS OF BI-EDF IN RING CAVITY. Journal of Nonlinear Optical Physics and Materials, 2009, 18, 521-527.	1.1	4

#	ARTICLE	IF	CITATIONS
811	Design and Operation of a Concentric-Fiber Displacement Sensor. <i>Fiber and Integrated Optics</i> , 2009, 28, 301-309.	1.7	8
812	Analytical and experimental studies on asymmetric bundle fiber displacement sensors. <i>Journal of Modern Optics</i> , 2009, 56, 1838-1842.	0.6	15
813	Multiwavelength source based on SOA and EDFA in a ring cavity resonator. <i>Microwave and Optical Technology Letters</i> , 2009, 51, 110-113.	0.9	6
814	Lateral and axial displacements measurement using fiber optic sensor based on beam through technique. <i>Microwave and Optical Technology Letters</i> , 2009, 51, 2038-2040.	0.9	14
815	Multiwavelength ytterbium-doped fiber ring laser. <i>Microwave and Optical Technology Letters</i> , 2009, 51, 2511-2512.	0.9	13
816	High power and compact switchable bismuth based multiwavelength fiber laser. <i>Laser Physics Letters</i> , 2009, 6, 380-383.	0.6	58
817	Multi-wavelength Brillouin fiber laser using a holey fiber and a bismuth-oxide based erbium-doped fiber. <i>Laser Physics Letters</i> , 2009, 6, 454-457.	0.6	52
818	The performance of double-clad ytterbium-doped fiber laser with different pumping wavelengths. <i>Laser Physics Letters</i> , 2009, 6, 458-460.	0.6	19
819	Switchable semiconductor optical fiber laser incorporating AWG and broadband FBG with high SMSR. <i>Laser Physics Letters</i> , 2009, 6, 539-543.	0.6	17
820	Double-clad erbium/ytterbium-doped fiber laser with a fiber Bragg grating. <i>Laser Physics Letters</i> , 2009, 6, 586-589.	0.6	22
821	Multi-wavelength Brillouin fiber laser using Brillouin-Rayleigh scatterings in distributed Raman amplifier. <i>Laser Physics Letters</i> , 2009, 6, 737-739.	0.6	62
822	Multi-wavelength erbium-doped fiber laser assisted by four-wave mixing effect. <i>Laser Physics Letters</i> , 2009, 6, 813-815.	0.6	59
823	Tunable dual wavelength fiber laser incorporating AWG and optical channel selector by controlling the cavity loss. <i>Optics Communications</i> , 2009, 282, 4771-4775.	1.0	63
824	Flat output and switchable fiber laser using AWG and broadband FBG. <i>Optics Communications</i> , 2009, 282, 2576-2579.	1.0	10
825	Multi-wavelength generation using a bismuth-based EDF and Brillouin effect in a linear cavity configuration. <i>Optics and Laser Technology</i> , 2009, 41, 198-201.	2.2	25
826	SOA-based multi-wavelength laser using fiber Bragg gratings. <i>Laser Physics</i> , 2009, 19, 1002-1005.	0.6	31
827	1028 nm single mode Ytterbium-doped fiber laser. <i>Laser Physics</i> , 2009, 19, 1021-1025.	0.6	11
828	Simple design of optical fiber displacement sensor using a multimode fiber coupler. <i>Laser Physics</i> , 2009, 19, 1446-1449.	0.6	21



#	ARTICLE	IF	CITATIONS
829	17-channels S band multiwavelength Brillouin/Erbium Fiber Laser co-pump with Raman source. Laser Physics, 2009, 19, 2188-2193.	0.6	21
830	Compact Brillouin-erbium fiber laser. Optics Letters, 2009, 34, 46.	1.7	59
831	Multi-wavelength laser generation with Bismuth-based Erbium-doped fiber. Optics Express, 2009, 17, 203.	1.7	15
832	Stopping and storing light pulses within a fiber optic ring resonator. Chinese Optics Letters, 2009, 7, 778-780.	1.3	3
833	Dual-Wavelength Erbium Fiber Laser in a Simple Ring Cavity. Fiber and Integrated Optics, 2009, 28, 430-439.	1.7	10
834	Wide-band Bismuth based erbium doped fiber amplifier for DWDM applications. , 2009, , .		1
835	Enhancement of four wave mixing characteristic in Semiconductor Optical Amplifier using Fiber loop mirror. , 2009, , .		0
836	An efficient double-pass Bismuth-based erbium-doped fiber amplifier. , 2009, , .		0
837	Dual wavelength fibre laser with tunable channel spacing using an SOA and dual AWGs. Journal of Modern Optics, 2009, 56, 1768-1773.	0.6	6
838	Compact Bi-EDF-Based Brillouin Erbium Fiber Laser Operating at the 1560-nm Region. IEEE Photonics Journal, 2009, 1, 254-258.	1.0	13
839	Wide-Band Bismuth-Based Erbium-Doped Fiber Amplifier With a Flat-Gain Characteristic. IEEE Photonics Journal, 2009, 1, 259-264.	1.0	40
840	High Sensitivity Fiber Bragg Grating Pressure Sensor Using Thin Metal Diaphragm. IEEE Sensors Journal, 2009, 9, 1654-1659.	2.4	39
841	Bismuth erbium-doped fiber based multi-wavelength laser assisted by four-wave mixing process. IEICE Electronics Express, 2009, 6, 40-43.	0.3	8
842	An Erbium -Ytterbium DFB laser with a simple and compact structure. Journal of Physics: Conference Series, 2009, 187, 012003.	0.3	0
843	BRILLOUIN FIBER LASER WITH SIGNIFICANTLY REDUCED GAIN MEDIUM LENGTH OPERATING IN L-BAND REGION. Progress in Electromagnetics Research Letters, 2009, 8, 143-149.	0.4	17
844	High-sensitivity pressure sensor using a polymer-embedded FBG. Microwave and Optical Technology Letters, 2008, 50, 60-61.	0.9	38
845	Linear cavity Brillouin fiber laser using a fiber Bragg grating. Microwave and Optical Technology Letters, 2008, 50, 265-266.	0.9	5
846	Fiber-optic displacement sensor using a multimode bundle fiber. Microwave and Optical Technology Letters, 2008, 50, 661-663.	0.9	16

#	ARTICLE	IF	CITATIONS
847	SOA based fiber ring laser with Fiber Bragg Grating. Microwave and Optical Technology Letters, 2008, 50, 3101-3103.	0.9	4
848	A new configuration of multi-wavelength Brillouin fiber laser. Laser Physics Letters, 2008, 5, 48-50.	0.6	56
849	The performance of a fiber optic displacement sensor for different types of probes and targets. Laser Physics Letters, 2008, 5, 55-58.	0.6	50
850	A linear cavity Brillouin fiber laser with multiple wavelengths output. Laser Physics Letters, 2008, 5, 361-363.	0.6	70
851	SOA-based quad-wavelength ring laser. Laser Physics Letters, 2008, 5, 726-729.	0.6	61
852	37.2dB small-signal gain from Er/Yb Co-doped fiber amplifier with 20mW pump power. Optics and Laser Technology, 2008, 40, 88-91.	2.2	19
853	Effects of an auxiliary pump on the performance of TDFA. Laser Physics, 2008, 18, 977-982.	0.6	7
854	A linear cavity brillouin/bismuth-based erbium-doped fiber laser with enhanced characteristics. Laser Physics, 2008, 18, 1344-1348.	0.6	10
855	High-power single-wavelength SOA-based fiber-ring laser with an optical modulator. Laser Physics, 2008, 18, 1349-1352.	0.6	9
856	Gain and noise figure improvements in a shorter wavelength region of EDFA using a macrobending approach. Laser Physics, 2008, 18, 1362-1364.	0.6	15
857	Self-Calibrating Automated Characterization System for Depressed Cladding EDFA Applications Using LabVIEW Software With GPIB. IEEE Transactions on Instrumentation and Measurement, 2008, 57, 2677-2681.	2.4	12
858	Bidirectional multiwavelength Brillouin fiber laser generation in a ring cavity. Journal of Optics, 2008, 10, 055101.	1.5	37
859	Bismuth-based Brillouin/erbium fiber laser. Journal of Modern Optics, 2008, 55, 1345-1351.	0.6	14
860	Linear cavity Brillouin fiber laser with improved characteristics. Optics Letters, 2008, 33, 770.	1.7	55
861	Effects of different Raman pumping schemes on stimulated Brillouin scattering in a linear cavity. Applied Optics, 2008, 47, 3088.	2.1	13
862	All-optical Gain-clamped Erbium-doped Fiber Amplifier with Narrowband Amplified Spontaneous Emission Feedback Technique. Journal of Optical Communications, 2008, 29, .	4.0	0
863	Brillouin Erbium Ytterbium Fiber Laser. , 2008, , .		2
864	SOA-based multi-wavelength source. Journal of Modern Optics, 2008, 55, 2179-2185.	0.6	2

#	ARTICLE	IF	CITATIONS
865	COMPACT AND EFFICIENT Er <sup>3+</sup> -DOPED FIBER AMPLIFIER. Journal of Nonlinear Optical Physics and Materials, 2008, 17, 193-198.	1.1	2
866	MULTIWAVELENGTH SOURCE USING A BRILLOUIN FIBER LASER. Journal of Nonlinear Optical Physics and Materials, 2008, 17, 199-203.	1.1	7
867	Brillouin fibre laser with 20µm-long photonic crystal fibre. Electronics Letters, 2008, 44, 1065.	0.5	16
868	Shorter Wavelength Gain Shift In EDFA Using A Macro-Bending Approach. , 2008, , .		2
869	Gain improvement in a dual-stage S-band EDFA by filtration of forward C-band ASE. Journal of Modern Optics, 2008, 55, 3035-3040.	0.6	4
870	An Enhanced Bismuth-Based Brillouin/Erbium Fiber Laser with Linear Cavity Configuration. Fiber and Integrated Optics, 2007, 27, 35-40.	1.7	4
871	Inductively coupled plasma of fluorocarbon plasma glass etching process on planar lightwave circuit device fabrication. , 2007, , .		0
872	Dynamic dispersing technique for PR coating process in planar lightwave circuit fabrication. Microwave and Optical Technology Letters, 2007, 49, 1993-1995.	0.9	1
873	Highly saturated EDFA for gain clamping operation. Microwave and Optical Technology Letters, 2007, 49, 1815-1816.	0.9	2
874	An efficient EYDFA with a 54 dB small signal gain. Microwave and Optical Technology Letters, 2007, 49, 2337-2339.	0.9	0
875	New Brillouin fiber laser configuration with high output power. Microwave and Optical Technology Letters, 2007, 49, 2656-2658.	0.9	9
876	An overview on S-band erbium-doped fiber amplifiers. Laser Physics Letters, 2007, 4, 10-15.	0.6	70
877	Multiwavelength Brillouin/Erbium-Ytterbium fiber laser. Laser Physics Letters, 2007, 4, 601-603.	0.6	71
878	Multiple wavelength Brillouin fiber laser from injection of intense signal light. Laser Physics Letters, 2007, 4, 678-680.	0.6	62
879	An efficient S-band brillouin erbium fiber laser with additional EDFA. Optics and Laser Technology, 2007, 39, 616-618.	2.2	3
880	Gain and noise figure improvements in double-pass S-band EDFA. Optics and Laser Technology, 2007, 39, 935-938.	2.2	9
881	Effects of output coupler reflectivity on the performance of a linear cavity Brillouin/erbium fiber laser. Pramana - Journal of Physics, 2007, 68, 451-456.	0.9	1
882	Self-excited brillouin erbium fiber laser for DWDM applications. Optics and Laser Technology, 2007, 39, 94-97.	2.2	7

#	ARTICLE	IF	CITATIONS
883	Dual-stage Er/Yb doped fiber amplifier for gain and noise figure enhancements. IEICE Electronics Express, 2006, 3, 517-521.	0.3	15
884	Gain-clamping techniques in two-stage double-pass L-band EDFA. Pramana - Journal of Physics, 2006, 66, 539-545.	0.9	5
885	A linear cavity S-band Brillouin/Erbium fiber laser. Laser Physics Letters, 2006, 3, 369-371.	0.6	59
886	An efficient multiwavelength light source based on ASE slicing. Laser Physics Letters, 2006, 3, 495-497.	0.6	35
887	An efficient gain-flattened C-band Erbium-doped fiber amplifier. Laser Physics Letters, 2006, 3, 536-538.	0.6	57
888	S-BAND BRILLOUIN/ERBIUM FIBER LASER FOR DWDM APPLICATION. Journal of Nonlinear Optical Physics and Materials, 2006, 15, 309-313.	1.1	5
889	DOUBLE PASS S-BAND EDFA. Journal of Nonlinear Optical Physics and Materials, 2006, 15, 303-307.	1.1	0
890	An efficient S-band erbium-doped fiber amplifier using double-pass configuration. IEICE Electronics Express, 2005, 2, 182-185.	0.3	60
891	Gain control in S-band erbium-doped fiber amplifier using a fiber bragg grating. IEICE Electronics Express, 2005, 2, 186-191.	0.3	2
892	An enhanced S-band brillouin/erbium fiber laser with an additional EDFA in sub-loop. IEICE Electronics Express, 2005, 2, 321-326.	0.3	2
893	Gain-clamped double-pass S-band erbium-doped fiber amplifier. IEICE Electronics Express, 2005, 2, 595-599.	0.3	1
894	Gain enhancement in partial double-pass L-band EDFA system using a band-pass filter. Laser Physics Letters, 2005, 2, 36-38.	0.6	22
895	S-band erbium-doped fiber ring laser using a fiber Bragg grating. Laser Physics Letters, 2005, 2, 369-371.	0.6	51
896	Effect of doped-fiber's spooling on performance of S-band EDFA. Laser Physics Letters, 2005, 2, 412-414.	0.6	10
897	Two-stage S-band erbium-doped fiber amplifier using a depressed-cladding fiber. Microwave and Optical Technology Letters, 2005, 46, 92-94.	0.9	2
898	A Partial Double-Pass S-Band Erbium-Doped Fibre Amplifier. Chinese Physics Letters, 2005, 22, 3080-3082.	1.3	3
899	S-band Brillouin erbium fibre laser. Electronics Letters, 2005, 41, 174.	0.5	51
900	Enhancement of Gain in L-Band Bismuth-Based Erbium-Doped Fibre Amplifier Using an Un-pumped EDF and Midway Isolator. Chinese Physics Letters, 2004, 21, 2452-2453.	1.3	0

#	ARTICLE	IF	CITATIONS
901	Tunable and Low Noise Gain-Clamped Double-Pass L-Band Erbium-Doped Fiber Amplifier. Japanese Journal of Applied Physics, 2004, 43, L1075-L1077.	0.8	2
902	Gain Clamped Two-Stage Double-Pass L-Band EDFA with a Single Fibre Bragg Grating. Chinese Physics Letters, 2004, 21, 1954-1957.	1.3	3
903	Gain-Clamped Double-Pass L-Band Erbium-Doped Fiber Amplifier Using A Ring Laser and Fiber Bragg Grating. Japanese Journal of Applied Physics, 2004, 43, L924-L926.	0.8	2
904	Effect of Recycling a Backward Ase on Performance of Double Pass L-Band Edfa. Journal of Optics (India), 2004, 33, 181-186.	0.8	0
905	L-BAND EDFA WITH INJECTION OF C-BAND ASE. Journal of Nonlinear Optical Physics and Materials, 2004, 13, 315-319.	1.1	0
906	Gain control in double-pass L-band EDFA using a ring resonator and two-stage configuration. Optik, 2004, 115, 525-527.	1.4	3
907	Gain clamping in double-pass L-band EDFA using a broadband FBG. Pramana - Journal of Physics, 2004, 62, 893-897.	0.9	0
908	Comparison of performances between partial double-pass and full double-pass systems in two-stage L-band EDFA. Laser Physics Letters, 2004, 1, 610-612.	0.6	27
909	Efficient and low-noise gain-flattened double-pass L-band erbium-doped fiber amplifier. Microwave and Optical Technology Letters, 2004, 40, 112-114.	0.9	3
910	L-band gain clamped erbium-doped fiber amplifier incorporating a C/L-band WDM coupler. Microwave and Optical Technology Letters, 2004, 40, 314-316.	0.9	1
911	Gain clamped double-pass L-band EDFA with incorporation of FBG at the input end of the optical amplifier. Microwave and Optical Technology Letters, 2004, 43, 166-168.	0.9	1
912	Gain clamping in double-pass L-band EDFA using a ring resonator. Microwave and Optical Technology Letters, 2004, 43, 484-486.	0.9	1
913	Low noise double pass L-band erbium-doped fiber amplifier. Optics and Laser Technology, 2004, 36, 245-248.	2.2	13
914	Partial gain-clamping in two-stage double-pass L-band EDFA using a ring resonator. , 2004, , .		2
915	Gain Clamping in Two-Stage L-Band EDFA Using a Broadband FBG. IEEE Photonics Technology Letters, 2004, 16, 422-424.	1.3	20
916	ASE Spectral Slice Gain-Clamping of EDFA. IEEE Photonics Technology Letters, 2004, 16, 2604-2606.	1.3	2
917	All-Optical Gain Clamped Double-Pass L-Band EDFA Based on Partial Reflection of ASE. IEICE Electronics Express, 2004, 1, 171-175.	0.3	1
918	An efficient and low noise Gain-Clamped Double-Pass L-Band EDFA. IEICE Electronics Express, 2004, 1, 98-102.	0.3	6

#	ARTICLE	IF	CITATIONS
919	Effect of coupling ratio on performance of self-excited Brillouin/erbium fiber laser. IEICE Electronics Express, 2004, 1, 460-464.	0.3	0
920	High gain L-band erbium-doped fiber amplifier with two-stage double-pass configuration. Pramana - Journal of Physics, 2003, 61, 93-97.	0.9	2
921	10-GHz Optical Comb in L-Band Region With Brillouin/Erbium-Doped Fibre Laser. Optical Review, 2003, 10, 133-135.	1.2	0
922	Gain and noise performances of an L-band EDFA utilizing a ring laser cavity with fiber Bragg grating. Microwave and Optical Technology Letters, 2003, 36, 1-2.	0.9	1
923	Gain improvement in L-band EDFA using unpumped EDF in a double pass system. Microwave and Optical Technology Letters, 2003, 36, 154-156.	0.9	8
924	Gain clamped L-band EDFA using a fiber Bragg grating in two stage configuration. Microwave and Optical Technology Letters, 2003, 37, 265-266.	0.9	3
925	Gain-clamping in two-stage L-band EDFA using an unwanted backward ase from second stage. Optics and Laser Technology, 2003, 35, 441-444.	2.2	6
926	Gain-clamped two-stage L-band EDFA with a FBG laser in second stage. Optics and Laser Technology, 2003, 35, 645-647.	2.2	4
927	Effect of injection of C-band ASE on L-band erbium-doped fiber amplifier. JETP Letters, 2003, 77, 461-463.	0.4	3
928	Double-pass L-band EDFA with enhanced noise figure characteristics. IEEE Photonics Technology Letters, 2003, 15, 1055-1057.	1.3	64
929	L-band erbium-doped fibre amplifier with clamped- and flattened-gain using FBG. Electronics Letters, 2003, 39, 1238.	0.5	12
930	Dual-Stage L-Band Erbium-Doped Fiber Amplifier for Gain Enhancement. Japanese Journal of Applied Physics, 2003, 42, L173-L175.	0.8	5
931	A New Gain-Clamped L-Band Erbium-Doped Fiber Amplifier with Highly Efficient Gain. Japanese Journal of Applied Physics, 2003, 42, L930-L931.	0.8	5
932	Gain-Clamped L-Band Erbium-Doped Fiber Amplifier with Co- and Counter-Propagating Lasers. Japanese Journal of Applied Physics, 2003, 42, L1262-L1264.	0.8	2
933	Gain and Noise Figure Improvements in Double Pass L-band EDFA using a Band-pass Filter. Journal of Optical Communications, 2002, 23, .	4.0	2
934	Multiwavelength Laser Comb in L-Band Region with Dual-Cavity Brillouin/Erbium Fiber Laser. Japanese Journal of Applied Physics, 2002, 41, L1234-L1236.	0.8	17
935	Highly Efficient L-Band Erbium-Doped Fiber Amplifier with Unpumped Erbium-Doped Fiber in Double Pass Configuration. Japanese Journal of Applied Physics, 2002, 41, L833-L835.	0.8	0
936	Gain Control in L-Band Erbium-Doped Fiber Amplifier Using a Ring Resonator. Japanese Journal of Applied Physics, 2002, 41, L332-L333.	0.8	14

#	ARTICLE	IF	CITATIONS
937	A Gain-Clamped L-Band Erbium-Doped Fiber Amplifier Using Ring Laser Cavity with a Fiber Bragg Grating. Japanese Journal of Applied Physics, 2002, 41, L836-L838.	0.8	7
938	Gain Control in L-Band Erbium-Doped Fiber Amplifier Incorporating Broadband Fiber Bragg Grating. Japanese Journal of Applied Physics, 2002, 41, L1459-L1460.	0.8	0
939	Gain clamping in L-band erbium-doped fiber amplifier using a fiber Bragg grating. IEEE Photonics Technology Letters, 2002, 14, 293-295.	1.3	69
940	Gain enhancement in L-band EDFA through a double-pass technique. IEEE Photonics Technology Letters, 2002, 14, 296-297.	1.3	86
941	Gain enhancement in L-band EDFA using a fiber Bragg grating. Microwave and Optical Technology Letters, 2002, 32, 388-390.	0.9	1
942	Hybrid Brillouin/Erbium fibre laser operating at long wavelength band. Microwave and Optical Technology Letters, 2002, 33, 383-385.	0.9	0
943	Efficient multiwavelength generation of Brillouin/erbium fiber laser at 1600-nm region. Microwave and Optical Technology Letters, 2002, 35, 506-508.	0.9	13
944	Double Pass L-Band EDFA with Unpumped EDF. , 2002, , .		1
945	All-optical gain-clamped erbium-doped fiber-ring lasing amplifier with laser filtering technique. IEEE Photonics Technology Letters, 2001, 13, 785-787.	1.3	35
946	Gain-clamped erbium-doped fiber amplifier using a single fiber Bragg grating. Microwave and Optical Technology Letters, 2001, 29, 290-293.	0.9	0
947	Gain flattening and clamping in L-band ring EDFA incorporating fiber Bragg grating. , 0, , .		1
948	Double pass L-band EDFA incorporating band pass filter. , 0, , .		2
949	Double pass L-band EDFA with an improved gain coefficient. , 0, , .		0
950	Gain clamping in dual-stage L-band EDFA by recycling a backward ASE. , 0, , .		0
951	Two-stage L-band erbium doped fiber amplifier. , 0, , .		0
952	Gain clamping in double-pass L-band EDFA. , 0, , .		1
953	Double-pass L-band EDFA with flat-gain and improved noise figure characteristic. , 0, , .		1
954	A compact O-plus C-band switchable quad-wavelength fiber laser using arrayed waveguide grating. Laser Physics Letters, 0, 7, 597-602.	0.6	17



#	ARTICLE	IF	CITATIONS
955	Microfiber loop resonator based temperature sensor. Journal of the European Optical Society-Rapid Publications, 0, 6, .	0.9	44
956	Four-Wave-Mixing in Zirconia-Yttria-Aluminum Erbium Codoped Silica Fiber. Journal of the European Optical Society-Rapid Publications, 0, 7, .	0.9	7
957	Tunable, low frequency microwave generation from AWC based closely-spaced dual-wavelength single-longitudinal-mode fibre laser. Journal of the European Optical Society-Rapid Publications, 0, 8, .	0.9	11
958	Dual wavelength single longitudinal mode Ytterbium-doped fiber laser using a dual-tapered Mach-Zehnder interferometer. Journal of the European Optical Society-Rapid Publications, 0, 10, .	0.9	9
959	Flat-gain wide-band erbium doped fiber amplifier by combining two difference doped fibers. Journal of the European Optical Society-Rapid Publications, 0, 10, .	0.9	5
960	Passive Q-switched and Mode-locked Fiber Lasers Using Carbon-based Saturable Absorbers. , 0, , .		7
961	Photon-to-photon polarization modulation using Mxene thin film as modulator. Electronics Letters, 0, , .	0.5	1
962	Tungsten disulfide coated side-polished fibre as polarisation state modulator in all-optical system. IET Optoelectronics, 0, , .	1.8	1
963	Titanium Carbide MXene as a Mode Locker in Erbium-Doped Fiber Laser Cavity. Journal of Russian Laser Research, 0, , .	0.3	1
964	Q-Switched Fiber Laser with a Hafnium-Bismuth-Erbium Codoped Fiber as Gain Medium and Sb <sub>2</sub> Te <sub>3</sub> as Saturable Absorber. Journal of Russian Laser Research, 0, , .	0.3	1